

APPLICATION

WESTCIDE 758 is used in industrial, commercial and institutional recirculating cooling water towers to control the growth of algae and fungi. Begin treatment when the system is in jeopardy of becoming badly affected or after cleaning systems whose efficiency is already impaired. Apply at a point in the system where the product will be uniformly mixed.

For continuous feed methods:

Initial Dose: When the system is just noticeably fouled, apply 15.7 to 31.4 fluid ounces of WESTCIDE 758 per 1000 gallons of water in the system.

Subsequent Dose: Maintain this treatment level by starting a continuous feed of no less than 5.4 fluid ounces of WESTCIDE 758 per 1000 gallons of water lost by blow-down. Badly fouled systems must be cleaned before treatment is begun.

For intermittent feed methods:

Initial Dose: When the system is noticeably fouled, apply 15.7 to 31.4 fluid ounces of WESTCIDE 758 per 1000 gallons of water in the system. Repeat until control is achieved.
Subsequent Dose: When microbial control is evident, add 5.4 to 31.4 fluid ounces of WESTCIDE 758 per 1000 gallons of water in the system every one to five days, or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

WESTCIDE 758 does not cause foaming and may therefore be added by slug additions at maximum application levels.

WESTCIDE 758

Algaecide

ACTIVE INGREDIENTS	4.20% by weight
Disodium cyanodithioimidocarbonate	1.76%
Potassium N-methyldithiocarbamate	2.44%
INERT INGREDIENTS	95.80% by weight
Weight per gallon	8.55 pounds
Weight of active ingredients per gallon	.36 pounds

See right side panel for additional precautionary and first aid statements.

WARNING
KEEP OUT OF REACH OF CHILDREN

EPA Registration No. 11712-11
EPA Establishment No. 11712GA01

Net Weight _____ Gallons

ACCEPTED
NOV 19 1975
UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTERED
ED UNDER NO. 11712-11

WARNING

Causes eye damage and skin irritation. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food.

FIRST AID: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse.

If swallowed, give patient doses of powdered charcoal immediately or all he can swallow of raw egg white, milk, gruel, or flour and water. Then induce vomiting with salt, soap or mustard in warm water. Call a physician immediately.

Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water.

Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on label.

Manufactured for

WEST CHEMICAL & ENGINEERING CO., INC.

1355 ELLSWORTH INDUSTRIAL DRIVE, NW

ATLANTA, GEORGIA 30318