

KEM-CIDE

ACCEPTED

AUG - 1972

APPLICATION

KEM-CIDE is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 3.9 to 7.5 fluid ounces of KEM-CIDE per 1000 gallons of water to provide a concentration of 32 to 80 parts per million of KEM-CIDE based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 1.0 to 9.75 fluid ounces of KEM-CIDE per 1000 gallons of water (8 to 80 parts per million of KEM-CIDE) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

COMPOSITION

	Percent by weight
Active ingredient	15.0 percent
Polyoxyethylene (dimethyliminio)ethylene (dimethyliminio)ethylene dichloride	15.0 percent
Inert ingredient	85.0 percent
Weight per gallon	8.58 pounds
Weight of active ingredient per gallon	1.29 pound

CAUTION

KEEP OUT OF THE REACH OF CHILDREN

Harmful if swallowed. Avoid contact with skin and eyes. In case of contact flush with plenty of water for at least 15 minutes. If eye irritation persists get medical attention. Avoid contamination of food.

This product is toxic to fish. Do not add treated effluent to lakes, streams, or ponds. Do not contaminate water by cleaning of equipment or disposal of waste. Use only as directed on label. Do not reuse container. Destroy when empty.

EPA Registration No. 11738-1

NET CONTENTS

GALS.

CHEMICAL WATER TREATING ENGINEERS, INC.

4022 Worth Street
Dallas, Texas 75246