



CLEAN CROP[®]

GRAIN PRESERVER

AN INHIBITOR FOR CONTROL OF MOLDS AND FUNGI IN HIGH-MOISTURE STORED CORN, CATS, BARLEY, WHEAT OR SORGHUM TO BE USED AS LIVESTOCK FEED.

DIRECTIONS FOR USE

1. Determine moisture content of corn, cats, barley, wheat or sorghum.
2. Apply SENTRY Grain Preserver to freshly harvested grain based on moisture content according to the following table.

Moisture Content of Grain % by Weight	U.S. Gallons of Grain Preserver Per Ton of Moist Grain	Pounds of Grain Preserver Per Ton of Moist Grain
16	1.33	11
18	1.57	13
20	1.81	15
22	2.05	17
24	2.29	19
26	2.54	21
28	2.78	23
30	3.02	25
32	3.26	27
34	3.50	29
36	3.74	31

3. Apply preserver to remove through mixing and coverage of grain.
4. Use of auger is recommended to convey grain to storage.
5. Eliminate feed dust from circulation. Waterproof floor of storage area.
6. Store metal surfaces in storage area with polyethylene or polyvinyl chloride sheeting.
7. Paint metal surfaces with suitable anticorrosive paint.

NET WT. 437 LBS.
NET VOL. 52.9 GALS. (U.S.)

Manufactured For
MIDWEST AGRICULTURAL WAREHOUSE CO.
FREMONT, NEBRASKA 68025

Active Ingredient: Propionic Acid 100%

CAUTION: KEEP OUT OF REACH OF CHILDREN

DANGER: Liquid causes eye injuries and skin burns. Do not get on skin, in eyes, or on clothing. Evolving vapors may be harmful. Avoid breathing vapors or mist. Harmful if swallowed. In case of contact with eyes or skin, immediately flush with plenty of water for at least 15 minutes. For eyes, get medical attention. Remove contaminated clothing and shoes at once. Wash thoroughly before reuse.

COMBUSTIBLE: Keep away from heat, sparks and fire. Do not leave container open.

WARRANTY:

1. The manufacturer warrants that the material is as described and that the net weight is as stated within 1/10% tolerance. The directions are based on responsible experts' evaluation of real-world conditions of use and on results of field experience. All other warranties are void with respect to the experts' evaluation of the individual ingredients of the material hereon.
2. The manufacturer makes no authorized agent or representative to make any other warranty, including warranty of FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, guarantee, or representation, express or implied, regarding the material. Time and method of application, weather, and conditions, and other factors for which the manufacturer, or the manufacturer's agent or representative, or the buyer, that buyer assumes all risks of application, which result in loss or damage, and which are beyond manufacturer's control. No claim of any kind and without limitation of remedy shall be in greater amount than the purchase price of the material in respect of which the manufacturer's agent or representative shall be liable for special, indirect or consequential damage resulting from the use of this material.
3. No other terms of this warranty and disclaimer shall exist, except by specific reference to them in writing by an employee of the manufacturer.

RINSE EMPTY CONTAINER THOROUGHLY WITH WATER. DO NOT REUSE. RETURN TO DRUM CONDITIONER OR DESTROY.

FWA 800-1-1000