

4643-40

DEARCIDE 702

26 FEB 1980

CONTROLS BACTERIA, ALGAE AND FUNGI IN INDUSTRIAL RE
CIRCULATING WATER COOLING TOWERS, AND BACTERIA AND
FUNGI IN METALWORKING FLUIDS

Active Ingredients:
6-Chloro-3-methyl-4-isothiazole-3-one 1.19%
2-Methyl-4-isothiazole-3-one 8.35%
Inert Ingredients 90.46%

EPA Reg. No. 4925-40
EPA Est. No. 4925-AL-1
Net Weights: 495 lbs (95 gal drum)
245 lbs (50 gal drum)
41 lbs (8 gal pail)

DANGER: KEEP OUT OF REACH OF CHILDREN PRECAUTIONARY STATEMENTS

Hazards to Humans and Domestic Animals
CORROSIVE. CAUSES EYE DAMAGE AND SKIN BURNS
MAY CAUSE ALLERGIC SKIN REACTION. MAY BE HARM-
FUL IF INHALED. MAY BE FATAL IF SWALLOWED OR
ABSORBED THROUGH THE SKIN. DO NOT GET IN EYES,
ON SKIN, OR CLOTHING. WEAR GOGGLES ON FACE
SHIELD AND RUBBER GLOVES WHEN HANDLING. AVOID
BREATHING VAPOR OR MIST. AVOID CONTAMINATION
OF FOOD. DO NOT TAKE INTERNALLY. WASH THOR-
OUGHLY AFTER HANDLING.

STATEMENT OF PRACTICAL TREATMENT FIRST AID

IF SWALLOWED: Do not induce vomiting. Drink
promptly a large quantity of milk, egg whites, gelatin
solution or if these are not available, drink large
quantities of water. Avoid alcohol. Call a physician
immediately.
IF INHALED: Remove immediately to fresh air. If not
breathing, apply artificial respiration. If breathing is
difficult, give oxygen and call a physician.
IF ON SKIN: Wash thoroughly with soap and water.
Remove and wash contaminated clothing before
reuse.
IF IN EYES: Flush with plenty of water for at least 15
minutes. Call a physician.

NOTE TO PHYSICIAN: Probable mucosal damage may
contraindicate the use of gastric lavage. Measures
against circulatory shock, respiratory depression and
convulsions may be needed.

ENVIRONMENTAL HAZARDS: This pesticide is toxic
to fish and wildlife. Do not discharge treated effluent
into lakes, streams, ponds, or public waters unless in
accordance with a EPCOS Regional Office of the EPA.
Do not contaminate water by cleaning of equipment or
disposal of waste. Apply this product only as specified
on this label.

DIRECTIONS FOR USE (Continued)
INDUSTRIAL RECIRCULATING WATER COOLING
TOWERS: INITIAL DOSE: When the system is noticeably
fouled apply 2.45 to 1.58 lbs (37 to 113 fluid ounces) of
DEARCIDE 702 per 1000 gallons of water in the system.
Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident,
add 1.26 to 1.88 lbs (19 to 28 fluid ounces) of DEARCIDE 702
per 1000 gal. of water in the system weekly or as needed to
maintain control. Badly fouled systems must be cleaned before
treatment is begun. DEARCIDE 702 weighs 8.4 lbs per gallon.

NOTICE: Seller warrants that the product conforms to its chemical
description and is reasonably fit for the purposes stated on the label when
used in accordance with directions under normal conditions of use, but
neither this warranty nor any other warranty of MERCHANTABILITY
OF FITNESS FOR A PARTICULAR PURPOSE, express or implied,
extends to the use of this product contrary to label instructions or under
abnormal conditions, or under conditions not reasonably foreseeable to
seller. Buyer assumes the risk of any such use.

d EARBORN CHEMICAL (U.S.)
CHEMED CORPORATION
100 GENESEE STREET • LAKE ZURICH, ILL. • 60057

CORROSIVE LIQUID N.O.R.
27

27-6