

Sol-Vet 421 X

**A BACTERIOSTAT AND ALGAEICIDE
FOR THE CONTROL OF BACTERIAL
SLIMES AND ALGAE IN OPEN
RECIRCULATING COOLING SYSTEMS**

ACTIVE INGREDIENT: 15% by weight
POLY [OXYETHYLENE (DIMETHYLIMINIO) ETHYLENE
(DIMETHYLIMINIO) ETHYLENEDICHLORIDE] 15% by weight
INERT INGREDIENT: 85.0% by weight
Weight per gallon 8.58 pounds
Weight of active ingredient per gallon 1.29 pounds

CAUTION: KEEP OUT OF REACH OF CHILDREN.

Harmful if swallowed. Avoid contact with skin and eyes. In case of eye contact, flush with plenty of water for at least 15 minutes.

If eye irritation persists get medical attention.

Avoid contamination of food.

This product is toxic to fish. Do not add treated effluent to lakes, streams or ponds.

Do not contaminate water by cleaning of equipment or disposal of waste.

Use only as directed on label.



**ANDERSON
CORPORATION
1733 WALNUT
KANSAS CITY,**

INDUSTRIAL WATER

DIRECTIONS FOR USE: Sol-Vet 421X is used to control algal growth in circulating commercial and industrial water cooling towers. Prior to use, clean towers to remove algal growth, microbiological slime and other deposits. Add 3.9 to 9.75 fluid ounces of Sol-Vet 421X per 1000 gallons of water. A concentration of 32 to 80 parts per million of Sol-Vet 421X based on total water in the system is recommended. Repeat if necessary until control is evident. A concentration of 1.0 to 9.75 fluid ounces of Sol-Vet 421X per 1000 gallons of water (1.0 to 9.75 million of Sol-Vet 421X) should be employed every two to five days. Frequency of addition depends upon the relative amount of bleedoff and the severity of the problem. Slug additions should be made in the sump of cooling towers.

EPA Registered

12016-2
with comments

21 X

**D ALGAECIDE
OF BACTERIAL
E IN OPEN
ING SYSTEMS**

..... 15% by weight
ETHYLENE
E] 15% by weight
..... 85.0% by weight
..... 8.58 pounds
..... 1.29 pounds

H OF CHILDREN.

and eyes. In case of eye contact,
utes.

treated effluent to lakes, streams

quipment or disposal of waste.

12016-2
with comments



**ANDERSON-STOLZ
CORPORATION**

**1733 WALNUT STREET
KANSAS CITY, MO. 64108**

INDUSTRIAL WATER TREATMENTS

DIRECTIONS FOR USE: Sol-Vet 421X is used to control algae, bacteria and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 3.9 to 9.75 fluid ounces of Sol-Vet 421X per 1000 gallons of water, to provide a concentration of 32 to 80 parts per million of Sol-Vet 421X based on the total weight of water in the system is recommended. Repeat if necessary until control is evident. Subsequent slug additions of 1.0 to 9.75 fluid ounces of Sol-Vet 421X per 1000 gallons of water (8 to 80 parts per million of Sol-Vet 421X) should be employed every two to five days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the microbiological problem. Slug additions should be made in the sump of cooling towers.

EPA Registration No. 12016-2

ACCEPTED WITH COMMENTS