

ACCEPTED

10/31/72

REG. NO. _____
EPA REG. NO. _____
12473-3
SUBJECT _____
COMMENTS _____

CARBICIDE G

COMPOSITION

Percent by weight

ACTIVE INGREDIENT: 18.0 percent

poly [oxyethylene (dimethyliminio) ethylene
(dimethyliminio)-ethylene dichloride] 18.0 percent

INERT INGREDIENT: 82.0 percent

Weight per gallon 8.65 pounds

Weight of active ingredient per gallon 1.56 pound

APPLICATION

CARBICIDE G is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 3.3 to 8.2 fluid ounces of CARBICIDE G per 1000 gallons of water, to provide a concentration of 27 to 66 parts per million of CARBICIDE G based on the total weight of water in the system is recommended. Repeat until control is achieved. Subsequent slug additions of 0.82 to 8.2 fluid ounces of CARBICIDE G per 1000 gallons of water (6.6 to 66 parts per million of CARBICIDE G) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

CAUTION

KEEP OUT OF REACH OF CHILDREN.

Harmful if swallowed. Avoid contact with skin and eyes. In case of contact flush with plenty of water for at least 15 minutes. If eye irritation persists get medical attention. Avoid contamination of food.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Do not contaminate water by cleaning of equipment or disposal of waste. Use only as directed on label. Do not reuse container. Destroy when empty.

Carbon Solvents Laboratories, Inc.

Kenilworth, New Jersey 07033

EPA Reg. No. 12473-3