

CP-100

COMPOSITION

ACCEPTED
 August 13, 1974
 UNDER THE FEDERAL INSECTICIDE
 FUNGICIDE AND RODENTICIDE
 ACT FOR REGISTRATION OF PESTICIDES
 EP A UNDER NO. 12477-1

Active ingredient	30.0 percent
Polyoxyethylene(dimethylamino)ethylene(dimethylamino)- ethylene dichloride].....	30.0 percent
Inert ingredient	10.0 percent
Weight per gallon	6.76 pounds
Weight of active ingredient per gallon	2.03 pounds

APPLICATION:

CP-100 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 2.0 to 5.0 fluid ounces of CP-100 per 1000 gallons of water to provide a concentration of 16 to 40 parts per million of CP-100 based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 0.5 to 5.0 fluid ounces of CP-100 per 1000 gallons of water (4 to 40 parts per million of CP-100) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of biocontrol and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

CAUTION:

KEEP OUT OF REACH OF CHILDREN. FOR INDUSTRIAL USE ONLY.

Hazardal if swallowed. Do not get in eyes. Avoid contact with skin. In case of contact, flush with plenty of water for at least 15 minutes. If eye irritation persists, get medical attention. Avoid contamination of food.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds or public water. Do not contaminate water by cleaning of equipment or disposal of wastes. Use only as directed on label.

Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

MANUFACTURED BY
 ECONOMY SERVICE & SALES CO.
 3511 N. 9th Street
 Philadelphia, Pennsylvania 19140
 EPA Reg. No. 12477-1