

MICRO-BIOCIDE 960

April 16, 1973

COMPOSITION

Percent by weight

Poly [oxyethylene (dimethyliminio) ethylene (dimethyliminio) - ethylene dichloride]	6.0 percent
Inert ingredient	94.0 percent
Weight per gallon	8.43 pounds
Weight of active ingredient per gallon51 pound

APPLICATION

Micro-Biocide 960 is used to control algae, bacteria and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 10.52 to 25.25 fluid ounces of Micro-Biocide 960 per 1000 gallons of water, to provide a concentration of 5 to 12 parts per million of active ingredient is recommended. Subsequent slug additions of 2.1 to 25.25 fluid ounces of Micro-Biocide 960 per 1000 gallons of water to provide 1 to 12 parts per million of active ingredient. This should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers. Repeat until control is achieved.

CAUTION

KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. Avoid contact with skin and eyes. In case of contact, flush with plenty of water for at least 15 minutes. If eye irritation persists get medical attention. Avoid contamination of food.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public waters. Do not contaminate water by cleaning of equipment or disposal of waste. Use only as directed on label.

Do not reuse container. Destroy when empty.

**Norman Chemical Company
1630 Carroll Ave.
St. Paul, Minnesota 55104**

CONTROL—
EPA Reg. No. 12488-1

NET CONTENTS