

SINCE 1904

WATER TREATMENT SPECIALISTS

))

ALGAE-SLIME TREATMENT

ACCEPTED

OCT 17 1975

UNDER THE FEDERAL INSECTICIDE FUNCIONE AND RODENTICIDE ACT POR ECONOMIC POISON REGISTED ED UNDER NO. 3 604 L

METLA-COTA 959A

E.P.A. REG. NO. 13604-4

COMPOSITION

WARNING KEEP OUT OF REACH OF CHILDREN

Causes eye damage and skin irritations. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of foods.

FIRST AID: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash clothing before re-use.

If swallowed, give patient doses of powdered charcoal immediately or all he can swallow of raw egg whites, milk, gruel, or flour and water.

Then, induce vomiting with salt, soap, or mustard in warm water. Call a physician immediately.

Do not re-use empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public waters. Do not contaminate water by cleaning of equipment, or disposal of wastes.

APPLICATIONS

Metla-Cota Algae and Slime Treatment 959A is used to inhibit the growth of algae, bacteria, and fungi in recirculating commercial and industrial cooling water systems. Before treatment with Metla-Cota Algae and Slime Treatment 959A, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. Then the system should be treated with an initial slug addition of 6.9 to 13.9 fluid ounces of Metla-Cota Algae and Slime Treatment 959A per 1,000 gallons of water in the system. Repeat the initial dosage until control is evident. Subsequent slug additions of 2.3 to 13.9 fluid ounces of Metla-Cota Algae and Slime Treatment 959A per 1,000 gallons of water should be made every 1 to 5 days or as needed. The required frequency of treatment depends on the relative amount of bleed-off and the severity of the microbiological problem. Slug additions of Metla-Cota Algae and Slime Treatment 959A should be made to the sump of the cooling towers.

MANUFACTURED BY

THE STATE MANUFACTURING COMPANY, INC., CLEVELAND, OHIO 44105