

Aug - 4 - 1972

WATCON 1278

E P A Reg. No. 13812-1

COMPOSITION

Active ingredient	12.0 percent by weight
Poly(oxyethylene(dinethyliminio)ethylene(dimethyliminio) ethylene dichloride)	12.0 percent
Inert ingredient	88.0 percent by weight

Weight per gallon 8.53 pounds

Weight of active ingredient per gallon 1.02 pounds

APPLICATION

Watcon 1278 is used to control algae, bacteria and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algae growth, microbiological slime and other deposits. An initial slug addition of 5 to 12.5 fluid ounces of Watcon 1278 per 1000 gallons of water, to provide a concentration of 40 to 100 parts per million of Watcon 1278 based on the total weight of water in the system is recommended. Repeat until control is achieved. Subsequent slug additions of 1.2 to 12.5 fluid ounces of Watcon 1278 per 1000 gallons of water (10 to 100 parts per million of Watcon 1278) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of the cooling towers.

CAUTION

KEEP OUT OF THE REACH OF CHILDREN

Harmful if swallowed. Avoid contact with skin and eyes. In case of contact flush with plenty of water for at least 15 minutes. If eye irritation persists get medical attention. Avoid contamination of food. This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds or public waters. Do not contaminate water by cleaning of equipment or disposal of waste. Use only as directed on label. Do not reuse container. Destroy when empty.

Watcon, Inc.
2215 S. Main Street

ACCEPTED WITH COMMENTS