

64
100-21
100-1

Restricted Use Pesticide

For sale to and use only by certified applicators
or by persons under their direct supervision and
only for those uses covered by the certified ap-
plicator's certification.

GATILL CREOSOTE OIL

A Wood Preservative for the Preservation of Un-
painted Lumber Against Decay, Rot and Wood
Borers

Active Ingredient:

Coal Tar Creosote 100.00%

FOR COMMERCIAL USE ONLY

ACCEPTED

JUN 12 1985

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
as amended, for the pesticide
registered under
EPA Reg. No. 13895-1

Keep Out of Reach of Children

DANGER

Statement of Practical Treatment

For Eyes: In case of contact with eyes, flush with
plenty of water immediately for at least 15 minutes. Call
a physician.

For Skin: Wash exposed areas of skin with soap and
warm water after handling or using.

If Swallowed: Do not induce vomiting. Call a physician
immediately.

Note: Remove and wash contaminated clothing before
reuse or discard in accordance with instructions for
pesticide container disposal.

See Side Panel for Additional Precautionary
Statements

EPA Reg. No. 13895-1

EPA Est. No. 50676-MX-01

Net Contents: _____ U.S. Gallons

Gatill Corporation
601 N. Shephard, Suite #340
Houston, TX 77007
Telephone: (713) 869-3944

2014

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND
DOMESTIC ANIMALS

DANGER

(18 pt)

Corrosive. Causes eye damage and skin irritation. Do not get in eyes, on skin or on clothing. Harmful or fatal if swallowed.

Applicators must wear gloves impervious to this wood treatment formulation in all situations where dermal contact is expected. (For example, during the actual application process and when handling freshly treated wood)

Spray applicators must wear protective clothing (including overalls, jackets, gloves and boots) impervious to this wood treatment formulation, and a respirator, head covering and goggles when spraying.

Applicators who apply creosote by other application methods (e.g., brush-on) must wear disposable coveralls or other suitable impermeable protective clothing. Launder non-disposable protective clothing separately from other clothing.

Applicators must not eat, drink, or use tobacco products during those parts of the application process that may expose them to this wood treatment formulation.

Avoid inhaling vapors. If inhalation of vapors cannot be avoided, applicators must wear a properly fitting, well-maintained half-mask canister or cartridge respirator which is MSHA/NIOSH approved for organic vapors and acid gases.

Wash thoroughly after skin contact, and before eating, drinking, use of tobacco products, or using restrooms.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not use this product to treat wood intended to be used where it may come into direct or indirect contact with public drinking water, or drinking water for domestic animals or livestock, except for those uses involving incidental contact such as docks and bridges.

PHYSICAL AND CHEMICAL HAZARDS

This product will burn. Do not use, pour or spill near heat or open flame. This product has a strong odor. Do not use where odor may penetrate to cause any odor problems.

Keep from freezing while in storage. If exposed to temperatures below 40° F., may settle out.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Container Disposal: Reseal cap and return to manufacturer.

BEST AVAILABLE COPY

Wood which has been treated with this product should be disposed of by burial or ordinary trash collection. Do not burn treated wood in an outdoor fire or in stoves or fireplaces because toxic chemicals may be produced as part of the smoke and ashes.

Do not apply where there may be direct contact with domestic animals or livestock, and where there may be contamination of food, feed, or drinking and irrigation water.

Do not apply in interiors. Do not apply to wood intended for use in interiors except for those support structures which are in contact with soil in barns, stables, and similar sites and which are subject to decay or insect infestation, and millwork which has outdoor surfaces (e.g., door frames, windows and patio frames). Interior surfaces of the treated wood should be sealed with two coats of an appropriate sealer.

Do not use this product to treat wood intended to be used for cutting-boards or counter-tops.

Do not use this product to treat wood intended for construction of those portions of beehives which may come into contact with the honey.

Wood to be treated with this product should be cut to size before treatment. If it is necessary to saw or machine wood after treatment, wear goggles to protect the eyes from flying particles and a dust mask to avoid inhaling sawdust from the treated wood. If oily preservatives or sawdust accumulate on clothes, launder before reuse. Wash work clothing separately from other household laundry. Contact with treated surfaces should be avoided even after the preservative has dried.

This product should not be used to treat wood which will be in frequent or prolonged contact with skin, unless the wood will be treated with an effective sealer.

Note to User: As used on this label, the term "respirators" means properly fitting, well-maintained half-mask canisters or cartridge respirators which are MSHA/NIOSH-approved for organic vapors and acid gases. Examples of acceptable materials for protective clothing (e.g., overalls, jackets, head covering, boots, disposable coveralls, and gloves) required during application and handling of creosote are polyvinylacetate (PVA), polyvinylchloride (PVC), neoprene, NBR (Buna-N), and nitrile. Urethane, shellac, latex epoxy enamel and varnish are acceptable sealers for creosote-treated wood.

INSTRUCTIONS FOR TREATING WOOD

Regardless of the type of pressure treatment used, the normal retention required for Creosote is from 6 to 12 lbs. per cubic foot. It is important to remember that only dry wood is satisfactorily treated by the pressure process. Unseasoned wood should first be steam conditioned, followed by a 1-3 hr. vacuum period, by vapor drying, where the vapors are condensed on the surfaces, or by Bouftorizing where wood is heated in creosote while under vacuum.

Note: Creosote may not be used on wood that is intended for interior use except for those support structures (e.g., foundation, timbers, pole supports and the bottom six inches of stall skirtboards) which are in contact with the soil in barns, stables and similar sites.

Creosote may not be used on wood in a manner which may result in direct exposure to domestic animals or livestock or in the contamination of food, feed, or drinking and irrigation water (e.g., irrigation flumes, watering troughs, feed lot bins and vegetable stakes.)

~~ALL INFORMATION CONTAINED HEREIN IS UNCLASSIFIED~~

