

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. For commercial use only.

CLASSIFICATION: Vinyl
USES: Anti-fouling protective coating for use in salt water environments to control the growth of barnacles and other common marine fouling organisms. Use over properly prepared and primed steel, wood, aluminum, ferro-cement or fiberglass marine structures and ships hulls.
FINISH: Eggshell
COLOR: Red
COMPONENTS: One
SURFACE PREPARATION: Paint only clean, dry surfaces. For new work, apply one or two coats over recommended Napko Epoxy or Coal Tar Epoxy anti-corrosive bottom systems. For refresher coats, sweep blast or water blast old coating to remove all marine growth, surface contamination and loose or peeling coating. Spot prime as required with recommended Napko Epoxies and apply one or two coats.
MIXING AND THINNING: Stir until thoroughly mixed. Thin as required up to 15% by volume with Napko 222 Thinner.
APPLICATION: Air or airless spray; brush for touch-up.
DRYING TIME: To Touch- 15 to 30 minutes;
To Recoat- 7 to 24 hours
To Launch- 24 hours
COVERAGE: 592 sq. ft./gal./mil (25 μ m)
RECOMMENDED THICKNESS: Wet-5.5 mils (140 μ m)
Dry-2.0 mils (50 μ m)
WEIGHT PER GALLON: 15.2 lbs (6.9 kg)
FLASH POINT: 74°F (23°C)
CLEAN-UP THINNER: Napko 222 Thinner

STORAGE AND DISPOSAL

Storage-Do not store near heat, sparks or open flame. Keep closures tight and upright to prevent leakage. Keep container closed when not in use. In case of spillage, absorb with sawdust or disposable rags and flush with large volumes of water.

Disposal-Anti-fouling coating, thinning and clean-up solvents, clean-up materials or rinsate that cannot be used according to label instructions must be disposed of according to Federal or approved state procedures under Subtitle C of the Resource Conservation and Recovery Act. Do not reuse containers. Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

PAINT



MANUFACTURED BY
THE O'BRIEN CORPORATION
South San Francisco, CA 94080
South Bend, IN • Baltimore, MD • Brunswick, GA • Houston, TX

FOR INDUSTRIAL USE ONLY

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS WARNING

Causes	eye irritation.	Harmful if
absorbed through skin.	Avoid contact with	skin,
eyes or	clothing.	Wear
protective clothing such as long sleeved cotton shirt, long pants,		
hat and gloves.	May be fatal if swallowed or inhaled.	

Do not breathe vapor, spray mist, or dust or chips from surface preparation. While spraying or abrading coated surfaces wear a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash thoroughly with soap and water before reuse. Wash thoroughly with soap and water after use.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS

Flammable. Keep away from heat and open flame.

NAPKO

DURAVIN VINYL ANTI-FOULING COMPOUND

5414 RED

ACTIVE INGREDIENT - Caprous Oxide	36.9%
INERT INGREDIENTS	63.1%
TOTAL	100.0%

THIS PRODUCT CONTAINS PETROLEUM DISTILLATES

KEEP OUT OF REACH OF CHILDREN

WARNING

SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS

EPA Establishment No. 14826-TX-1
EPA Registration No. 14826-3

NET CONTENTS 5 U.S. GALLONS (18.925 LITERS)



INDUSTRIAL/MARINE COATINGS

STATEMENT OF PRACTICAL TREATMENT

If swallowed—

Drink promptly a large quantity of milk, egg white, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

If in eyes—

Flush with plenty of water. Get medical attention.

If on skin—

Wash with plenty of soap and water. Get medical attention.

If inhaled. Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

Draft Labeling