

DIRECTIONS FOR USE

Mixing Instructions:

Mix the amount of material shown below into 5 gallons of water. Then add this amount of material at the pump discharge for uniform mixing.

Initial Dose:

Badly fouled system must be cleaned before treatment is begun. The recommended initial dose is 3 ounces of P-17, Algae Control Powder, per 1,000 gallons of water in the system. Repeat until control is achieved.

Subsequent Dose:

When microbial control is evident, add 2 ounces of P-17, Algae Control Powder, per 1,000 gallons of water in the system every 2 days and repeat the above dosages as needed to maintain the recommended chlorine residual in the water at all times with a chlorine test kit.



Engineered
Water Chemistry

P-17 ALGAE CONTROL POWDER

For Control of Bacterial and Algae Slime
Growth in Industrial Cooling Water Systems.

ACTIVE INGREDIENT:

Sodium Dichloro-s-triazinetrione Dihydrate 100%
Available Chlorine 56%

EPA Establishment No. 14886-NC-1
EPA Reg. No. 14886-8

DANGER:
KEEP OUT OF REACH OF CHILDREN.

See First Aid and additional precautions on the side panel.
Container Disposal: Rinse empty container thoroughly with water and discard in a safe place.

DISTRIBUTED BY

PARKER ENGINEERED CHEMICALS, INC.
320 Hodgin Street, P. O. Box 869
High Point, North Carolina 27261

NET CONTENTS

DANGER! KEEP OUT OF REACH OF CHILDREN!

**CORROSIVE, CAUSES EYE DAMAGE.
MAY BE FATAL IF SWALLOWED.**
Do Not Get In Eyes, On Skin Or On Clothing
Irritating To Nose And Throat.
Avoid Breathing Dust.
May Cause Burns To Broken Skin.
Wash Hands After Handling.

FIRST AID:

If swallowed, feed gruel, cooked cereal, or bread soaked in milk, followed by olive oil or cooking oil. In case of personal contact, remove excess material and flush skin or eyes with cold water for at least 15 minutes. For eyes get medical attention. Remove and wash contaminated clothing before reuse.

STRONG OXIDIZING AGENT:

Mix only with water. Use clean dry utensils. Contamination by moisture, organic matter, or other chemicals may liberate hazardous gases. Store in a cool, dry, well ventilated area away from heat or open flame. Decomposes at 350° - 475° F with liberation of harmful gases. In case of decomposition, if possible, isolate container in open air. Flood with large amounts of water. Keep container tightly closed when not in use. Rinse empty container thoroughly with water to dissolve all material before discarding.

ENVIRONMENTAL HAZARDS:

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public waters. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on the label.

ACCEPTED
14886-8
OCT 20 1975

DIRECTIONS FOR USE

Mixing Instructions:

Mix the amount of material shown below into 5 gallons of water. Then add this amount of material at the pump discharge for uniform mixing.

Initial Dose:

Badly fouled system must be cleaned before treatment is begun. The recommended initial dose is 3 ounces of P-17, Algae Control Powder, per 1,000 gallons of water in the system. Repeat until control is achieved.

Subsequent Dose:

When microbial control is evident, add 2 ounces of P-17, Algae Control Powder, per 1,000 gallons of water in the system every 2 days, and repeat the above dosages as needed to maintain the recommended chlorine residual in the water at all times with a chlorine test kit.



Engineered
Water Chemistry

P-17 ALGAE CONTROL POWDER

For Control of Bacterial and Algae Slime
Growth in Industrial Cooling Water Systems.

ACTIVE INGREDIENT:

Sodium Dichloro S-triazinetrione Dihydrate 100

Available Chlorine 50

EPA Establishment No. 14886-N01
EPA Reg. No. 14886-8

DANGER:

KEEP OUT OF REACH OF CHILDREN.

See First Aid and additional precautions on the side panel.

Container Disposal: Rinse empty container thoroughly with water and discard in a safe place.

DISTRIBUTED BY

PARKER ENGINEERED CHEMICALS, INC.
320 Hodgins Street, P. O. Box 869
High Point, North Carolina 27261

NET CONTENTS

DANGER!

KEEP OUT OF REACH OF CHILDREN!

CORROSIVE, CAUSES EYE DAMAGE

MAY BE FATAL IF SWALLOWED.

Do Not Get In Eyes, On Skin Or On Clothing

Irritating To Nose And Throat

Avoid Breathing Dust

May Cause Burns To Broken Skin

Wash Hands After Handling

FIRST AID:

If swallowed, feed quiet, cooked cereal, or bread soaked in milk, followed by olive oil or cooking oil. In case of personal contact, remove excess material and flush skin or eyes with cold water for at least 15 minutes. For eyes get medical attention. Remove and wash contaminated clothing before reuse.

STRONG OXIDIZING AGENT:

Mix only with water. Use clean dry utensils. Contamination by moisture, organic matter, or other chemicals may liberate hazardous gases. Store in a cool, dry, well ventilated area away from heat or open flame. Decomposes at 350-475 F with liberation of harmful gases. In case of decomposition, if possible, isolate container in open air. Flood with large amounts of water. Keep container tightly closed when not in use. Rinse empty container thoroughly with water to dissolve all material before discarding.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Treated effluent should not be discharged where it will drain to or back into streams, ponds, or public waters. Disposal: Dilute with water by volume of equipment or disposal of wastes. Apply this product only as specified on the label.

APPROVED
14886-8