

APPLICATION

JEF-CIDE C-515 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial treatment of 4.0 to 10.0 fluid ounces of JEF-CIDE C-515 per 1000 gallons of water to provide a concentration of 32 to 80 parts per million of JEF-CIDE C-515 based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident. Subsequent treatments of 1.0 to 10.0 fluid ounces of JEF-CIDE C-515 per 1000 gallons of water (8 to 80 parts per million of JEF-CIDE C-515) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Treatments should be made in the sump of water cooling towers.

CAUTION:

KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. Avoid contact with skin and eyes. In case of contact flush with plenty of water for at least 15 minutes. If eye irritation persists get medical attention. Avoid contamination of food.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Do not contaminate water by cleaning of equipment or disposal of waste. Use only as directed on label. Do not reuse container. Destroy when empty.

EPA Reg. No. 14955-1

ACCEPTED

14955-1

APR 19 1976

UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTERED
UNDER NO.

JEF-CO

COMPOSITION

	Percent by weight
Active ingredient	15.0 percent
Poly[oxyethylene(dimethyl- minio)ethylene(dimethyl- minio)ethylene dichloride]	
Inert ingredient	85.0 percent
Weight per gallon	8.58 pounds
Weight of active ingredient per gallon	1.29 pound

MANUFACTURED BY

JEF-CO LABORATORIES

618 W. JACKSON BLVD., CHICAGO, ILLINOIS 60606