



Pounds Net

CHEMTOX-S

FOR CONTROL OF SAPSTAIN AND MOLD IN LUMBER
AND WOOD PRODUCTS

ACTIVE INGREDIENTS:

| | |
|-------------------------------------|-------|
| Sodium Pentachlorophenate | 80.0% |
| Sodium Salts of Other Chlorophenols | 10.0% |

INERT INGREDIENTS:

TOTAL 100.0%

DIRECTIONS

To control Sapstain and Mold in softwoods and hardwoods, best results will be obtained if the lumber is dipped within 24 hours after cutting. If lumber is not treated within 24 hours, interior stain may develop.

For lumber 2" or less in thickness dissolve 5 pounds of CHEMTOX-S in 80 to 100 U.S. gallons of water. For thicker lumber dissolve 10 pounds of CHEMTOX-S in 100 U.S. gallons of water.

Agitate solution thoroughly in a mixing tank and then run into the dipping vat or spray tank. To avoid dust, bags should be immersed below water level and then opened.

In order to assure best results, the vat or tank must be protected from dilution by rain. Treated lumber should not be allowed to remain unprotected in heavy rain, especially just after dipping.

Approved stacking practice should be employed with adequate space between boards and stacks. Green or infected wood should not be used for stickers. The bottom of the stacks should be well above the ground.

DANGER

KEEP OUT OF REACH OF CHILDREN. Harmful dust. Avoid breathing dust. Use mechanically operated equipment only. Lumber wet with solution should be handled with rubber hand protectors. Causes skin irritation. Harmful or fatal if swallowed. Do not breathe dust or spray mist. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. In case of swallowing, induce vomiting by giving an emetic such as a tablespoon of mustard in water. Then give flour and water or raw egg white, beaten, and **CALL A DOCTOR.** Keep away from domestic animals. Avoid contamination of food and food stuffs. Causes eye damage. Wear goggles or face shield when handling.

Do not reuse container. Destroy it by perforating or crushing. Bury or discard in a safe place away from water supplies.

This product is toxic to fish and wildlife. Keep out of lakes, streams, or ponds. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this

To control Sapstain and Mold in softwoods and hardwoods, best results will be obtained if the lumber is dipped within 24 hours after cutting. If lumber is not treated within 24 hours, interior stain may develop.

For lumber 2" or less in thickness dissolve 5 pounds of CHEMIOX-S in 80 to 100 U.S. gallons of water. For thicker lumber dissolve 10 pounds of CHEMIOX-S in 100 U.S. gallons of water.

Agitate solution thoroughly in a mixing tank and then run into the dipping vat or spray tank. To avoid dust, bags should be immersed below water level and then opened.

In order to assure best results, the vat or tank must be protected from dilution by rain. Treated lumber should not be allowed to remain unprotected in heavy rain, especially just after dipping.

Approved stacking practice should be employed with adequate space between boards and stacks. Green or infected wood should not be used for stickers. The bottom of the stacks should be well above the ground.

DANGER

KEEP OUT OF REACH OF CHILDREN. Harmful dust. Avoid breathing dust. Use mechanically operated equipment only. Lumber wet with solution should be handled with rubber hand protectors. Causes skin irritation. Harmful or fatal if swallowed. Do not breathe dust or spray mist. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. In case of swallowing, induce vomiting by giving an emetic such as a tablespoon of mustard in water. Then give flour and water or raw egg white, beaten, and **CALL A DOCTOR.** Keep away from domestic animals. Avoid contamination of food and food stuffs. Causes eye damage. Wear goggles or face shield when handling.

Do not reuse container. Destroy it by perforating or crushing. Bury or discard in a safe place away from water supplies.

This product is toxic to fish and wildlife. Keep out of lakes, streams, or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

NON-WARRANTY

Seller warrants that this product conforms to the ingredient statement on the label. Since conditions of use, such as weather, compatibility with other chemicals and condition of application equipment will vary, Seller makes no claims other than those stated on this label.

EPA Reg. No. 15146-3

MANUFACTURED BY

CHEMWOOD CORPORATION

810 WASHINGTON AVENUE

P. O. BOX 1270, MEMPHIS, TENNESSEE 38104