



Pounds Net

BUCHANAN SPECIAL BLEND

ACTIVE INGREDIENTS:

Borax	28.0%
Sodium Pentachlorophenate	55.3%
Sodium Salts of Other Chlorophenols	7.7%

INERT INGREDIENTS

TOTAL100.0%

*Equivalent to 70% Technical Sodium Pentachlorophenate.

DIRECTIONS

To control Sapstain and Mold in softwoods and hardwoods, best results will be obtained if the lumber is dipped within 24 hours after cutting. If lumber is not dipped within 24 hours, interior stain may develop.

For lumber 2" or less in thickness, dissolve 10 lbs. of BUCHANAN SPECIAL BLEND in 100 U.S. gallons of water. For thicker lumber or timber or severe conditions favorable to the growth of sapstain and mold, dissolve 10 lbs. of BUCHANAN SPECIAL BLEND in 50 - 75 U.S. gallons of water. A dip of 15 seconds or more is sufficient.

The treating solution should be carefully prepared in a separate mixing tank and then run into the dipping vat or spray tank. After adding the dry chemical to the water, the mixture should be stirred until dissolved. To avoid dust, bags should be immersed below water level and then opened.

In order to insure best results, the vat or tank must be protected from dilution by rain. Treated lumber should not be allowed to remain unprotected in heavy rain, especially just after dipping.

Approved stacking practice should be employed with adequate space between boards and stacks. Green or infected wood should not be used for stickers. The bottom of the stacks should be well above the ground with weeds and debris kept away from the stacks.

WARNING

KEEP OUT OF REACH OF CHILDREN. Harmful dust. Avoid breathing dust. Use mechanically operated equipment only. Lumber wet with solution should be handled with rubber hand protectors. Causes skin irritation. Harmful if swallowed. Do not breathe dust or spray mist. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. In case of swallowing, induce vomiting by giving an emetic such as a tablespoon of mustard in water. Then give flour and water or raw egg white, beaten, and CALL A DOCTOR. Keep away from domestic animals. Avoid contamination of food and food stuffs.

Do not reuse container. Destroy when empty.

This product is toxic to fish and wildlife. Keep out of lakes, streams, or ponds. Do not contaminate water by cleaning of equipment, or disposal of waters. Apply this product only as specified on this label.

NON-WARRANTY

ACCEPTED
December 10, 1974
UNDER THE FEDERAL INSECTICIDE
ACT OF 1947
EPA REG. NO. 15146-6

ACTIVE INGREDIENTS:

Borax	28.0%
Sodium Pentachlorophenate	55.3%
Sodium Salts of Other Chlorophenols	7.7%
INERT INGREDIENTS	
TOTAL	100.0%

*Equivalent to 70% Technical Sodium Pentachlorophenate.

DIRECTIONS

To control Sapstain and Mold in softwoods and hardwoods, best results will be obtained if the lumber is dipped within 24 hours after cutting. If lumber is not dipped within 24 hours, interior stain may develop.

For lumber 2" or less in thickness, dissolve 10 lbs. of BUCHANAN SPECIAL BLEND in 100 U.S. gallons of water. For thicker lumber or timber or severe conditions favorable to the growth of sapstain and mold, dissolve 10 lbs. of BUCHANAN SPECIAL BLEND in 50 - 75 U.S. gallons of water. A dip of 15 seconds or more is sufficient.

The treating solution should be carefully prepared in a separate mixing tank and then run into the dipping vat or spray tank. After adding the dry chemical to the water, the mixture should be stirred until dissolved. To avoid dust, bags should be immersed below water level and then opened.

In order to insure best results, the vat or tank must be protected from dilution by rain. Treated lumber should not be allowed to remain unprotected in heavy rain, especially just after dipping.

Approved stacking practice should be employed with adequate space between boards and stacks. Green or infected wood should not be used for stickers. The bottom of the stacks should be well above the ground with weeds and debris kept away from the stacks.

WARNING

KEEP OUT OF REACH OF CHILDREN. Harmful dust. Avoid breathing dust. Use mechanically operated equipment only. Lumber wet with solution should be handled with rubber hand protectors. Causes skin irritation. Harmful if swallowed. Do not breathe dust or spray mist. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. In case of swallowing, induce vomiting by giving an emetic such as a tablespoon of mustard in water. Then give flour and water or raw egg white, beaten, and CALL A DOCTOR. Keep away from domestic animals. Avoid contamination of food and food stuffs.

Do not reuse container. Destroy when empty.

This product is toxic to fish and wildlife. Keep out of lakes, streams, or ponds. Do not contaminate water by cleaning of equipment, or disposal of waters. Apply this product only as specified on this label.

NON-WARRANTY

Seller warrants that this product conforms to the ingredient statement on the label. Since conditions of use, such as weather, compatibility with other chemicals and condition of application equipment will vary, Seller makes no claims other than those stated on this label.

EPA Reg. No. 15146-6

MANUFACTURED BY

CHEMWOOD CORPORATION

810 WASHINGTON AVENUE

P. O. BOX 4270, MEMPHIS, TENNESSEE 38104

ACCEPTED
December 10, 1974
ORDER THE FEDERAL BUREAU OF INVESTIGATION
15146-6

