



Nov 24/1972

CHEMICAL TREATMENT CL-2151

(EPA Reg. No. 15300-1)

COMPOSITION

	<u>Percent by weight</u>
Active ingredient	7.5
Polyoxyethylene(dimethyliminio)ethylene (dimethyliminio)ethylene dichloride)	
Inert ingredient	92.5
Weight per gallon	8.4 pounds
Weight of active ingredient per gallon	0.64 pound

APPLICATION

CHEMICAL TREATMENT CL-2151 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 8.0 to 20.0 fluid ounces of CHEMICAL TREATMENT CL-2151 per 1000 gallons of water to provide a concentration of 64 to 160 parts per million of CHEMICAL TREATMENT CL-2151, based on the total weight of water in the system, is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 2.0 to 20.0 fluid ounces of CHEMICAL TREATMENT CL 2151 per 1000 gallons of water (16 to 160 parts per million of CHEMICAL TREATMENT CL 2151) should be employed every 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

CAUTION KEEP OUT OF THE REACH OF CHILDREN

Harmful if swallowed. Avoid contact with skin and eyes. In case of contact, flush with plenty of water for at least 15 minutes. If eye irritation persists, get medical attention. Avoid contamination of food.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Do not contaminate water by cleaning of equipment or disposal of waste. Use only as directed on label. Do not reuse container. Destroy when empty.

NET CONTENTS 55 GALLONS

CHEMICAL TREATMENT COMPANY

302 South 7th Street
Richmond, Virginia 23219