



*Gen. 147972*

## CHEMICAL TREATMENT CL-2152

(EPA Reg. No. 15300-2)

### COMPOSITION

	Percent by weight
Active ingredient .....	15.0
Poly(oxyethylene(dimethyliminio)ethylene (dimethyliminio)ethylene dichloride)	
Inert ingredient .....	85.0
Weight per gallon .....	8.58 pounds
Weight of active ingredient per gallon .....	1.29 pound

### APPLICATION

CHEMICAL TREATMENT CL-2152 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 3.9 to 9.75 fluid ounces of CHEMICAL TREATMENT CL-2152 per 1000 gallons of water to provide a concentration of 32 to 80 parts per million of CHEMICAL TREATMENT CL-2152, based on the total weight of water in the system, is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 1.0 to 9.75 fluid ounces of CHEMICAL TREATMENT CL-2152 per 1000 gallons of water (8 to 80 parts per million of CHEMICAL TREATMENT CL-2152) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

### CAUTION

#### KEEP OUT OF THE REACH OF CHILDREN

Harmful if swallowed. Avoid contact with skin and eyes. In case of contact, flush with plenty of water for at least 15 minutes. If eye irritation persists, get medical attention. Avoid contamination of food.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds or public water. Do not contaminate water by cleaning of equipment or disposal of waste. Use only as directed on label. Do not reuse container. Destroy when empty.

NET CONTENTS 55 GALLONS

**CHEMICAL TREATMENT COMPANY**

302 South 7th Street  
Richmond, Virginia 23219