



HANOVER INDUSTRIAL AIR PARK  
ASHLAND, VA 23005 (804) 798-3231

15300-4

EPA Est. No. 15-300-VA-1

**DIRECTIONS**

**KEEP OUT OF**

When the cooling water system is in jeopardy of becoming affected by algae and fungal growths, or after the system has been cleaned because the efficiency has been impaired by growth, manually add 1 1/2 to 3 pints (200 to 400 ppm) of CHEMICAL TREATMENT CL-208 for each 1,000 gallons of water in the system as an initial slug dose. Repeat initial dose until control is achieved. Subsequently, add 3/4 to 1 1/2 pints (100 to 200 ppm) for each 1,000 gallons of water in the system. Additions should be made approximately once a week or as needed. In severe growth situations, good practice is to repeat the dosage when the bleed off from the system has reduced the concentration to approximately one-tenth (1/10) of the dosage amount. Slug additions should be made at points in the system where it will be uniformly mixed such as the sump of the cooling tower where rapid flow is evident.

**CHEMICAL TREATMENT CL-208**

**CONTROLS ALGAE AND FUNGAL  
SLIME FORMATION  
NONCORROSIVE TO METAL**

Causes eye damage get in eyes, on skin with goggles or face handling. Harmful if sorbed through skin.

For use in all recirculating cooling systems such as cooling towers and evaporative condensers where water is not used for drinking or bathing purposes.

In case of eye contact of water for at least 15 minutes. In case of skin contact of water. Wash contact area. If swallowed, induce vomiting. If inhaled, get to fresh air or give artificial respiration if necessary. If salt in a glass of water.

ACTIVE INGREDIENTS .....	20.3%
Sodium Pentachlorophenate .....	11.85%
Sodium Salts of other Chlorophenols .....	1.65%
Sodium 2,4,5-Trichlorophenate .....	6.8%
INERT INGREDIENTS .....	79.7%
WEIGHT PER GALLON .....	9.5 lbs.
WEIGHT OF ACTIVE INGREDIENT PER GALLON .....	1.9 lbs.

**NO**  
This product is a skin irritant. Treat symptoms.  
**E**  
This product is toxic if swallowed. Should not be discharged into streams, ponds, or other bodies of water. Clean up by cleaning of equipment. Use this product only as directed. Rinse empty container.



HANOVER INDUSTRIAL AIR PARK  
 ASHLAND, VA 23005 (804) 798-3231

EPA Est. No. 15-300-VA-1

## CHEMICAL TREATMENT CL-208

**CONTROLS ALGAE AND FUNGAL  
 SLIME FORMATION**

**NONCORROSIVE TO METAL**

For use in all recirculating cooling systems such as cooling towers and evaporative condensers where water is not used for drinking or bathing purposes.

ACTIVE INGREDIENTS .....	20.3%
Sodium Pentachlorophenate .....	11.85%
Sodium Salts of other Chlorophenols .....	1.65%
Sodium 2,4,5-Trichlorophenate .....	6.8%
INERT INGREDIENTS .....	79.7%
WEIGHT PER GALLON .....	9.5 lbs.
WEIGHT OF ACTIVE INGREDIENT PER GALLON .....	1.9 lbs.

EPA Reg. No. 15300-4

## DANGER

**KEEP OUT OF REACH OF CHILDREN:  
 CORROSIVE**

Causes eye damage. May produce severe burns. Do not get in eyes, on skin or on clothing. Protect eyes and skin with goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed, inhaled or absorbed through skin. Do not breathe vapor or mist.

### FIRST AID

In case of eye contact, flush eyes immediately with plenty of water for at least 15 minutes, and get medical attention. In case of skin contact, wash with soap and plenty of water. Wash contaminated clothing before reuse. If swallowed, induce vomiting by sticking finger down the throat or by giving an emetic such as 2 tablespoonsful of salt in a glass of warm water. Call a physician.

### NOTE TO PHYSICIAN

This product is a metabolic stimulant. Causes hyperthermia. Treat symptomatically.

### ENVIRONMENTAL

This product is toxic to fish and wildlife. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label. Rinse empty container thoroughly and discard it.