



100% ALKALYLATED QUATERNARY AMMONIUM CHLORIDES
 100% DIMETHYL BENZYL AMMONIUM CHLORIDES

NET CONTENTS: 1 GALLON

DIRECTIONS FOR USE

Begin treatment when the system is in jeopardy or becoming affected or after cleaning systems where efficiency is already impaired.

Initial Dose: 1-2 gallons CL-200 to each 5,000 gallons of water contained in the system. Repeat until control is evident.

Periodic Dose: 1-3 quarts CL-200 to each 5,000 gallons of water contained in the system every 7 days or sooner should visible growth appear.

For best results, clean heavily contaminated systems before treatment with this product. If soap or anionic detergent is used, rinse thoroughly before charging with CL 200. Apply CL 200 at a point in the system where uniform mixing will take place.

Do not be alarmed with the sudden appearance of organic debris in the system during the first week of operation. This is normal and is a good indication that CL 200 has effectively penetrated and dislodged dead organic material which tenaciously adheres to metal and wooden surfaces as living matter. This debris should be removed from the system to avoid clogging of screens and pipes.

FISH AND/OR WILDLIFE PRECAUTIONS

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds or public waters. Apply this product only as specified on the label.

Place empty container and apply with water used in system.

CL-200

Concentrated Algaecide for industrial re-circulating water cooling towers. Helps keep water cooling tower systems clear and free of visible algae slimes.

ACTIVE INGREDIENTS

- n-Alkyl (60) C₁₂, 30% C₁₂, 5% C₁₄, 5% C₁₆) dimethyl benzyl ammonium chlorides 5%
- n-Alkyl (68) C₁₂, 92% C₁₄ dimethyl ethyl benzyl ammonium chlorides 5%

INERT INGREDIENTS

- 90%
- 100%

Net Contents: 1 Gallon

DANGER

Keep Out of Reach of Children

See front label panel for first aid and additional precautionary statements.

When CL 200 is used as directed, it will aid in controlling and/or preventing the development of unsanitary slime conditions which are unsightly, produce foul odors and which are often the cause of equipment breakdown.

CL 200 is compatible with virtually all corrosion inhibition additives, but should not be used in the presence of soap or other anionic detergents. CL 200 at use dilution is non-corrosive to inanimate hard surfaces.

DANGER

Keep Out of Reach of Children. Corrosive. Causes severe eye and skin damage. Do not get in eyes, on skin or on clothing. Wear goggles or face shield, and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food.

FIRST AID

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash all contaminated clothing before reuse. If swallowed, drink milk, egg whites, gelatin solution, or if these are not available, drink large quantities of water. Call a physician.

NOTE TO PHYSICIAN

Possible mucosal damage may contraindicate the use of gastric lavage. Mucous membranes of the respiratory tract may be irritated. Do not induce vomiting.