



## CHEMICAL TREATMENT CT-202

Chemical Treatment CT-202 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers.

### DIRECTIONS FOR USE

Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 2.53 to 6.33 fluid ounces of Chemical Treatment CT-202 per 1000 gallons of water to provide a concentration of 20 to 50 parts per million of Chemical Treatment CT-202 based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 0.63 to 6.33 fluid ounces of Chemical Treatment CT-202 per 1000 gallons of water (5 to 50 parts per million of Chemical Treatment CT-202) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

	<u>Percent by weight</u>
ACTIVE INGREDIENT .....	24.0%
Poly[oxyethylene(dimethyliminio)ethylene (dimethyliminio)ethylene dichloride] .....	24.0%
INERT INGREDIENT .....	76.0%
Weight per gallon .....	8.77 pounds
Weight of active ingredient per gallon..	2.10 pounds

### CAUTION:

#### KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. Do not get in eyes. Avoid contact with skin. If swallowed induce vomiting by giving 1 or 2 tablespoons of salt in water. In case of contact with eyes, flush with water for at least 15 minutes. In case of contact with skin, wash with soap and water for at least 15 minutes.

million of Chemical Treatment CT-202 based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 0.63 to 6.33 fluid ounces of Chemical Treatment CT-202 per 1000 gallons of water (5 to 50 parts per million of Chemical Treatment CT-202) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

	<u>Percent by weight</u>
ACTIVE INGREDIENT .....	24.0%
Poly[oxyethylene(dimethyliminio)ethylene (dimethyliminio)ethylene dichloride] .....	24.0%
INERT INGREDIENT .....	76.0%
Weight per gallon .....	8.77 pounds
Weight of active ingredient per gallon..	2.10 pounds

## CAUTION:

### KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. Do not get in eyes. Avoid contact with skin. If swallowed induce vomiting by giving 1 or 2 tablespoons of salt in warm water and sticking finger in back of throat. In case of contact with eyes flush with plenty of water for at least 15 minutes. If eye irritation persists call a physician. Avoid contamination of food.

### ENVIRONMENTAL HAZARDS

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Apply this product only as specified on the label.

Do not reuse empty container. Rinse thoroughly with water before discarding or return to drum conditioner.

Manufactured by

### CHEMICAL TREATMENT COMPANY

Hanover Industrial Air Park

Ashland, Va. 23005

E.P.A. Reg. No. 15300-11

