PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS (& DOMESTIC ANIMALS)

DANGER

CORROSIVE

CAUSES EYE DAMAGE AND SKIN BURNS. MAY CAUSE ALLERGIC SKIN REACTION. MAY BE HARMFUL IF INHALED. MAY BE FATAL IF SWALLOWED OR ABSORBED THROUGH THE SKIN.

Do not get in eyes, on skin, on clothing. Wear goggles or face shield and rubber gloves when handling. Avoid breathing vapor or mist. Avoid contamination of food. Do not take internally. Wash thoroughly after handling.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and wildlife. Do not discharge into lakes, streams, ponds or public waters unless in accordance with an NPDES permit, For guidance, contact your Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label.

STORAGE AND DISPOSAL

STORAGE: Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited. If plastic, do not reuse empty container.

DISPOSAL: Pesticide or residue that cannot be used or chemically reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies. Triple rinse (or equivalent) all containers and, for metal containers, offer for recycling or reconditioning (for plastic containers dispose in an incinerator), or dispose in landfill approved for pesticide containers or bury in a safe place. Consult federal, state or local disposal authorities for approved alternative procedures.

MANUFACTURED BY:

CHEMICAL TREATMENT CO. Hanover Industrial Air Park ASHLAND, VIRGINIA 23005

Chemical Treatment CL-2150

Industrial Recirculating

: Cooling Water Microbicide :

ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazolin-3-one	
2-Methyl-4-isothiazolin-3-one).35%
INERT INGREDIENTS:	3.50%
INERT INGREDIENTS: 98 TOTAL).00%

KEEP OUT OF REACH OF CHILDREN

DANGER

STATEMENT OF PRACTICAL TREATMENT

- IF SWALLOWED: Do not induce vomiting. Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.
- IF INHALED: Remove immediately to fresh air. If not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Call a physician.
- IF ON SKIN: Wash thoroughly with soap and water. Remove and wash contaminated clothing before reuse.
- IF IN EYES: Flush with plenty of water for at least 15 minutes. Call a physician.

NOTE TO PHYSICIAN:

Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsions may be needed.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

4 EPA Est. No. 15300–VA--1 EPA Reg. No. 15300–24

NET CONTENTS

GALLONS

DIRECTIONS FOR USE

GENERAL CLASSIFICATION

It is a violation of Federal Law to use this product in a manger inconsistent with its labeling. Ś

14

300

γ

90

5

COOLING TOWERS

For the control of bacteria, algae and fungi, add Chemical Treatment CL-2150 to the tower basin, distribution box or some other point to insure uniform mixing.

INITIAL DOSE

. .

When the system is noticeably fouled, apply 1.26 to 7.46 pounds (19 to 113 fluid ounces) of Chemical Treatment CL-2150 per 1000 gallons of water in the system. Repeat until control is achieved.

SUBSEQUENT DOSE

When microbial control is evident, add 0.3 to 1.86 lbs. (4.5 to 28 fluid ounces) of Chemical Treatment CL-2150 per 1000 gallons of water in the system weekly or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

AIR WASHERS

CHEMICAL TREATMENT CL-2150 is used to control bacteria in industrial air washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacteria and other deposits.

INITIAL DOSE

When the system is noticeably fouled, apply 1.26 to 7.46 lbs. (19 to 113 fl. oz.) of Chemical Treatment CL-2150 per 1000 gal. of water in the system. Repeat until control is achieved.

SUBSEQUENT DOSE

When microbial control is evident, add 0.3 to 1.86 lbs. (4.5 to 28 fl. oz.) of Chemical Treatment CL-2150 per 1000 gal. of water in the system weekly or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun. CHEMICAL TREATMENT CL-2150' weighs 8.4 lbs. per gallon.

