


**87L**



**ACTIVE INGREDIENT**

Poly (oxyethylene (dimethylamino) ethylene-  
(dimethylamino) ethylene dichloride) 15.0%

**INERT INGREDIENT**

85.0%  
This product contains 1.20 lb. of active ingredient per gallon and weighs  
6.66 lb. per gallon

**KEEP OUT OF REACH OF CHILDREN**  
**CAUTION**

**PRECAUTIONARY STATEMENTS**

**HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

**CAUTION:** Harmful if swallowed. Avoid breathing vapors.  
Avoid contact with skin, eyes, or clothing.

**FIRST AID:** If swallowed, drink promptly a large quantity of  
milk, egg whites, pepto-bismol solution, or, if these are not available,  
drink large quantities of water. Avoid alcohol. Call a physician  
immediately.

**ENVIRONMENTAL HAZARDS:** This pesticide is toxic to fish.  
Keep out of lakes, streams, or ponds. Permits may be required  
for discharges containing this pesticide into lakes, streams,  
ponds or public water. For guidance, contact the regional  
office of the Environmental Protection Agency

**DIRECTIONS FOR USE**  
**GENERAL CLASSIFICATION**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

87L is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 4.0 to 10.0 fluid ounces of 87L per 1000 gallons of water to provide a concentration of 32 to 80 parts per million of 87L is recommended. Repeat initial dosage until control is evident.

Subsequent slug additions of 1.0 to 10.0 fluid ounces of 87L per 1000 gallons of water (8 to 80 parts per million of 87L) should be employed every 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.


87L is used to control bacteria in industrial air-washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial dose of 14.8 to 24.7 fluid ounces of 87L per 1000 gallons of water is recommended. Repeat initial dose until control is evident. Subsequent slug additions of 10.6 to 24.7 fl. oz. of 87L per 1000 gallons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water collection tanks of the air-wash system.

**STORAGE & DISPOSAL:** Keep container closed when not in use. Do not contaminate water, food, or feed by storage, disposal, or cleaning of equipment. The container must be triple rinsed (or equivalent) and offered for recycling, reconditioning, or disposal in an approved landfill or buried in a safe place. Rinse that cannot be used or reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies. Open dumping is prohibited.

Manufactured by:  
The Bond Chemical Company, Inc.  
103 Pleasant Avenue, Upper Saddle River, NJ 07458

EPA REG. NO. 15311-5      EPA EST. NO. 15311-NJ-1  
NET CONTENTS      Gallons

**87L**



**ACTIVE INGREDIENT**

Poly [oxymethylene (dimethylamino) ethylene-  
(dimethylamino) ethylene dichloride]

15.0%

**INERT INGREDIENT**

85.0%

This product contains 1.29 lb. of active ingredient per gallon and weighs  
8.58 lb. per gallon.

**KEEP OUT OF REACH OF CHILDREN**  
**CAUTION**

**PRECAUTIONARY STATEMENTS**

**HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

**CAUTION:** Harmful if swallowed. Avoid breathing vapors.  
Avoid contact with skin, eyes, or clothing.

**FIRST AID:** If swallowed, drink promptly a large quantity of  
milk, egg whites, gelatin solution, or, if these are not available,  
drink large quantities of water. Avoid alcohol. Call a physician  
immediately.

**ENVIRONMENTAL HAZARDS:** This pesticide is toxic to fish.  
Keep out of lakes, streams, or ponds. Permits may be required  
for discharges containing this pesticide into lakes, streams,  
ponds or public water. For guidance, contact the regional  
office of the Environmental Protection Agency.

**DIRECTIONS FOR USE**  
**GENERAL CLASSIFICATION**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

87L is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 4.0 to 10.0 fluid ounces of 87L per 1000 gallons of water to provide a concentration of 32 to 80 parts per million of 87L, based on the total weight of water in the system, is recommended. Repeat initial dosage until control is evident.

Subsequent slug additions of 1.0 to 10.0 fluid ounces of 87L per 1000 gallons of water (8 to 80 parts per million of 87L) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

87L is used to control bacteria in industrial air-washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial sludge and other deposits. An initial slug dose of 14.0 to 24.7 fluid ounces of 87L per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 10.1 to 24.7 fluid ounces of 87L per 1000 gallons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water collection trays of the airwash system.

**STORAGE & DISPOSAL:** Keep container closed when not in use. Do not contaminate water, food, or feed by storage, disposal, or cleaning of equipment. The container must be triple rinsed (or equivalent) and offered for recycling, reconditioning, or disposal in an approved landfill or buried in a safe place. Rinseate that cannot be used or reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies. Open dumping is prohibited.

Manufactured by:  
The Bond Chemical Company, Inc.  
103 Pleasant Avenue, Upper Saddle River, NJ 07458

EPA REG. NO. 15311-5

EPA EST. NO. 15311-NJ-1

NET CONTENTS

Gallons