

4029
R&E
1 2 3 4 5 6 7 8 9 10 11 12 -80
1 2 3 4 5 6 7 8 9 10 11 12 -81
1 2 3 4 5 6 7 8 9 10 11 12 -82

WARRANTED
8-WAYS

SEMI-TRANSPARENT
FLAT FINISH

**STAIN & WOOD
PRESERVATIVE**

CONTAINS POLYURETHANE

**8-WAY WARRANTY
STAIN & WOOD
PRESERVATIVE**

- Penetrates & protects natural wood beauty
- Resists rot
- Resists mildew
- Water repellent
- Resists fading
- Guards against warping
- Resists cracking
- Easy to apply

When applied according to directions if stain fails to perform as specified above, our obligation shall be limited solely to the refund of the purchase price. This warranty does not include labor or cost of labor for application of stain.

KEEP OUT OF THE REACH
OF CHILDREN
CAUTION
SEE ADDITIONAL PRECAUTIONS
ON BACK PANEL
**ONE GALLON
(3.785 LITERS)**

EPA G. NO. 17322-1
EPA EST. NO. 17322-IN-1

Semi-Transparent Stain and Wood Preservative

Resists Mildew • Resists Rotting and Decay

The Semi-Transparent Polyurethane Wood Preservative brings out the natural beauty of wood while protecting against rot and mildew. It beautifies in one easy step, deeply penetrating the wood fibers.

This special formula contains a long lasting fungicide (Copper 8 Quinolinolate) along with special additives that seal out deterioration caused by moisture and the onslaught of environmental elements. This Semi-Transparent Stain is designed for use on exterior siding, fences, and wood surfaces. Due to its penetrating and absorbent features, the natural texture and grain of the wood will be enhanced.

How To Use

Semi-Transparent Stain and Wood Preservative is ready for use. Do not use thinner. Stir thoroughly before using and occasionally while applying.

All surfaces should be thoroughly clean and dry before staining. Unsightly mildew stains should be scrubbed with a solution of 1 quart household bleach to 3 quarts of warm water. Let stand for 30 minutes, then rinse with water. When surface is dry, liberally apply stain by brush, roller, pad applicator or spray. To eliminate lap marks, apply to only a few boards at a time, working from top to bottom or from side to side, stopping only at locations as corners, windows, or door frames. Avoid using in direct sunlight. Do not apply if temperature is below 50°F. Dries to touch rapidly. Thorough drying will take 24 hours. If necessary, a second coat may be applied at any time. In addition, the greater the amount of stain absorbed by the wood the more effective the protection.

Coverage

A gallon will treat 100-200 square feet on rough or unfinished surfaces and 100-300 square feet on previously stained or finished surfaces.

Clean-Up

Clean brushes and equipment with mineral spirits or other suitable paint thinners.

Meets or exceeds water repellency requirements of U.S. Federal Specification TT-W-572b, 3.7.

Note

Color of chip represented on front panel could vary with the number of coats applied, the color of the surface covered, and the method of application.

Precautionary Statements

Hazards to Humans (and Domestic Animals)

CAUTION

Harmful if swallowed. If swallowed, do not induce vomiting. Call physician immediately. Avoid contact with skin, eyes, or clothing. In case of contact, immediately flush eyes or skin with plenty of water. Get medical attention if irritation persists.

Environmental Hazards

This product is toxic to fish. Keep out of lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes.

Physical and Chemical Hazards

Keep away from heat and open flames.

Directions for Use

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL

Do not reuse empty container. Wrap container and put in trash collection.

MANUFACTURED BY UNITED COATINGS INC., CHICAGO, ILLINOIS 60618