

ACTIVE INGREDIENT:
Poly [oxyethylene (dimethyliminio) ethylene(dimethyliminio) ethylene dichloride] 10.0%

INERT INGREDIENTS 90.0%

This product contains 0.85 lb. of active ingredient per gallon and weighs 8.49 lb. per gallon.

CAUTION

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed. Avoid breathing vapors. Avoid ontact with skin, eyes, or clothing.

PRACTICAL TREATMENT (FIRST AiD):

If Swallowed: Rinse mouth with copious amounts of water then drink

promptly: a large quantity of water. Do not induce

vomiting. Avoid alcoho!. Get medical attention.

If In Eyes: Flush with plenty of water for 15 minutes. Get medical

attention.

If On Skin: Wash with plenty of soap and water. Get medical

attention, if irritation persists

ENVIRONMENTAL HAZARDS: This: icide is toxic to fish. Keep out of lakes, streams, or ponds. I mits may be required for discharges containing this pesticide into lakes, streams, ponds or public waters. For guidance contact your Regional Office of the Environmental Protection Agency.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product is a manner inconsistent with its labeling.

BA-105 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 6.13 to 15.32 fluid ounces of BA-105 per 1000 gallons of water to provide a concentration of 48 to 120 parts per million of BA-105, based on the total weight of water in the system, is recommended. Repeat initial dosage until control is evident.

Subsequent slug additions of 1.53 to 15.32 fluid cunces of BA-105 per 1000 gallons of water (12 to 120 parts per million of BA-105) should be employed every 2 to 5 days, or as needed. The frequency of addition depends upn the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

BA-105 is used to control bacteria in industrial air-washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 24.7 to 41.2 fluid ounces of BA-105 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 16.9 to 41.2 fluid ounces of BA-105 per 1000 gallons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water collection trays of the airwash system.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal. STORAGE: Do not stack more than four drums high. Leaking or damaged drums

should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or hand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

CONTAINER DISPOSAL:

- ☐ PLASTIC: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.
- ☐ METAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

Manufactured by:

Industrial Maintenance Corporation

3520 Trycian Drive, Charlotte, NC 28217 704/525-6967

EPA REG. NO. 17866-1

EPA EST. NO. 17866-NC 1

EMERGENCY CONTACT: CHEMTREC 1-800-424-9300

(24 Hours Per Day)