



PRECAUTIONARY STATEMENTS - WARNING

HAZARDS TO HUMANS AND DOMESTIC ANIMALS—AVOID CCNTACT WITH SKIN, EYES OR CLOTHING. IN CASE OF CONTACT IMMEDIATELY FLUSH EYES OR SKIN WITH PLENTY OF WATER. USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING OF VAPOR OR SPRAY MIST. DO NOT TAKE INTERNALLY. AVOID PROLONGED CONTACT WITH SKIN AND BREATHING OF VAPORS OR SPRAY MIST. CLOSE CONTAINER AFTER EACH USE.

ENVIRONMENTAL HAZARD — THIS PRODUCT IS TOXIC TO FISH. DO NOT APPLY DIRECTLY TO LAKES, STREAMS OR PONDS. DO NOT CONTAMINATE WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES.

PHYSICAL CHEMICAL HAZARD — COMBUSTIBLE: DO NOT USE OR STORE NEAR OPEN FLAME,

STORAGE AND DISPOSAL

PROHIBITIONS — DO NOT CONTAMINATE WATER, FOOD OR FEED BY STORAGE OR DISPOSAL OPEN DUMPING IS PROHIBITED.

PESTICIDE DISPOSAL — PESTICIDE, SPRAY MIXTURE OR RINSATE THAT CANNOT BE USED ACCORDING TO LABEL INSTRUCTIONS MUST BE DISPOSED OF ACCORDING TO FEDERAL, STATE OR LOCAL PROCEDURES UNDER THE RESOURCE CONSERVATION AND RECOVERY ACT.

CONTAINER DISPOSAL — TRIPLE RINSE (OR EQUIVALENT) AND OFFER FOR RECYCLING, RECONDITIONING OR DISPOSE OF IN A SANITARY LANDFILL OR BY INCINERATION IF PERMITTED BY STATE AND LOCAL AUTHORITIES. GENERAL — CONSULT FEDERAL, STATE OR LOCAL DISPOSAL AUTHORITIES FOR APPROVED ALTERNATIVE PROCEDURES.

ULTRA LIFE CLEAR WOOD PRESERVATIVE

Ultra-Life is a clear interior and exterior wood preservative that protects and enhances the natural beauty of wood. Provides positive protection against decay, fungi staining and warping. Ultra-Life Clear is an odorless, non-tlammable water repellant that reduces swelling and shrinking. Ultra-Life will not adversely affect plant or animal life and is safe for use in lood processing operations not in direct contact with food products. When dry, Ultra-Life provides a repaintable surface for the subsequent application of paints, stains, enamels or varnishes if desired. Ultra-Life increases top coat resistance to peeling and bistering. Ultra-Life has a very low odor and may be applied to in terior surfaces without appreciable discomfort to occupants.

USES: Brunings Ultra-Life Wood Preservative is highly recommended for wood and wood products. Ultra-Life lengthens the life and protects shingles millwood, windows, siding, doors, fences, outdoor turniture, structural lumber, docks, piers, posts and pilings.

SURFACE PREPARATION. Be sure that the surface to be treated is clean and free of all dift. bark wax grease or grine. Be sure that the wood is dry and well seasoned. Wipe off dust with a clean tack rag.

NEW GR UNTREATED WOOD For small areas apply by brush, roller, conventional or airless spray. Dipping is recommended where possible. Side or end grains should be coated two or three times for full protection. Lumber intended to come in contact with the soil should be dipped for a minimum of three minutes. Heavy lumber such as lence posts, poles, foundation timbers and other large wooden members should be dry, well seasoned and free of bank or dirt. It is suggested that such large lumber be immersed in Ultra-Life Clear for a period of 12 to 48 hours before being used.

TECHNICAL DATA. Apply as it comes from the container. Appearance in container is milky white, but Ultra Life dries to a clear flat finish. Spread at a rate of 150-200 square feet per gallon depending upon porosity of surface and method of application.

BRUNING PAINT COMPANY

Baltimore, Maryland 21224 . Poinpano Beach Florida 33061