

LARGE CAN No. 1

1/3/73

18710-5

For treating
badly damaged
wooden works of art

XYLAMON™

LX - HARDENING

ACTIVE INGREDIENTS:

Lindane (Gamma isomer of benzene
hexachloride) 1.0%

INERT INGREDIENTS 99.0%

TOTAL 100.0%

CAUTION:

KEEP OUT OF REACH OF CHILDREN
READ DIRECTIONS ON SIDE PANEL

EPA REG. NO. 18911-5

1.32 GALLON (5 LITER)

DESOWAG-BAYER HOLZSCHUTZ GMBH, 4 DUSSELDORF 32, W. GERMANY

XYLAMON-LX-Hardening

XYLAMON-LX is a solvent for badly damaged wooden
works of art. Penetrates deeply into wood
forming a protective film. Acts as a wood
preservative.

Preventative and curative wood preservative
for all types of wood. Protects against
decay, rot, and insect damage.

Application:

Apply to surface.

CAUTION:

KEEP OUT OF REACH OF CHILDREN!
READ CAUTIONS ON SIDE PANEL

EPA REG. NO. 18910-3

1.32 GALLON (5 LITER)

DESOWAG-BAYER HOLZSCHUTZ GMBH, 4 DUSSELDORF 32, W. GERMANY

XYLAMON-LX-Hardening

A treatment for badly damaged wooden works of art. Penetrates deeply into wood—hardens bore dust of Anobiidae without causing stresses.

Preventative and curative wood protection against House Longhorn Beetle, Woodworm, Termites.

Odorless after drying.

Colorless.

Application Field

Worm-eaten and crumbled wood of statues, altars and carvings.

Application Method

Injection through inclined bore holes. Excess XYLAMON should be wiped off immediately to prevent staining of the paint coat or polish.

Rate of use depends on the degree of damage. *Seal cans tightly after use to exclude air.*

Remarks

XYLAMON-LX-Hardening is quickly absorbed but may in special cases be diluted with up to 50% of trichloroethylene. The product hardens on evaporation of the solvent, therefore, bore holes must not be too small and treatment should preferably be carried out at room temperature.

Syringe can easily be cleaned with trichloroethylene. Remove excess and hardened XYLAMON-LX-Hardening also with trichloroethylene.

ACCEPTED
JAN - 9 1973
UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTERED
ED UNDER NO. 40005

XYLAMON™
LX-Hardening

CAUTION

Harmful if swallowed inhaled or absorbed through skin! Contains solvent whose non combustible vapors have narcotic effect— Avoid inhalation of vapors! Use only in well ventilated rooms. If feeling drowsy or sick, breathe fresh air away from area of treatment. After use close container tightly.

Avoid contact with skin, eyes or clothing. In case of contact with skin or eyes flush with plenty of water, for eyes get medical attention.

Avoid contamination of feed and foodstuffs. Keep out of reach of children!

Do not reuse empty container. Destroy it by perforating or crushing. Bury or discard in a safe place away from water supplies.

**XYLAMON is a Trade Name of
DESOWAG-BAYER HOLTZSCHUTZ GMBH**

ACCEPTED
UNDEF
FED