

UNDER THE PEDERAL INSECTIONS FOR FORMATION POPULATION OF THE PERSON OF T

ANCOCIDE

1201

Manufactured by: Anco Refining Company, Inc.
681 Main Street
Belleville, New Jersey 07109
EPA REG. NO. 20957-5

NET WEIGHT:

KEEP OUT OF REACH OF CHILDREN CAUTION

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed. Avoid breathing vapors. Avoid contact with skin, eyes, or clothing.

FIRST AID: If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or if these are not available drink large quantities of water. Avoid alcohol. Call a physician immediately.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Keep out of lake, streams, or ponds. Permits may be required for discharges containing this pesticide into lakes, streams, ponds or public water. For guidance, contact the regional office of the Environmental Protection Agency.

DIRECTIONS FOR USE GENERAL CLASSIFICATION

It is a violation of Federal law to use this princonsistent with its labeling.

ANCOCIDE 1201 is used to control algae, be recirculating commercial and industrial water cool use, systems must be cleaned to remove algal gradime, and other deposits. An initial slug addition of 1 of ANCOCIDE 1201 per 1000 gallons of water to pro 16 to 40 parts per million of ANCOCIDE 1201, base water in the system, is recommended. Repeat initial evident.

Subsequent slug additions of 0.47 to 4.75 fluid ounce per gallons of water (4 to 40 parts per million of AN be employed every 2 to 5 days, or as needed.). The depends upon the relative amount of bleedoff and the biological problem. Slug additions should be made cooling towers.


ANCOCIDE 1201 is used to control bacteria in systems that maintain effective mist eliminating of use, systems whould be cleaned to remove bactedeposits. An initial slug dose of 7.1 to 11.9 fluid object per 1000 gallons of water is recommended. Reper control is evident. Subsequent slug additions of 4.8 ANCOCIDE 1201 per 1000 gallons of water should adays, or as needed. The frequency of addition deper amount of bleedoff and severity of the bacterial promay be made to the sump or to the water collection system.

STORAGE & DISPOSAL: Keep container closed with contaminate water, food, or feed by storage, distinguishment. The container must be triple rinsed (or effor recycling, reconditioning, or disposal in an approximate a safe place. Rinsate that cannot be used or redisposed of in a landfill approved for pesticides or away from water supplies. Open dumping is prohib

Manufactured by: Anco Refining Company, Inc. 681 Main Street Belleville, N.J. 07109

EPA REG. NO. 20957-5

EPA



ANCOCIDE

ufactured by: Anco Refining Company, Inc. 681 Main Street Belleville, New Jersey 07109 EPA REG. NO. 20957-5

WEIGHT:

| /E INGREDIENT oxyethylene (dimethyliminio) ethylene- thyliminio) ethylene dichloride] | 30.0% |
|---|----------------------|
| INGREDIENT | 70.0% |
| product contains 2.67 lb. of active ingredient p | er gallon and weighs |
| | |

KEEP OUT OF REACH OF CHILDREN

CAUTION

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

ION: Harmful if swallowed. Avoid breathing vapors. Avoid contact kin, eyes, or clothing.

! AID: If swallowed, drink promptly a large quantity of milk, egg >, gelatin solution, or if these are not available drink large quantities of

Avoid alcohol. Call a physician immediately.

RONMENTAL HAZARDS: This pesticide is toxic to fish. Keep out of streams, or ponds. Permits may be required for discharges containing pesticide into lakes, streams, ponds or public water. For guidance, act the regional office of the Environmental Protection Agency.

DIRECTIONS FOR USE GENERAL CLASSIFICATION

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

ANCOCIDE 1201 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 1.90 to 4.75 fluid ounces of ANCOCIDE 1201 per 1000 gallons of water to provide a concentration of 16 to 40 parts per million of ANCOCIDE 1201, based on the total weight of water in the system, is recommended. Repeat initial dosage until control is evident.

Subsequent slug additions of 0.47 to 4.75 fluid ounces of ANCOCIDE 1201 per gallons of water (4 to 40 parts per million of ANCOCIDE 1201) should be employed every 2 to 5 days, or as needed.i. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

ANCOCIDE 1201 is used to control bacteria in industrial air-washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 7.1 to 11.9 fluid ounces of ANCOCIDE 1201 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 4.8 to 11.9 fluid ounces of ANCOC IDE 1201 per 1000 gallons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water collection trays of the airwash system.

STORAGE & DISPOSAL: Keep container closed when not in use. Do not contaminate water, food, or feed by storage, disposal, or cleaning of equipment. The container must be triple rinsed (or equivalent) and offered for recycling, reconditioning, or disposal in an approved landfill or buried in a safe place. Rinsate that cannot be used or reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies. Open dumping is prohibited.

> Manufactured by: Anco Refining Company, Inc. 681 Main Street Belleville, N.J. 07109

EPA REG. NO. 20957-5

EPA EST. NO. 20957-NJ-1