ACCEPTED

NOV -8 1988

EPA Reg. No. 2294?-5

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER [illegible] corrosive. May cause eye damage and skin burns. Harmful if [illegible] absorbed through skin. Do not get in eyes, on skin, or on clothing. Avoid breathing [illegible]. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse.

FIRST AID [illegible] Have victim drink water immediately. If product is swallowed, call a physician or Poison Control Center. Drink 1 or 2 glasses of water. Do not induce vomiting or give anything by mouth to an unconscious person.

ENVIRONMENTAL HAZARDS This pesticide is toxic to fish. Do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment washwaters or rinsate. Permits may be required for discharges containing this pesticide into waters, streams, ponds, or public waters. For guidance contact your regional office of the Environmental Protection Agency.

PHYSICAL AND CHEMICAL HAZARDS Do not expose to extreme temperatures.

Manufactured and Marketed by
AMANAR Maintenance Corporation
[illegible]

EPA Registration No.

EPA Establishment No. 22947-MO-01

FOR INDUSTRIAL and PROFESSIONAL USE ONLY

"for professional water treatment programs"

AMANAR Maintenance Corp.

Poly-Pro MBC.

INDUSTRIAL MICROBICIDE

ACTIVE INGREDIENTS	
Methylene bis(thiocyanate)	25%
2-(Thiocyanomethylthio)benzothiazole	25%
INERT INGREDIENTS	95.0%

This product weighs 9.99 pounds per gallon

KEEP OUT OF REACH OF CHILDREN

DANGER

SEE LEFT SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

NET ONE U.S. GALLON

DIRECTIONS FOR USE

COOLING WATER Poly-Pro MBC is used to control algae, bacteria and fungi in industrial recirculating cooling water systems. Before treatment is begun, the system should be cleaned thoroughly to remove [illegible] algal growth, microbiological slime, and other deposits. The system should then be drained, flushed, refilled with water, and treated with an initial dose of 2.4 to 14.8 fl. oz. Poly-Pro MBC per 1000 gal. water in the system. Subsequent additions of 0.8 to 4.8 fl. oz. per 1000 gal. should be made every 1 to 5 days, depending on amount of slime and severity of microbiological fouling.

CRUDE AND REFINED OILS Poly-Pro MBC is an oil soluble preservative for the control of bacteria and fungi that cause the sour, [illegible] of crude oil and refined fuel oils during storage. It should be added to the oil as it is being transferred from the shipping container to the storage tank at the rate of 2.4 to 24.0 fl. oz. Poly-Pro MBC per 1000 gal. of oil. Addition should be made [illegible] where mixing occurs or continuously to the suction side of the transfer pump.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

STORAGE Do not stack more than four cases high. Leaking or damaged containers should be placed in overpack bags for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

CONTAINER DISPOSAL Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, by incineration, or if allowed by state and local authorities, by burning. If burned, stay out of smoke.