

CAUTION
KEEP OUT OF REACH OF CHILDREN
SEE PRECAUTIONS ON BACK LABEL

U.S. YACHT PAINT

NET 32 FL. OZ. (1 QT.)

tropical anti-fouling

610 HATTERAS COPPER RED

FOR FIBERGLASS & WOOD BOTTOMS

SOFT, CHALKING, AF GOOD, THINNER 950

#610
ACTIVE INGREDIENT
CUPROUS OXIDE 25.0%
INERT INGREDIENTS 75.0%
100.0%
EPA REG. NO. 23566-6

EPA EST NO. 23566-NJ-1

ACCEPTED

JUL 14 1975

Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, the pesticide
registered under
EPA Reg. No. 23566-6

This paint is an antifouling paint for Fiberglass and Wood boat bottoms, available in several colors (see Color Card). It is designed for use under salt water fouling conditions. It brushes easily, and is suitable for amateur as well as professional use.

This paint can be applied by brush or roller. Use the Thinner listed on front label for thinning if needed for good brushing, and for clean-up. On NEW FIBERGLASS (wax washed off with any paint thinner, and well sanded to a finish with 80-150 grit paper) apply 2 coats. On NEW WOOD (sanded clean and smooth with 80-150 grit paper) apply 2-3 coats. For annual repainting of OLD PAINT (scrubbed clean, if sound and tight; well sanded, if rough or "wooded" by sanding or paint remover, if much peeling exists) spot-coat bare spots, and then apply 1-2 coats. Use a respirator when sanding. Do not sand between coats, and wait 6 hours before the next coat. For best results launch boat 12-3 days after last coat, however a delayed launch will still give good results.

This paint can be applied over most old paints. To be sure, apply a small patch near keel and observe for 15 minutes to see if "lifting" occurs.

CAUTION

HARMFUL IF SWALLOWED. MAY CAUSE SKIN IRRITATION.
MAY BE ABSORBED THROUGH SKIN.

If ingested, do not induce vomiting, drink milk, see doctor. Do not breathe spray mist. If eyes, skin, clothing in close contact, remove contaminated clothing and immerse in water. Wash skin with soap and water. For eyes, immediately flush with plenty of water. If not persists, get medical attention. Wash contaminated clothing before reuse.

DO NOT USE, POUR, SPILL, OR STORE NEAR HEAT OR OPEN FLAME.
Avoid storage near food and feed products. Do not reuse container, destroy when empty. Do not contaminate water by cleaning of equipment or disposal of wastes.

U.S. YACHT PAINT CO., ROSELAND, N.J. U.S.A.