

**CAUTION**  
KEEP OUT OF REACH OF CHILDREN  
SEE PRECAUTIONS ON BACK LABEL

# U.S. YACHT PAINT

NET 32 FL OZ. (1 QT)

*tropical anti-fouling*

**611 HATTERAS COPPER BLUE**  
FOR FIBERGLASS & WOOD BOTTOMS  
**SOFT, CHALKING, AF GOOD, THINNER 950**

#611  
ACTIVE INGREDIENTS  
CUPROUS OXIDE 25.0%  
BIS(TRIBUTYL TIN) OXIDE 1.0%  
INERT INGREDIENTS 74.0%  
100.0%  
EPA REG. NO. 23566-7

EPA EST NO. 23566-NJ-1

**ACCEPTED**  
JUN 11 1975  
United States Federal Insecticide,  
Fungicide, and Rodenticide Act  
Registration No. 23566-7  
EPA Reg. No. 23566-7

This paint is an antifouling paint for Fiberglass and Wood boat bottoms. Available in several colors (see Color Card). It is designed for use under fouling conditions. It brushes easily, and is suitable for amateur as well as professional use.

This paint can be applied by brush or roller. Use the Thinner listed on label for thinning if needed for good brushing, and for clean up. **FIBERGLASS** (wax washed off with any paint thinner, and well sanded) finish with 80-150 grit paper) apply 2 coats. On **NEW WOOD** (sanded and smooth with 80-150 grit paper) apply 2-3 coats. For annual repainting of **OLD PAINT** (scrubbed clean, if sound and tight, well sanded, if "wooded" by sanding or paint remover, if much peeling exists) spot-bare spots, and then apply 1-2 coats. Use a respirator when sanding. Sand between coats, and wait 6 hours before the next coat. For launch boats, 2-3 days after last coat, however a delayed launch will give good results.

This paint can be applied over most old paints. To be sure, apply a patch, pour keep and observe for 15 minutes to see if lifting occurs.

**CAUTION**

HARMFUL IF SWALLOWED. MAY CAUSE IRRITATION. MAY BE ABSORBED THROUGH SKIN.

It is advised that you do not eat, drink, or smoke while using this product. Wash your hands thoroughly after use. Avoid breathing dust or fumes. Avoid contact with eyes. If contact occurs, flush with water. Avoid contact with skin. If contact occurs, wash with soap and water. Avoid contact with clothing. If contact occurs, wash with soap and water. Avoid contact with children and pets. If contact occurs, wash with soap and water. Avoid contact with water. If contact occurs, wash with soap and water. Avoid contact with fire. If contact occurs, extinguish with water. Avoid contact with electrical equipment. If contact occurs, unplug equipment and wash with soap and water.

U.S. YACHT PAINT CO., ROSELAND, N.J. U.S.

**WARNING**  
KEEP OUT OF REACH OF CHILDREN.  
SEE PRECAUTIONS ON BACK LABEL

# U.S. YACHT PAINT

NET 32 FL. OZ. (1 QT.)

*tropical anti-fouling*

**641 SUPER VINYL COPPER BLUE**

FOR FIBERGLASS & WOOD BOTTOMS

HARD, NON-CHALKING, AF EXCELLANT, THINNER 952

#641  
ACTIVE INGREDIENT  
CUPROUS OXIDE 35.0%  
INERT INGREDIENTS 65.0%  
100.0%

EPA REG. NO. 23566-8

EPA EST NO. 23566-NJ-1

**ACCEPTED**  
JUL 14 1975  
Under the Federal Insecticide,  
Fungicide, and Rodenticide Act  
as amended, for the pesticide  
registered under  
EPA Reg. No. 23566-8

This paint is an anti-fouling paint for Fiberglass and  
other in several colors (see Color Cards). It is designed for  
fouling conditions. It brushes easily, and is suitable for  
professional use.

This paint can be applied by brush or roller. Use a  
roller for thinning if needed for good brushing. On  
FIBERGLASS, wax washed off with any paint that  
brushes off. 80-150 grit paper, apply 2 coats. On  
WOOD, sand with 80-150 grit paper, apply 2-3 coats.  
OLD PAINT: scrubbed clean, sanded and tight  
wooded, by sanding or paint remover, if much  
bare spots, and then apply 1-2 coats. Use a respirator  
between coats, and wait 6 hours before the  
brush coat. 3 days after last coat, however, a  
brush coat.

Do not use on painted surfaces. If  
paint is present, it should be removed for 15 minutes to  
ensure adhesion.

**WARNING**  
DANGEROUS TO AQUEOUS MEDIA. CAUSE  
OF IRRITATION. KEEP AWAY FROM  
CHILDREN. This paint is highly flammable. It  
should be stored in a cool, dry place. Do not  
mix with other paints and water. For maximum  
protection, use a respirator. Wash your hands  
thoroughly after use.  
**WARNING - FLAMMABLE KEEP AWAY FROM  
FIRE.**

U.S. YACHT PAINT CO., ROSELAND, N.J.