

WARNING
KEEP OUT OF REACH OF CHILDREN.
SEE PRECAUTIONS ON BACK LABEL

U.S. YACHT PAINT

NET 32 FL.OZ.(1QT.)

tropical anti-fouling
640 SUPER VINYL COPPER RED

FOR FIBERGLASS & WOOD BOTTOMS

HARD, NON-CHALKING, AF EXCELLANT, THINNER 952

#640
ACTIVE INGREDIENT
CUPROUS OXIDE 49.1%
INERT INGREDIENTS 50.9%
100.0%

EPA REG. NO. 23566-10

EPA EST NO. 23566-NJ-1

ACCEPTED

JUL 14 1975

Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
registered under
EPA Reg. No. 23566-10

This paint is an antifouling paint for Fiberglass and Wood boat bottoms, available in several colors (see Color Card). It is designed for use under salt water fouling conditions. It brushes easily, and is suitable for amateur as well as professional use.

This paint can be applied by brush or roller. Use the Thinner listed on the label for thinning if needed for good brushing, and for clear cut. On FIBERGLASS: wax washed off with any paint thinner, and well sanded to a finish with 80-150 grit paper; apply 2 coats. On NEW WOOD: sanded to a finish with 80-150 grit paper; apply 2-3 coats. For annual repainting OLD PAINT: scrubbed clean, if sound and tight, well sanded, if rough. If wooded, by sanding or paint remover, if much peeling exists; spot coat bare spots, and then apply 1-2 coats. Use a respirator when sanding. (1) sand between coats, and wait 6 hours before the next coat. For best launch coat 1-3 days after last coat, however a delayed launch will still give good results.

This paint can be applied over most old paints. To be sure, apply a small patch near keel and observe for 15 minutes to see if lifting occurs.

WARNING

HARMFUL IF SWALLOWED. MAY CAUSE SKIN IRRITATION.
MAY BE ABSORBED THRU SKIN.

If ingested, do not induce vomiting; drink milk, see a doctor. Do not breathe spray mist. P. eyes, skin, clothing. In case of skin contact, remove contaminated clothing and immerse in soap and water. For eyes, immediately flush with plenty of water. If persists, get medical attention. Wash contaminated clothing before reuse.

WARNING - FLAMMABLE. KEEP AWAY FROM HEAT OR OPEN FLAME.

Always store near food or feed products. Do not reuse container, destroy when empty. Do not contaminate water by cleaning of equipment or disposal of wastes.

U.S. YACHT PAINT CO., ROSELAND, N.J. U.S.A.

Initial Application: To a cleaned pool add one gallon to 50,000 gallons of water, or ratio thereof.

Maintenance Dose: Use one quart per 50,000 gallons of water every 5 to 7 days. When weather is hot or bathing load is heavy, use this dosage every 5 days or as necessary.

Booster Dose: Immediately after every rain add one quart per 50,000 gallons of water as above.

Important: Follow above directions without fail, even when pool is not used. Algae growth must be fought at all times.

Pool-side surfaces: After cleaning surfaces, use one oz. to four gallons of water for sanitizing or one oz. to two gallons of water for disinfecting. Apply by wiping, mopping, or scrubbing so as to wet surfaces thoroughly with the recommended dilution.

Do not reuse container. Destroy when empty.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds or public water.

Apply this product only as specified on this label.

KEMKO

Swimming Pool

ALGAECIDE

Outstanding Algae Growth Depressant

ACTIVE INGREDIENT:

Alkyl* Dimethyl Benzyl Ammonium Chloride

*(C₁₄, 60%; C₁₂, 25%; C₁₆, 15%)....10%

INERT INGREDIENTS:.....90%

ACCEPTED

APR 21 1975

Manufactured By:
Kemko, Inc.
P.O. Box 392
Deerfield Beach, Fla. 33441
EPA Reg. No. 24069-1

DANGER

Keep Out of Reach of Children.

Corrosive. Causes severe eye and skin damage. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food.

KEMKO Algaecide is efficient, economical and stable in use dilution.

KEMKO Algaecide is compatible with all chemicals used in pool water and will not damage tile, concrete, metal, or plastic.

KEMKO Algaecide keeps pool water free, sparkling, clear of visible algae, slime and green brown colors.

KEMKO Algaecide improves filter operation and cuts down need for other chemicals.

KEMKO Algaecide imparts tone and a pleasant "feel" to swimming pool water.

EPA REG. NO. 24069-1

FIRST AID:

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse. If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution; or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, as well as oxygen and measures to support breathing may be needed.

ACCEPTED WITH COMMENTS