

23566-19

1/5

AUG 04 2003

International Paint Inc
2270 Morris Avenue
Union, N.J. 07083

Attention: John P. Pazdera.
Pesticide Registration Manager

Subject: Copperplus 661 Blue
EPA Registration No. 23566-19
Amendment Dated April 25, 2003

The amendment, submitted in connection with registration under the Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, is acceptable.

- In response to PR Notice 2001-1

Minor Revisions

Change the "Environmental Hazards" statements to read:

ENVIRONMENTAL HAZARDS

This paint is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

General Comments

Submit two (2) copies of the final printed labeling for our review. A stamped copy of the accepted labeling is enclosed for your records. **CONCURRENCES**

SYMBOL								
SURNAME								
DATE								

Page 2
EPA Registration 23566-19

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely,



Marshall Swindell
Product Manager 33
Regulatory Management Branch 1
Antimicrobials Division (7510C)

Enclosure

★ U.S. YACHT ★

a fine paint PAINT *for fine boats*

ACCEPTED

AUG 04 2003

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. **23566-19**

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of our company including surface preparation, proper application, and environmental condition. Therefore, we cannot guarantee this product's suitability for your particular purpose or application. Implied warranties or fitness for a particular purpose and of merchantability are excluded. We shall not, under any circumstances, be liable for incidental or consequential damages. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product, at the company's option.

Keep Out of Reach
of Children
WARNING
SEE SIDE PANELS FOR
ADDITIONAL PRECAUTIONARY
STATEMENTS

ACTIVE INGREDIENT:
CUPROUS OXIDE 43.0%
INERT INGREDIENTS 57.0%
TOTAL: 100.0%
EPA REG. 23566-19
EPA ESTABLISHMENT 2693-NJ-1
CONTAINS PETROLEUM DISTILLATES

STORAGE AND DISPOSAL

STORE IN A DRY AREA AWAY FROM HEAT AND SEVERE COLD. KEEP PARTIALLY USED CONTAINER TIGHTLY SEALED. DO NOT CONTAMINATE WATER, FOOD OR FEED BY STORAGE OR DISPOSAL.

PESTICIDE DISPOSAL

PESTICIDE WASTES ARE TOXIC. IMPROPER DISPOSAL OF EXCESS PESTICIDES OR RINSATE IS A VIOLATION OF FEDERAL LAW. IF THESE WASTES CANNOT BE DISPOSED OF BY USE ACCORDING TO LABEL INSTRUCTIONS, CONTACT YOUR STATE PESTICIDE OR ENVIRONMENTAL CONTROL AGENCY, OR HAZARDOUS WASTE REPRESENTATIVE AT THE NEAREST EPA REGIONAL OFFICE FOR GUIDANCE.

CONTAINER DISPOSAL

TRIPLE RINSE CONTAINER, THEN OFFER IT FOR RECYCLING OR RECONDITIONING, OR PUNCTURE AND DISPOSE OF IN A SANITARY LANDFILL, OR BY OTHER PROCEDURES APPROVED BY STATE AND LOCAL AUTHORITIES.

FIBERGLASS ANTI-FOULING BOTTOM PAINT

COPPER PLUS

661 BLUE

A full season of protection at a money-saving price
Hard, Full Season Powerboat Antifoulant
Polishing Full Season Sailboat Antifoulant
Overcoats Existing Bottom Paint - Fiberglass, Wood, Steel
Manufactured by Interlux, A Division of International Paint Inc.

NET CONTENTS ONE U.S. GALLON (3.785 LITERS)

3/5

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
 CAUSES EYE IRRITATION. HARMFUL IF ABSORBED THROUGH SKIN.
 AVOID CONTACT WITH SKIN, EYES, OR CLOTHING. WEAR PROTECTIVE
 CLOTHING SUCH AS GLOVES, LONG SLEEVED COTTON SHIRT, LONG
 PANTS AND HAT. MAY BE FATAL IF SWALLOWED OR INHALED. DO NOT
 BREATHE DUST, VAPOR, OR SPRAY MIST. WEAR A MASK OR RESPIRA-
 TOR JOINTLY APPROVED BY THE MINING ENFORCEMENT AND SAFETY
 ADMINISTRATION AND BY THE NATIONAL INSTITUTE FOR OCCUPATION-
 AL SAFETY AND HEALTH WHILE SANDING BOAT SURFACES. REMOVE
 CONTAMINATED CLOTHING AND WASH BEFORE REUSE. WASH THOR-
 OUGHLY WITH SOAP AND WATER AFTER HANDLING.

FIRST AID

If Swallowed:

- Immediately call a poison control center or doctor.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give **any** liquid to the person.
- Do not give anything by mouth to an unconscious person.

If on skin or clothing:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

If inhaled:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for further treatment advice.

If in eyes:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

Other: Have the product container or label with you when calling a poison control center or doctor or going for treatment.

Note to Physician: Contains petroleum distillate – vomiting may cause aspiration pneumonia.

ENVIRONMENTAL HAZARDS
 THIS PAINT IS TOXIC TO FISH. DO NOT APPLY DIRECTLY TO WATER BY
 CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES. DO NOT ALLOW
 CHIPS AND DUST FROM PAINT REMOVAL TO ENTER WATER. DISPOSE
 OF PAINT IN AN APPROVED LANDFILL.

PHYSICAL AND CHEMICAL HAZARDS
 DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME.

ACCEPTED
 AUG 04 2003
 Under the Federal Insecticide, Fungicide, and
 Rodenticide Act as amended, for the
 pesticide, registered under
 EPA Reg. No. 235-66-19

5/5

PRODUCT DESCRIPTION: THIS PRODUCT PROVIDES ANTI FOULING PROTECTION AGAINST BARNACLES, ALGAE, AND HYDROIDS IN SALT AND FRESH WATER ON BOAT BOTTOMS ONLY. ITS MODIFIED EPOXY BASE RENDERS A HARD, SMOOTH FINISH WITH DURABILITY AND ABRASION RESISTANCE. IT HAS UNIVERSAL APPLICATION OVER ALL TYPES OF PROPERLY PREPARED BOTTOM PAINTS (EXCEPT ALUMINUM). FOR USE ON FAST FIBERGLASS BOATS, AS WELL AS WOOD AND STEEL HULLS, WHERE A TOUGHER THAN NORMAL COATING IS DESIRED. MAY BE BURNISHED EVEN SMOOTHER FOR RACING SAIL AND POWER BOATS.

DIRECTIONS FOR USE
IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

SURFACE PREPARATION: SURFACE MUST ALWAYS BE CLEAN, DRY AND PROPERLY PREPARED PRIOR TO PAINTING. FAILURE TO DO SO WILL LEAD TO EVENTUALLY BLISTERING AND/OR PEELING. ALL SANDED SURFACES MUST BE WIPED CLEAN WITH [70021 REDUCER/THINNER; WEST MARINE MODEL 329591 REDUCER/THINNER; INTERLUX FIBERGLASS SOLVENT WASH 202; 551 DEWAXER] TO REMOVE SANDING RESIDUE.

GENERAL APPLICATION: FOR USE ON BOATS BELOW THE TRUE WATERLINE. CAN BE BRUSHED OR ROLLED ON FIBERGLASS, WOOD, STEEL AND PREVIOUSLY PAINTED SURFACES PER APPLICATION SYSTEMS BELOW. DO NOT USE ON ALUMINUM. TWO (2) COATS ARE RECOMMENDED FOR BEST PERFORMANCE.

MIXING AND THINNING: SHAKE OR MIX THOROUGHLY AND STIR CONTINUOUSLY WHILE USING. WHEN APPLYING WITH BRUSH OR ROLLER, DO NOT THIN BOTTOM PAINTS.

THEORETICAL COVERAGE: DEPENDING ON SURFACE AND CONDITIONS, ONE GALLON OF BOTTOM PAINT WILL USUALLY COVER OVER 350 SQUARE FEET OF SURFACE WHEN BRUSHED OR ROLLED.

CLEAN UP: USE [70021 REDUCER/THINNER; WEST MARINE MODEL 329591 REDUCER/THINNER; 551 DEWAXER; INTERLUX SPECIAL THINNER 216] FOR CLEANING EQUIPMENT AND PAINT BRUSHES.

ESTIMATED DRY TIMES: BOTTOM PAINTS ARE DESIGNED FOR OVERCOATING AFTER AN OVERNIGHT DRY. PRIOR TO LAUNCHING, ALLOW A MINIMUM DRY OF OVERNIGHT AND MAXIMUM OF 60 DAYS. IF DRYING CONDITIONS ARE POOR, OR IF PAINT WAS APPLIED TOO THICKLY, LONGER PERIODS OF DRYING WILL BE REQUIRED. FRESH COATS

OF PAINT MUST BE THOROUGHLY DRY BEFORE OVERCOATING.

YEARLY REPAINTING: SCRUB BOTTOM CLEAN AT HAUL-OUT. REPAINT ONLY IF OLD PAINT IS SOUND AND TIGHT. IF NOT, REMOVE IT BY SANDING OR WITH PAINT REMOVER. IF OLD PAINT IS ROUGH, SAND IT WITH 100-150 GRIT SANDPAPER. PREPARE SEAMS, NICKS AND CHIPS AS BELOW. SPOT COAT ANY SCUFFS WITH ANTI FOULANT. APPLY 2 COATS OF ANTI FOULANT.

ON BARE WOOD: IF SEAMS ARE NOT FLUSH, FILL THEM WITH SEAM COMPOUND. DRY SEVERAL DAYS UNTIL SKIN FORMS. DO NOT SAND. FILL NICKS WITH [INTERLUX INTERPROTECT WATER TITE V135; TROWEL CEMENT]. DRY HARD. SAND. APPLY [3035 UNDERCOAT PRIMER; 173 UNDERCOAT PRIMER; A HIGH QUALITY UNDERCOAT PRIMER; INTERLUX PRIMOCOAT 360R]. THEN APPLY 2 COATS OF ANTI FOULANT.

ON BARE FIBERGLASS: DEWAX BY WASHING WITH [70021 REDUCER/THINNER; WEST MARINE MODEL 329591 REDUCER/THINNER; 551 DEWAXER; INTERLUX FIBERGLASS SOLVENT WASH 202]. REMOVE DISSOLVED WAX AT ONCE WITH CLEAN PAPER TOWELS OR RAGS. REPEAT. SAND HARD TO A DULL FINISH WITH 80-100 GRIT SANDPAPER. FILL ANY CHIPS WITH INTERLUX INTERPROTECT WATER TITE V135. TROWEL CEMENT. DRY HARD. SAND. APPLY [3035 SUPERCOAT WHITE PRIMER OR 3038 NON SANDING GRAY PRIMER; 179 NO SAND PRIMER OR 173 WHITE UNDERCOAT PRIMER; A HIGH QUALITY MARINE PRIMER OR A HIGH QUALITY MARINE NON SANDING PRIMER; INTERLUX INTERPROTECT 2000E]. THEN APPLY TWO COATS OF ANTI FOULANT.

ON BARE STEEL: SANDBLAST SURFACE TO A NEAR WHITE METAL. REMOVE BLAST RESIDUE WITH A BROOM AND AIR HOSE. WIRE OFF WITH [70021 REDUCER/THINNER; WEST MARINE MODEL 329591 REDUCER/THINNER; 551 DEWAXER; INTERLUX FIBERGLASS SOLVENT WASH 202]. DO NOT SAND. FILL IN ANY IMPERFECTIONS WITH FAIRING COMPOUND. SAND SMOOTH AND WIPE CLEAN. APPLY 3 COATS OF [3037 RED OXIDE PRIMER OR 3039 ZINC CHROMATE PRIMER; 2408 RED LEAD PRIMER OR B304 2 PART RED EPOXY PRIMER; A HIGH QUALITY MARINE RED OXIDE PRIMER OR A HIGH QUALITY MARINE ZINC CHROMATE PRIMER; INTERLUX INTERPROTECT 2000E]. FOLLOWED BY TWO COATS OF BOTTOM PAINT.

Interlux

INTERNATIONAL PAINT INC.

2270 MORRIS AVENUE • UNION, NJ 07083 • 800-628-8422

ACCEPTED

AUG 04 2003

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 23566-19