



U.S. ENVIRONMENTAL PROTECTION AGENCY
 Office of Pesticide Programs
 Antimicrobials Division (7510P)
 1200 Pennsylvania Ave., N.W.
 Washington, D.C. 20460

EPA Reg. Number:

23566-19

Date of Issuance:

9/18/2019

NOTICE OF PESTICIDE:

Registration
 Reregistration
 (under FIFRA, as amended)

Term of Issuance:

Unconditional

Name of Pesticide Product:

Copperplus 661 Blue

Name and Address of Registrant (include ZIP Code):

Bathsheba Njuguna
 PSRA Team Leader
 Akzo Nobel
 6001 Antoine Drive
 Houston, TX 77091

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Antimicrobials Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended. Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on her/his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

EPA received a label amendment request submitted by email on September 16, 2019. EPA grants this request under the authority of section 3(c)(5) of FIFRA, as amended. With this accepted labeling, all requirements set forth in the Reregistration Eligibility Decision for Coppers have been satisfied. Therefore, EPA reregisters the product listed above. This action is taken under the authority of section 4(g)(2)(c) of FIFRA, as amended. Reregistration under this section does not eliminate the need for continual reassessment of pesticides. EPA may require submission of data at any time to maintain the registration of your product.

Submit one (1) copy of final printed labeling. Amended labeling will supersede all previously accepted labels. A copy of your label stamped "Accepted" is enclosed for your records. Products shipped after 12 months from the date of this Notice or the next printing of your label, whichever occurs first, must bear the new revised label.

Signature of Approving Official:

E. Miederhoff
 Eric Miederhoff, Product Manager 31
 Regulatory Management Branch I
 Antimicrobials Division (7510P)
 Office of Pesticide Programs

Date:

9/18/2019

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Compliance.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6. Your release for shipment of the product constitutes acceptance of these conditions. A stamped copy of the label is enclosed for your records.

Please also note that the record for this product currently contains the following CSFs:

- Basic CSF dated 11/21/2014
- Alternate CSF 1-10 dated 11/21/2014

If you have any questions, you may contact Joseph Daniels at (703) 347-8669 or via email at Daniels.joseph@epa.gov.

Enclosure

FIBERGLASS ANTI-FOULING BOTTOM PAINT COPPER PLUS 661 BLUE

A full season of protection at a money-saving price
Hard, Full Season Powerboat Antifoulant
Polishing Full Season Sailboat Antifoulant
Overcoats Existing Bottom Paint – Fiberglass, Wood, Steel
Manufactured by Interlux, A Division of International Paint LLC

ACCEPTED

09/18/2019

Under the Federal Insecticide, Fungicide
and Rodenticide Act as amended, for the
pesticide registered under

EPA Reg. No. 23566-19

KEEP OUT OF REACH OF CHILDREN

WARNING

See side panel for additional precautionary statements

NET CONTENTS: ONE U.S. GALLON (3.785 LITERS)

EPA Registration No. 23566-19
EPA Establishment No. 2693-TX-1

Active Ingredient:	Percent
Cuprous Oxide CAS #1317-39-1	43.00%
Other Ingredients	<u>57.00%</u>
Elemental Copper 37.9%	100.00%

CONTAINS PETROLEUM DISTILLATES

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of International Paint LLC including surface preparation, proper application and environmental conditions. Therefore, International Paint LLC cannot guarantee this product's suitability for your particular purpose or application. **IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND OF MERCHANTABILITY ARE EXCLUDED. INTERNATIONAL PAINT LLC SHALL NOT, UNDER ANY CIRCUMSTANCES, BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.** By purchase or use, of the product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at International Paint LLC's option.

**International Paint LLC
6001 Antoine Drive
Houston, TX 77091**

Interlux.com

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
KEEP OUT OF REACH OF CHILDREN**

WARNING

WARNING. Causes substantial but temporary eye injury. Harmful if absorbed through skin. Do not get in eyes or on clothing. Avoid contact with skin. Wear goggles, face shield, or safety glasses. Wear chemical protective gloves, long sleeved shirt, long pants and hat. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Remove and wash contaminated clothing before reuse.

Personal Protective Equipment (PPE):

Mixers, loaders, applicators, and other handlers must wear the following:

-goggles, face shield, or safety glasses, long-sleeved shirt, chemical protective gloves, long pants, shoes plus socks

Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry. Discard clothing and other absorbent material that have been drenched or heavily contaminated with the product's concentrate. Do not reuse them.

USER SAFETY RECOMMENDATIONS

Users should wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet.

Users should remove clothing/PPE immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing.

Users should remove PPE immediately after handling this product. As soon as possible, wash thoroughly and change into clean clothing.

FIRST AID

If in eyes:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

If on skin or clothing:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

If inhaled:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for further treatment advice.
-

If Swallowed:

- Immediately call a poison control center or doctor.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give **any** liquid to the person.
- Do not give anything by mouth to an unconscious person.

Other: Have the product container or label with you when calling a poison control center or doctor or going for treatment.

Note to Physician: Contains petroleum distillate – vomiting may cause aspiration pneumonia.

Medical Advisory Number: Contact your local Poison Control Center or call 1-800-854-6813.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARDS

Combustible: Do not store or use the product near heat or open flame.

STORAGE AND DISPOSAL:

Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited. Keep From Freezing

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Non-refillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

NOTE: Protective Clothing/PPE should be used as described under Precautionary Statements.

GENERAL DESCRIPTION

This product is an antifouling protective coating resistant to algae, barnacles, zebra mussels and other marine fouling. For use in fresh, salt and brackish waters.

[Directions for Use for Pleasure Craft]

PRODUCT DESCRIPTION: FIBERGLASS BOTTOMKOTE® provides excellent, long term antifouling protection against marine growth. Its modified epoxy base renders a hard, smooth finish with outstanding durability and abrasion resistance. It has universal application over all types of properly prepared bottom paints and surfaces (except aluminum). Ideal for use on fast fiberglass boats, as well as wood and steel hulls, when a tougher than normal coating is desired. May be burnished even smoother for racing sail and power boats.

SURFACE PREPARATION: Surface must always be clean, dry and properly prepared prior to painting. Failure to do so will lead to eventual blistering and/or peeling. All sanded surfaces must be wiped clean with INTERLUX SPECIAL THINNER 216 to remove sanding residue.

GENERAL APPLICATION: For use on boats below the true waterline. Can be brushed or rolled on fiberglass, wood, steel and previously painted surfaces per application systems below. **Do not use on aluminum.** Two (2) coats are recommended for best performance.

MIXING & THINNING: Shake or mix thoroughly and stir continuously while using. When applying with brush or roller, do not thin bottom paints.

THEORETICAL COVERAGE: Depending on surface and conditions, one gallon of bottom paint will usually cover 350 square feet of surface when brushed or rolled.

CLEAN-UP: Use INTERLUX SPECIAL THINNER 216 for cleaning equipment and paint brushes.

ESTIMATED DRY TIMES: INTERLUX bottom paints are designed for overcoating after an overnight dry. Prior to launching, allow a minimum dry of overnight and a maximum of 60 days. If drying conditions are poor, or if paint was applied too thickly, longer periods of drying will be required. Fresh coats of paint must be thoroughly dry before overcoating.

APPLICATION SYSTEMS

PREVIOUSLY PAINTED SURFACES – Good Condition: Remove all traces of loose paint and contamination by sanding the entire surface well with 80-120 grit production paper; wipe surface clean. Apply 2 coats of bottom paint.

Poor Condition: Completely remove all old paint with INTERLUX PINTOFF 299 for fiberglass, INTERLUX PINTOFF 199 for wood and by sandblasting steel surfaces to a near white metal. Proceed with application system for bare work as described below.

BARE FIBERGLASS – No Sand System: Wash entire surface thoroughly with INTERLUX FIBERGLASS SOLVENT WASH 202, changing rags frequently. Before liquid dries, wipe clean with a dry cloth. (Be sure all wax contaminants are removed.) Repair imperfections with EPOXY SURFACING AND FAIRING COMPOUND 417A/418B; sand and wipe clean. Apply one thin continuous coat of INTERLUX NO SAND PRIMER AL 200 with brush or roller. Do not spray, do not sand. Allow to cure between 2-3 hours – no more, no less. Apply two coats of bottom paint.

Sanding System: Wash entire surface thoroughly with INTERLUX FIBERGLASS SOLVENT WASH 202, changing rags frequently. Before liquid dries, wipe clean with a dry cloth. (Be sure all wax contaminants are removed.) Repair imperfections with EPOXY SURFACING AND FAIRING COMPOUND 417A/418B; sand and wipe clean. Sand entire gelcoat well with 80-120 grit production paper until a flat, matte finish is obtained, wipe surface clean. Apply two coats of bottom paint.

BARE WOOD: Sand entire surface thoroughly to a smooth finish with 80 grit production paper; wipe surface clean. Repair imperfections with EPOXY SURFACING AND FAIRING COMPOUND 417A/418B; sand and wipe clean. Apply first coat of bottom paint reduced with INTERLUX SPECIAL THINNER 216 (10% maximum) to penetrate the porous grain. Fair seams with INTERLUX SEAM COMPOUND 30. Apply second and third coats of bottom paints unreduced.

***BARE STEEL:** Sandblast surface to a near white metal; remove blast residue with a broom and air hose. Immediately apply one very thin coat of VINY-LUX PRIMEWASH 353/354; allow to dry a minimum of 1 hour, maximum of 24. Do not sand. Fill in all imperfections with EPOXY SURFACING & FAIRING COMPOUND 417A/418B; sand smooth and wipe clean. Apply 3 coats of INTERLUX UNDERWATER METAL PRIMER 360R; allow a minimum of 3 hours for the first coat to dry, 6 hours for the second and overnight for the third. Apply two coats of bottom paint.

* This is a simple system for small areas. For a more advanced, professional system, please consult the INTERLUX Technical Department, P.O. Box 386, Union, NJ 07083.

[Alternate Directions for Use for Commercial Vessels]

This product is an antifouling protective coating resistant to algae, barnacles and other marine fouling.

SURFACE PREPARATION AND COMPATIBILITY: Surface preparation directions must be followed exactly in order to ensure adhesion. Surface must always be clean and dry prior to painting.

GENERAL APPLICATION PROCEDURES: Airless spray is recommended. Tip Size 21-26 thou. inch pump ratio of 30:1 or greater. For small areas, brush or roller may be used, but multiple coats may be required to achieve the required dry film thickness. It is recommended to apply by airless spray one (1) or two (2) full coats of this product.

MIXING AND THINNING INSTRUCTIONS: Mix thoroughly with power mixer prior to application. This coating is designed to be applied without thinning. Should thinning be necessary, consult your International representative prior to altering this coating.

CLEANUP: For tools, equipment, etc., use International GTA007.

MINIMUM DRY AND LAUNCHING TIMES: Minimum drying time between coats is 6 hours, and before launching is 12 hours at a temperature of 73°F.

THEORETICAL COVERAGE: 385 square feet per gallon, per coat at 2.0 mils D.F.T. Consult your International representative for practical application coverages. Practical square foot coverage per gallon, per coat is directly proportional to surface application techniques and climatic conditions.

APPLICATION SYSTEMS

EXISTING ANTIFOULING SYSTEMS – GOOD CONDITION: High pressure fresh water wash with a minimum 2500 p.s.i. and/or scrape to remove all marine growth, slime, salts, etc. Spot blast all areas of corrosion to a Near White Metal Standard of SSPC-SP10-85. Blow down with clean and dry high pressure air to remove spent abrasives. Apply an approved underwater anticorrosive system.

POOR CONDITION: For “optimum” results, blast entire area to a Near White Metal Standard SSPC-SP-10-85. Apply an approved underwater anticorrosive system.

NEW BUILDING: Blast entire area to a Near White Metal Standard SSPC-SP10-85. Blow down with clean, dry high pressure air to remove all spent abrasives. Apply an approved underwater anticorrosive system.

WOOD AND NON-FERROUS SURFACES: Use surface preparation and primers as specified by the Navy.