

	U.S. ENVIRONMENTAL PROTECTION AGENCY Office of Pesticide Programs Registration Division (H750SC) 401 "M" St., S.W. Washington, D.C. 20460	EPA Reg. Number: 23566-20	Date of Issuance: 10/31/95	
	NOTICE OF PESTICIDE: <u> X </u> Registration <u> </u> Reregistration	Term of Issuance: Conditional		
	(under FIFRA, as amended)	Name of Pesticide Product: Bio C ³ Continuous Copper Copolymer		
Name and Address of Registrant (include ZIP Code): <div style="text-align: center;"> U.S. Yacht Paint Co., Inc. 1525 Route 1 South North Brunswick, NJ 08902 </div>				
Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.				
<p>On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.</p> <p>Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.</p> <p style="text-align: center;">This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:</p> <ol style="list-style-type: none"> 1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4. 2. Make the following label changes: <ol style="list-style-type: none"> a. Revise the EPA Registration Number to read, "EPA Reg. No. 23566-20". b. Move the heading "Directions For Use" and the misuse statement so that they appear above the "Surface Preparation" portion of the use directions. 				
Signature of Approving Official:  Marion J. Johnson, Product Manager 31		Date: 		


3. Submit two copies of the revised final printed label for the record.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

If you have any questions concerning this letter please contact Marshall Swingell at 703-305-6908.

Sincerely yours,


Marion Johnson
Product Manager 31
Antimicrobial Programs Branch
Registration Division (7505C)

★ U.S. YACHT ★ PAINT

Keep Out of Reach
of Children

WARNING
See Side Panels for
Additional Precautionary
Statements

Active Ingredient
Cuprous oxide55.
Inert Ingredients ...45.
Total.....100.

EPA Reg.No.23566-20
EPA Establishment No.

MULTI-SEASON ANTI-FOULING BOTTOM PAINT

BIO C³ CONTINUOUS COPPER COPOLYMER

3901 BLUE

NET CONTENTS ONE U.S. GALLON (3.785 LITERS)

DISCLAIMER: The performance of any product is subject to various conditions, including but not limited to, the condition of the surface to which it is applied, the skill of the user, and the weather conditions. Therefore, no warranty is made by the manufacturer for the performance of this product under any conditions other than those stated on the label. The user assumes all responsibility for the results of the use of this product. The manufacturer disclaims any liability for damages, including but not limited to, property damage, personal injury, or death, resulting from the use of this product. The user should read and follow the instructions on the label and the safety data sheet carefully. If any doubt exists, the user should consult the manufacturer for further information.

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

STORAGE AND DISPOSAL

STORE IN A DRY AREA AWAY FROM HEAT AND SEVERE COLD. KEEP PARTIALLY USED CONTAINER TIGHTLY SEALED. DO NOT CONTAMINATE WATER, FOOD OR FEED BY STORAGE OR DISPOSAL.

PESTICIDE DISPOSAL

PESTICIDE WASTES ARE TOXIC. IMPROPER DISPOSAL OF EXCESS PESTICIDES OR PESTICIDES IS A VIOLATION OF FEDERAL LAW. IF THESE WASTES CANNOT BE DISPOSED OF BY USE ACCORDING TO LABEL INSTRUCTIONS, CONTACT YOUR STATE PESTICIDE OR ENVIRONMENTAL CONTROL AGENCY OR HAZARDOUS WASTE REPRESENTATIVE AT THE NEAREST EPA REGIONAL OFFICE FOR GUIDANCE.

CONTAINER DISPOSAL

TRIPLE RINSE CONTAINER, THEN OFFER IT FOR RECYCLING OR RECONDITIONING, OR PUNCTURE AND DISPOSE OF IN A SANITARY LANDFILL OR BY OTHER PROCEDURES APPROVED BY STATE AND LOCAL AUTHORITIES.

ACCEPTED
with COMMENTS
in EPA Letter Dated:

BEST COPY AVAILABLE

OCT 31 1995

Under the provisions of the
Fungicide, and Rodenticide
Act, amended, for the pest
registered under EPA Reg.
23566-20

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUSES EYE IRRITATION. HARMFUL IF ABSORBED THROUGH SKIN. AVOID CONTACT WITH SKIN, EYES, OR CLOTHING. WEAR PROTECTIVE CLOTHING SUCH AS GLOVES, LONG SLEEVED COTTON SHIRT, LONG PANTS AND HAT. MAY BE FATAL IF SWALLOWED OR INHALED. DO NOT BREATHE DUST, VAPOR, OR SPRAY MIST. WEAR A MASK OR RESPIRATOR JOINTLY APPROVED BY THE MINING ENFORCEMENT AND SAFETY ADMINISTRATION AND BY THE NATIONAL INSTITUTE FOR OCCUPATIONAL SAFETY AND HEALTH WHILE SANDING BOAT SURFACES. REMOVE CONTAMINATED CLOTHING AND WASH BEFORE REUSE. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING.

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: DRINK PROMPTLY A LARGE QUANTITY OF WATER. AVOID ALCOHOL. GET MEDICAL ATTENTION.
IF IN EYES: FLUSH WITH PLenty OF WATER. GET MEDICAL ATTENTION.
IF ON SKIN: WASH WITH PLenty OF SOAP AND WATER. GET MEDICAL ATTENTION.
IF INHALED: REMOVE VICTIM TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. REFERENTLY MOUTH TO MOUTH. GET MEDICAL ATTENTION.

ENVIRONMENTAL HAZARDS

THIS PAINT IS TOXIC TO FISH. DO NOT APPLY DIRECTLY TO WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES. DO NOT ALLOW CHIPS AND DUST FROM PAINT REMOVAL TO ENTER WATER. DISPOSE OF PAINT IN AN APPROVED LANDFILL.

PHYSICAL AND CHEMICAL HAZARDS

DO NOT USE OR BE NEAR HEAT OR OPEN FLAME.

U.S. YACHT PAINT COMPANY
1525 ROUTE 1 SOUTH NORTH BRUNSWICK, NJ 08902
1-800-586-8888

PRODUCT DESCRIPTION: BIOOD® PROVIDES MULTISEASON ANTIFOULING PROTECTION AGAINST BARNACLES, ALGAE, AND HYDROIDS IN SALT AND FRESH WATER ON BOAT BOTTOMS ONLY. ITS ABLATIVE COPOLYMER BASE RENDERS A HARD, SMOOTH FINISH WITH DURABILITY AND ABRASION RESISTANCE. BIOOD® RELEASES BIOCIDES BY THE CONSTANT EXPOSURE OF NEW PAINT FILM TO THE WATER. IT HAS UNIVERSAL APPLICATION OVER ALL TYPES OF PROPERLY PREPARED BOTTOM PAINTS (EXCEPT ALUMINUM). FOR USE ON FAST FIBERGLASS BOATS, AS WELL AS WOOD AND STEEL HULLS. EXTENDED PROTECTION IS POSSIBLE, SINCE PERFORMANCE IS DIRECTLY PROPORTIONAL TO THE AMOUNT OF PAINT APPLIED.

SURFACE PREPARATION: SURFACE MUST ALWAYS BE CLEAN, DRY AND PROPERLY PREPARED PRIOR TO PAINTING. FAILURE TO DO SO WILL LEAD TO EVENTUALLY BUSTERING AND/OR PEELING. ALL SANDED SURFACES MUST BE WIPE CLEAN WITH 70021 REDUCER/THINNER TO REMOVE SANDING RESIDUE.

GENERAL APPLICATION: FOR USE ON BOATS BELOW THE TRUE WATERLINE. CAN BE BRUSHED OR ROLLED ON FIBERGLASS, WOOD, STEEL AND PREVIOUSLY PAINTED SURFACES PER APPLICATION SYSTEMS BELOW. DO NOT USE ON ALUMINUM. APPLY AT LEAST 3 COATS FOR BEST PERFORMANCE. AS THE LIFE OF THE PAINT IS PROPORTIONAL TO THE NUMBER OF COATS APPLIED.

MIXING AND THINNING: SHAKE OR MIX THOROUGHLY AND STIR CONTINUOUSLY WHILE USING. THIN WHEN NECESSARY WITH 70021 REDUCER/THINNER.

THEORETICAL COVERAGE: DEPENDING ON SURFACE AND CONDITIONS, ONE GALLON OF BOTTOM PAINT WILL USUALLY COVER OVER 350 SQUARE FEET OF SURFACE WHEN BRUSHED OR ROLLED.

CLEAN UP: USE 70021 REDUCER/THINNER FOR CLEANING EQUIPMENT AND PAINT BRUSHES.

ESTIMATED DRY TIMES: BOTTOM PAINTS ARE DESIGNED FOR OVERCOATING AFTER AN OVERNIGHT DRY. PRIOR TO LAUNCHING, ALLOW A MINIMUM DRY OF OVERNIGHT AND MAXIMUM OF 60 DAYS. IF DRYING CONDITIONS ARE POOR, OR IF PAINT WAS APPLIED TOO THICKLY, LONGER PERIODS OF DRYING WILL BE REQUIRED. FRESH COATS OF PAINT MUST BE THOROUGHLY DRY BEFORE OVERCOATING.

YEARLY REPAINTING: SCRUB BOTTOM CLEAN AT HAUL-OUT. REPAINT ONLY IF OLD PAINT IS SOUND AND TIGHT. IF NOT, REMOVE IT BY SANDING OR WITH PAINT REMOVER. IF OLD PAINT IS ROUGH, SAND IT WITH 100-150 GRIT SANDPAPER. PREPARE SEAMS, NICKS AND CHIPS AS BELOW. SPOTCOAT ANY SCUFFS WITH ANTIFOULANT. APPLY 3 COATS OF ANTIFOULANT.

ON BARE WOOD: IF SEAMS ARE NOT FLUSH, FILL THEM WITH BEAM COMPOUND. DRY SEVERAL DAYS UNTIL SKIN FORMS. DO NOT SAND. FILL NICKS WITH TROWEL CEMENT. DRY HARD, SAND, APPLY 3035 UNDERCOAT PRIMER, THEN APPLY 3 COATS OF ANTIFOULANT.

ON BARE FIBERGLASS: DEWAX BY WASHING WITH 70021 REDUCER. REMOVE DISSOLVED WAX AT ONCE WITH CLEAN PAPER TOWELS OR RAGS. REPEAT. SAND HARD TO A DULL FINISH WITH 80-100 GRIT SANDPAPER. FILL ANY CHIPS WITH TROWEL CEMENT. DRY HARD, SAND, APPLY 3035 SUPERCOAT WHITE PRIMER OR 3038 NON-SANDING GRAY PRIMER, THEN APPLY 3 COATS OF ANTIFOULANT.

ON BARE STEEL: SANDBLAST SURFACE TO A NEAR WHITE METAL. REMOVE BLAST RESIDUE WITH A BROOM AND AIRHOSE. WIPE OFF WITH 70021 REDUCER/THINNER. DO NOT SAND. FILL IN ANY PERFECTIONS WITH FAIRING COMPOUND. SAND SMOOTH AND WIPE CLEAN. APPLY 3 COATS OF 3037 RED OXIDE PRIMER OR 3039 ZINC CHROMATE PRIMER, FOLLOWED BY 3 COATS OF ANTIFOULANT.

ACCEPTED
with COMMENTS
by EPA Letter Dated:

OCT 31 1995

Under the Clean Air Act, the
Fungicide, and Rodenticide Act
as amended, for the pesticide
registered under EPA Reg. No.

23566-20

BEST COPY AVAILABLE