

Directions for Use

For best results, use the following directions for each treatment.

Where to Use

Wood Treatment

To treat wood, soak treated lumber in solution for at least 10 minutes. Soaking time may vary depending on the type of wood. It is most important to allow enough time for solution to penetrate wood fibers. Apply, after thorough soaking, to all exposed surfaces. Allow a minimum of one day to dry the wood before using. This is to insure that the wood has been treated. Do not paint or varnish wood that has been treated with Preservative until it has dried for 48 hours.

Subterranean Termites—Directions for Homeowner Use.

Termite Control in Existing Structures

Buildings with Basements or Crawl Spaces

First remove all wood debris and wood forms. Drill holes in piles, chimney bases and along foundations of poured concrete 1/4 inch wide 6 inches apart. Drill holes in brick and block foundations along the trench about 12 inches deep. If footing is more than 12 inches deep, make holes with a crowbar pile or a rod about one foot apart that extend from the trench bottom to the top of the footing. Make holes closer in hard-packed clay soils. NEVER DIG BELOW THE TOP OF THE FOOTING. Apply the solution in the trench at a rate of 4 gallons per 10 linear feet per foot of depth. Apply half of this to the crawl-space. Treat along the inside of foundations of crawl-space buildings. Cover treated soil with a thin layer of untreated soil.

For raised porches, terraces and entrance steps, drill holes at one foot intervals, 6 inches from the foundation, and pour one-half gallon of solution into each hole. Refill holes. Drabs with heat ducts or radiating heat pipes should be treated by commercial pest control operator.

The object is to establish a treated soil barrier which will prevent termite entry. Other critical areas may also require treatment, particularly if there are inaccessible areas, basements or slab-type construction. It is suggested that you contact the Agricultural Cooperative Extension Service for advice or consult a commercial pest control service.

Avoid contamination of public and private water supplies by following these precautions. Do not allow a hose or any type of faucet extension to reach into the termite chemical solution while filling or mixing this material with water. Use anti-backflow anti-siphonage equipment on all filling equipment. These devices can be purchased at hardware or plumbing supply stores. Use of anti-backflow equipment will help to insure that the user of this toxic chemical will not contaminate domestic water supplies. Refer to Federal (Federal Housing Administration), state and local specifications for safe distances of treatment areas from wells. Soil in the vicinity of wells, cisterns or ponds should not be treated if it is water saturated, subject to excessive saturation due to an accumulation of water or if the soil to be treated around the perimeter of the structure is at a grade lower than surrounding yard or property area. If this is the situation, treat as follows: DO NOT APPLY UNDER PRESSURE. Soil should be removed to an area safe from well or domestic water contamination, treated, allowed to stand undisturbed for 2-4 hours, then returned to the trench which has been lined with 4 mil plastic sheeting. Be careful not to puncture the plastic sheeting when returning soil to the trench. Do not treat structures that contain cisterns or wells.

Estimated Coverage

Wood Treatment: Five to ten gallons per thousand board feet for open tank treating. Two hundred square feet per gallon for brush application.

Subterranean Termite Control: Four gallons per 10 linear feet per foot of depth for trench treatment.

BEST DOCUMENT AVAILABLE

JT 15453 LR557

ACTIVE INGREDIENTS	4.46%
Pentachlorophenol	4.46%
Other chlorophenois and related compounds	52%
INERT INGREDIENTS	95.02%
	100.00%
Preservative contains 5.19% of Technical Pentachlorophenol as defined in Federal Specification TT-W-570	

Manufactured By:
The Enterprise Companies
Wheeling, Illinois 60090
An **Insilco Company**

DRENCHER
kills termites
protects wood

 ENTERPRISE

water repellent

penta wood preservative

KEEP OUT OF THE REACH OF CHILDREN

WARNING: 5% ACETONE 75% PENTACHLOROPHENOL 1% DIBROMINE

EPA REG. NO. 25014-4 EPA EST. NO. 9232-HL-1

2026-01 1 GALLON 128 FL. OZ. 3.785 LITERS

1140

38044 4

Precautionary Statements

Hazards to Humans and Domestic Animals

WARNING. COMBUSTIBLE: CONTAINS PETROLEUM DISTILLATES. HARMFUL OR FATAL IF SWALLOWED OR HARMFUL IF ABSORBED THROUGH SKIN.

Causes skin irritation USE WITH ADEQUATE VENTILATION. (Keep a constant flow of fresh air during and after use) Keep container closed when not in use. Do not breathe vapor or spray mist. Do not get in eyes, on skin or on clothing. Wash thoroughly after handling. Wear rubber gloves and protective waterproof clothing when handling the freshly treated lumber. Vapors will cause injury if adequate ventilation is not assured. Do not apply this product indoors or in any other confined areas where the vapors may concentrate and cause injury to plant or animal life.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of waste.

STORAGE AND DISPOSAL

Do not reuse empty container (bottle, can, bucket). Wrap container and cut in trash collection.

PHYSICAL AND CHEMICAL HAZARDS

DO NOT USE POUR, SPILL OR STORE NEAR HEAT OR OPEN FLAME