WARCO ALGAECIDE-30

MANUFACTURED BY WARREN COOK CHEMICALS, INC. OAK & ASTOR STS. MONEE, ILLINOIS 60449

COMPOSITION

Active ingredient	Percent by weight 30 percent
Poly (oxyethylene (dimethylim ethylene (dimethyliminio)- eth dichloride)	inio) ylene 30.0 percent
Inert ingredient	70 percent
Weight per gallon	8.90 pounds
Weight of active ingredient per galion	2.67 pounds

CAUTION KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. Avoid contact with skin eyes. In case of contact flush with plenty of water for at least 15 minutes. If eye irritation persists get medical attention. Avoid contamination of food.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds or public water. Do not contaminate water by cleaning of equipment or disposal of waste. Use only as directed on label. Do not reuse container. Destroy when empty.



APPLICATION

WARCO ALGAECIDE-30 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 1.90 to 4.75 fluid ounces of WARCO ALGAECIDE-30 per 1000 gallons of water to provide a concentration of 16 to 40 parts per million of WARCO ALGAECIDE-30 based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 0.47 to 4.75 fluid ounces of WARCO ALGAECIDE-30 per 1000 gallons of water (4 to 40 parts per million of WARCO AL-GAECIDE-30) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of infeeliof and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

UPDER THE FEDERAL INSPONCED FOR THE EPA RESIDENCE POISONOMIC POISO