

EMERGENCY TREATMENT HAZARDOUS INFORMATION

DANGER: ...

FIRST AID: In case of contact immediately flush eyes or skin with plenty of water for at least 15 minutes. Call a physician. If contaminated clothing promptly and wash before re use. If swallowed give large quantities of water. Give at least 1 ounce of milk of magnesia, aluminum hydroxide gel in an equal amount of water. If these are not available give milk, white of 2 or 3 eggs or gelatin solution. Never give anything by mouth to an unconscious person. Call a physician.

ENVIRONMENTAL HAZARD: This product is toxic to fish. Treated effluent should not be discharged into streams, ponds, or public water. Do not contaminate water by cleaning of equipment or disposal of wastes.


PERSONAL HAZARD: Contact with other materials may cause fire or explosion or result in dangerous pressure, especially if heated. Contact with water or moist air may be irritating or hazardous gases.

IN CASE OF FIRE: Use water spray to cool containers exposed to heat and in case of fire use water spray to cool material. Noxious fumes can be formed. Wear full protective clothing and self contained breathing apparatus.

STORAGE: Store in cool, well ventilated area. Keep out of sun and away from heat. Keep containers tightly closed. Do not use if container is damaged or leaking. Use polyethylene bags after use. Do not use if container is damaged or leaking.

SPILLAGE: Sweep up and dispose of in accordance with local, state and federal regulations. Do not discharge into water.

Paddock

QUALITY  CHEMICALS

PAD CHEM

Active Ingredient: Sodium Dichloro-s-triazinetriene ... 100%

DRY GRANULAR CHLORINATING PRODUCT

62% AVAILABLE CHLORINE

DANGER: KEEP OUT OF REACH OF CHILDREN. CORROSIVE

SEE SIDE PANEL FOR FIRST AID AND ADDITIONAL PRECAUTIONARY STATEMENTS

Manufactured By: **PADDOCK POOL CONSTRUCTION CO.**
8625 E. Thomas Road
Scottsdale, Arizona 85261

ESTABLISHMENT NO. 27570-AZ-1 NET WT LBS.
EPA REG. NO. 27570-3

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

1. ... with a reliable test kit. If label of PAD CON stabilizer. Omit if this has been done previously.
2. ... immediately and at least once each week with a reliable pool test kit. Adjust pH to 7.2 - 7.8 if necessary. pH can be decreased by adding a suitable agent such as Sodium Bisulphite or increased by adding a suitable agent such as Soda Ash. Follow directions for use on label of these products.
3. ... with a reliable test kit. If below 1.0 - 1.5 ppm, add 2 ounces of PAD CHEM for each 10,000 gallons of water. (2 ounces of PAD CHEM per 10,000 gallons of water will provide 1.0 ppm chlorine residual). Additional dosages (2 oz per 10,000 gal) may be required to maintain the 1.0 - 1.5 ppm chlorine residual during exceptionally hot weather or when many people are using the pool. Additions of PAD CHEM should be made by broadcasting the granules into the water at the deepest end of the pool.
4. ... It is good practice to "super-chlorinate" every 2 - 4 weeks by broadcasting 10 ounces of PAD CHEM over the deep end of the pool when not in use and then resume regular maintenance program when chlorine residual falls to 1.0 to 1.5 ppm.

Paddock

ACCEPTED

5 AUG 1977

37570-3

FEDERAL BUREAU OF INVESTIGATION
U.S. DEPARTMENT OF JUSTICE
RECEIVED IN REGISTERED MAIL