


MIDLAND 670



PRECAUTIONARY STATEMENTS

Hazards to Humans and Domestic Animals.

DANGER

Highly corrosive. Causes skin and eye damage. May be fatal if swallowed. Do not get in eyes, on skin, or on clothing. Do not handle with bare hands. Wear goggles or face shield and use neoprene gloves and only thoroughly clean utensils when handling. Irritating to nose and throat. Avoid breathing fumes. Remove and wash contaminated clothing to avoid fire.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not discharge into lakes, streams, ponds, or public waters unless in accordance with an NPDES permit. For guidance contact your regional office of EPA.

CHEMICAL HAZARDS

Danger: Strong oxidizing agent. Mix only into water. Contamination may start a chemical reaction with generation of heat, liberation of hazardous gases (chloride dioxide, a poisonous, explosive gas), and possible fire and explosion. Do not contaminate with garbage, dirt, organic matter, household products, chemicals, soap products, paint products, solvents, acids, vinegar, beverages, oils, pine, dirty rags, or any other foreign matter.

STORAGE AND DISPOSAL

Keep product dry in tightly closed container when not in use. Do not drop, roll or skid drum. Keep upright. Always replace cover. Store in a cool, dry, well-ventilated area away from heat or open flame. Do not reuse empty container. Rinse empty container thoroughly with water before discarding. Place in trash collection or dispose in approved landfill area or bury in a safe place.

EMERGENCY HANDLING

In case of contamination or decomposition, do not reseal container. If possible, isolate container in open and well-ventilated area. Flood with large volumes of water. If fire occurs, extinguish fire by applying large quantities of water. Any unopened drums near the fire should be cooled by spraying with water.

ACTIVE INGREDIENT	
Sodium Chlorite*	25%
INERT INGREDIENTS	75%
TOTAL	100%
*Available chlorine	39%
CONTAINS 2.58 LBS. OF SODIUM CHLORITE PER GALLON AT 70°F.	

KEEP OUT OF REACH OF CHILDREN

DANGER STATEMENT OF PRACTICAL TREATMENT

If on skin: Brush off excess chemicals and flush skin with cold water for at least 15 minutes. If irritation persists, get medical attention. If in eyes: Flush with cold water for at least 15 minutes. Get medical attention. If swallowed: Feed bread soaked in milk, followed by olive oil or cooking oil. Call a physician immediately.

See Side Panel For Additional Precautionary Statements

Manufactured by



MIDLAND RESEARCH LABORATORIES, INC.

10850 Mid America Avenue
Lenexa, Kansas 66219

913-888-0560

A subsidiary of Associated Chemicals And Services, Inc.

E.P.A. Establishment No. 27581-KS-01

E.P.A. Registration No. 27581-25

Net Contents: Liquid

See Markings on Top of Drum for Net Weight

DIRECTIONS FOR USE

If it is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

READ THE PRECAUTIONARY STATEMENTS BEFORE USE. DIRECTIONS FOR CONTROLLING THE GROWTH OF BACTERIAL ORGANISMS IN WHITE WATER PAPER MILL SYSTEMS.

Add MIDLAND 670 to the machine chest, heater, blend chest, or any other convenient point in the wet end of the paper machine at the rate of 1 to 25 fl. ozs. (125-250 ppm sodium chlorite) per ton of paper. Repeat as often as necessary to maintain control.

DIRECTIONS FOR CONTROLLING THE GROWTH OF ALGAE IN RECIRCULATING COOLING WATER TOWERS.

1. Clean badly fouled systems before starting treatment.
2. When algae are visible, add an initial dosage of 0.67 lbs. MIDLAND 670 (20 ppm active) per 1,000 gallons of water in the system. Repeat if necessary until control is evident.
3. Where algae control is evident, use a subsequent dose of 0.33 lbs. of MIDLAND 670 (10 ppm active) per 1,000 gallons of water in the system twice a week or as needed to maintain control.
4. Add MIDLAND 670 directly to the cooling tower drip pan (cold water basin) near the inlet to the recirculating pump.

Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material, when such use and/or handling is contrary to label instructions.

