

US ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (TS-767) WASHINGTON, DC 20460 NOTICE OF PESTICIDE: ☐ REGISTRATION ☒ REREGISTRATION <i>(Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended)</i>	EPA REGISTRATION NO. 27581-20001	DATE OF ISSUANCE DEC 17 1993
	TERM OF ISSUANCE	
NAME OF PESTICIDE PRODUCT Midland 655		
NAME AND ADDRESS OF REGISTRANT (Include ZIP code) Midland Research Laboratories, Inc. 10850 Mid America Avenue Lenexa, KS 66219		
NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.		
On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act. A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.		
Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.		
Based on you response to the Reregistration Eligibility Document, EPA has reregistered the above named product subject to the comments recorded in the succeeding paragraph. This action is taken under the authority of section 4(g)(2)(C) of the Federal Insecticide, Fungicide, and Rodenticide Act, as amended. Reregistration under this section does not eliminate the need for continual reassessment of pesticides. EPA may require submission of data at any time to maintain the registration of your product.		
Make the following labeling changes before you release the product for shipment:		
1. Remove the sentence, "Rinse system with potable water prior to use" from the "Clean In Place" paragraph of the "Sanitization of Non-Porous Food Contact Surfaces" use directions on the product label. 2. Because you are repackaging a sodium hypochlorite source product, the label claim for your product has to be the same as your source product. Since your source products are 12.5% you must change the label claim for the active ingredient from 14.05% to 12.5%.		
☐ ATTACHMENT IS APPLICABLE		
SIGNATURE OF APPROVING OFFICIAL	DATE	

3. Note that one of your source products is not yet reregistered. A revision of the ingredient statement or sources of supply may be necessary when this source product is reregistered, if the active ingredient declarations on the product labels differ.

A stamped copy of the product label is enclosed for your records.

Submit one copy of the final printed label before releasing the product in channels of trade with the revised labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.



Ruth G. Douglas
Product Manager (32)
Antimicrobial Program Branch
Registration Division (7505C)

PRECAUTIONARY STATEMENTS

Hazards to Humans and Domestic Animals.

DANGER: Corrosive, may cause severe skin and eye irritation or chemical burns to broken skin. Causes eye damage. Wear safety glasses or goggles and rubber gloves when handling this product. Wash after handling. Avoid breathing vapors. Vacate poorly ventilated areas as soon as possible. Do not return until strong odors have dissipated.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL AND CHEMICAL HAZARDS.

STRONG OXIDIZING AGENT: Mix only with water according to label directions. Mixing this product with chemicals (e.g. ammonia, acids, detergents, etc.) or organic matter (eg. urine, feces, etc.) will release chlorine gas which is irritating to eyes, lungs and mucous membranes.

STORAGE AND DISPOSAL:

Store this product in a cool dry area, away from direct sunlight and heat to avoid deterioration. In case of spill, flood areas with large quantities of water. Product or residues that cannot be used should be diluted with water before disposal in a Sanitary sewer. Do not reuse container but place in trash collection. Do not contaminate food or feed by storage, disposal or cleaning of equipment.

MIDLAND 655

ACTIVE INGREDIENT:

SODIUM HYPOCHLORITE

INERT INGREDIENTS

12.50
14.05%
85.95%
87.50

KEEP OUT OF REACH OF CHILDREN DANGER

STATEMENT OF PRACTICAL TREATMENT (FIRST AID)

IF CONTACT WITH EYES OCCURS, flush with water for at least 15 minutes. Get prompt medical attention.

IF CONTACT WITH SKIN OCCURS, wash with plenty of soap and water.

IF SWALLOWED, drink large amounts of water. DO NOT induce vomiting. Call a physician or poison control center immediately.

See Side Panel For Additional Precautionary Statements
Manufactured for Associated Chemicals and Services, Inc.
EPA Reg. No. 27581-2000



DEC 17 1993

Under Fungicide, Disinfectant, and Antiseptic Act as registered for the pesticide registered under EPA Reg. No.

**MIDLAND
RESEARCH
LABORATORIES, INC.**

10850 Mid America Avenue
Lenexa, Kansas 66219
913-888-0560

A Subsidiary of:
Associated Chemicals And Services, Inc.

- ☐ E.P.A. Establishment No. 27581-KS-01
- ☐ E.P.A. Establishment No. 44323-CA-01
- ☐ E.P.A. Establishment No.
E.P.A. Registration No. 27581-2000

NET CONTENTS: _____ LBS.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

NOTE: This product degrades with age. Use a chlorine test kit and increase dosages, as necessary, to obtain the required level of available chlorine.

COOLING TOWER/EVAPORATIVE CONDENSER

SLUG FEED METHOD - Initial Dose: When system is noticeably fouled, apply 52 to 104 oz. of MIDLAND 655 per 10,000 gallons of water in the system to obtain from 5 to 10 ppm available chlorine. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 11 oz. of MIDLAND 655 per 10,000 gallons of water in the system daily, or as needed to maintain control and keep the chlorine residual at 1 ppm. Badly fouled systems must be cleaned before treatment is begun.

INTERMITTENT FEED METHOD - Initial Dose: When system is noticeably fouled, apply 52 to 104 oz. of MIDLAND 655 per 10,000 gallons of water in the system to obtain from 5 to 10 ppm available chlorine. Apply half (or $\frac{1}{3}$, $\frac{1}{4}$, or $\frac{1}{5}$) of this initial dose when half (or $\frac{1}{3}$, $\frac{1}{4}$, or $\frac{1}{5}$) of water in the system has been lost by blowdown.

Subsequent Dose: When microbial control is evident, add 11 oz. of MIDLAND 655 per 10,000 gallons of water in the system to obtain a 1 ppm residual. Apply half (or $\frac{1}{3}$, $\frac{1}{4}$, or $\frac{1}{5}$) of this initial dose when half (or $\frac{1}{3}$, $\frac{1}{4}$, or $\frac{1}{5}$) of water in the system has been lost by blowdown. Badly fouled systems must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD - Initial Dose: When system is noticeably fouled, apply 52 to 104 oz. of MIDLAND 655 per 10,000 gallons of water in the system to obtain from 5 to 10 ppm available chlorine.

Subsequent Dose: Maintain this treatment level by starting a continuous feed of 1 oz. of MIDLAND 655 per 1,000 gallons of water lost by blowdown to maintain a 1 ppm residual. Badly fouled systems must be cleaned before treatment is begun.

Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material, when such use and/or handling is contrary to label instructions.

SUPPLEMENTAL LABELING

MIDLAND 655

Active Ingredients:

Sodium Hypochlorite ¹²⁵⁰~~14.05%~~

Inert Ingredients ~~85.95%~~
^{87.50}

EPA Registration Number - 27581-20001

ACCEPTED
with COMMENTS
in EPA Labeling
DEC 17 1993
Under the
Fungicide, Insecticide,
and Plant Growth Regulator
Registration Act

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

SPAS, HOT-TUBS, IMMERSION TANKS, ETC.

SPAS/HOT-TUBS -- Apply 5 oz. of MIDLAND 655 per 1000 gallons of water to obtain a free available chlorine concentration of 5 ppm, as determined by a suitable chlorine test kit. Adjust and maintain pool water pH to between 7.2 and 7.8. Some oils, lotions, fragrances, cleaners, etc. may cause foaming or cloudy water as well as reduce the efficiency of the MIDLAND 655.

To maintain the water, apply 5 oz. of MIDLAND 655 per 1000 gallons of water over the surface to maintain a chlorine concentration of 5 ppm.

After each use, shock treat with 8 oz. of MIDLAND 655 per 500 gallons of water to control odor and algae.

During extended periods of disuse, add 3 oz. of MIDLAND 655 daily per 1000 gallons of water to maintain a 3 ppm chlorine concentration.

HUBBARD AND IMMERSION TANKS -- Add 5 oz. of MIDLAND 655 per 200 gallons of water before patient use to obtain a chlorine residual of 25 ppm, as determined by a suitable test kit. Adjust and maintain the water pH to between 7.2 and 7.6. After each use drain the tank. Add 5 oz. to a bucket of water and circulate this solution through the agitator of the tank for 15 minutes and then rinse out the solution. Clean tank thoroughly and dry with clean cloths.

HYDROTHERAPY TANKS -- Add 1 oz. of MIDLAND 655 per 1000 gallons of water to obtain a chlorine residual of 1 ppm, as determined by a suitable chlorine test kit. Pool should not be entered until the chlorine residual is below 3 ppm. Adjust and maintain the water pH to between 7.2 and 7.6. Operate pool filter continuously. Drain pool weekly, and clean before refilling.

KEEP OUT OF REACH OF CHILDREN
DANGER

See Principal Label for Complete Precautionary Information and Storage and Handling Instructions

Midland Research Laboratories
10850 Mid America Avenue
Lenexa, KS 66219

SUPPLEMENTAL LABELING

MIDLAND 655

Active Ingredients: 12.50
 Sodium Hypochlorite ~~14.05%~~
 Inert Ingredients ~~85.95%~~
87.50

EPA Registration Number - 27581-20001

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

SWIMMING POOL WATER DISINFECTION

For a new pool or spring start-up, superchlorinate with 52 to 104 oz. of MIDLAND 655 for each 10,000 gallons of water to yield 5 to 10 ppm available chlorine by weight. Check the level of available chlorine with a test kit. Adjust and maintain pool to water pH to between 7.2 to 7.6. Adjust and maintain the alkalinity of the pool to between 50 to 100 ppm.

To maintain the pool, add manually or by a feeder device 11 oz. of MIDLAND 655 for each 10,000 gallons of water to yield an available chlorine residual between 0.6 to 1.0 ppm by weight. Stabilized pools should maintain a residual of 1.0 to 1.5 ppm available chlorine. Test the pH, available chlorine residual and alkalinity of the water frequently with appropriate test kits. Frequency of water treatment will depend upon temperature and number of swimmers.

Every 7 days, or as necessary, superchlorinate the pool with 52 to 104 oz. of MIDLAND 655 for each 10,000 gallons of water to yield 5 to 10 ppm available chlorine by weight. Check the level of available chlorine with a test kit. Do not reenter pool until the chlorine residual is between 1.0 to 3.0 ppm.

At the end of the swimming pool season or when water is to be drained from the pool, chlorine must be allowed to dissipate from treated pool water before discharge. Do not chlorinate the pool within 24 hours prior to discharge.

WINTERIZING POOLS -- While water is still clear and clean, apply 3 oz. of MIDLAND 655 per 1,000 gallons, while filter is running, to obtain a 3 ppm available chlorine residual, as determined by a suitable test kit. Cover pool, prepare heater, filter and heater components for winter by following manufacturers' instructions.

KEEP OUT OF REACH OF CHILDREN
DANGER

See Principal Label For Complete Precautionary Information and Storage and Handling Instructions

Midland Research Laboratories
 10850 Mid America Avenue
 Lenexa, KS 66219
 (913) 888-0560

SUPPLEMENTAL LABELING

MIDLAND 655

6/22

Active Ingredients: ^{12.00}
 Sodium Hypochlorite ~~14.05%~~
 Inert Ingredients ~~85.35%~~
^{87.35%}

EPA Registration Number - 27581-20001

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

SANITIZATION OF NONPOROUS FOOD CONTACT SURFACES

RINSE METHOD -- A solution of 100 ppm available chlorine may be used in the sanitizing solution if a chlorine test kit is available. Solutions containing an initial concentration of 100 ppm available chlorine must be tested and adjusted periodically to insure that the available chlorine does not drop below 50 ppm. Prepare a 100 ppm sanitizing solution by thoroughly mixing 1 oz. of MIDLAND 655 with 10 gallons of water. If no test kit is available, prepare a sanitizing solution by thoroughly mixing 2 oz. of MIDLAND 655 with 10 gallons of water to provide approximately 200 ppm available chlorine by weight.

Clean equipment surfaces in the normal manner. Prior to use, rinse all surfaces thoroughly with the sanitizing solution, maintaining contact with the sanitizer for at least 2 minutes. If solution contains less than 50 ppm available chlorine, as determined by a suitable test kit, either discard the solution or add sufficient MIDLAND 655 to reestablish a 200 ppm residual. Do not rinse equipment with water after treatment and do not soak equipment overnight.

Sanitizers used in automated systems may be used for general cleaning but may not be reused for sanitizing purposes.

IMMERSION METHOD -- A solution of 100 ppm available chlorine may be used in the sanitizing solution if a chlorine test kit is available. Solutions containing an initial concentration of 100 ppm available chlorine must be tested and adjusted periodically to insure that the available chlorine does not drop below 50 ppm. Prepare a 100 ppm sanitizing solution by thoroughly mixing 1 oz. of MIDLAND 655 with 10 gallons of water. If no test kit is available, prepare a sanitizing solution by thoroughly mixing 2 oz. of MIDLAND 655 with 10 gallons of water to provide approximately 200 ppm available chlorine by weight.

Clean equipment in the normal manner. Prior to use, immerse equipment in the sanitizing solution for at least 2 minutes and allow the sanitizer to drain. If solution contains less than 50 ppm available chlorine, as determined by a suitable test kit, either discard the solution or add sufficient MIDLAND 655 to reestablish a 200 ppm residual. Do not rinse equipment with water after treatment.

Sanitizers used in automated systems may be used for general cleaning but may not be reused for sanitizing purposes.

FLOW/PRESSURE METHOD -- Disassemble equipment and thoroughly clean after use. Assemble equipment in operating position prior to use. Prepare a volume of a

SUPPLEMENTAL LABELING

MIDLAND 655

Active Ingredients: *12.50*
 Sodium Hypochlorite ~~14.05%~~
 Inert Ingredients ~~85.95%~~
87.50

EPA Registration Number: 27581-20001

DIRECTIONS OF USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

SANITIZATION OF POROUS FOOD CONTACT SURFACES

RINSE METHOD - Prepare a sanitizing solution by thoroughly mixing 6 oz. of MIDLAND 655 with 10 gallons of water to provide approximately 600 ppm available chlorine by weight. Clean surfaces in the normal manner. Prior to use, rinse all surfaces thoroughly with the sanitizing solution, maintaining contact with the sanitizer for at least 2 minutes. Rinse all surfaces with a 200 ppm available chlorine solution, prepared by thoroughly mixing 2 oz. of MIDLAND 655 with 10 gallons of water, and let the equipment drain.

IMMERSION METHOD - Prepare a sanitizing solution by thoroughly mixing, in an immersion tank, 6 oz. of MIDLAND 655 with 10 gallons of water to provide approximately 600 ppm available chlorine by weight. Clean equipment in the normal manner. Prior to use, immerse all surfaces in a 200 ppm available chlorine solution, prepared by thoroughly mixing 2 oz. of MIDLAND 655 with 10 gallons of water, and let the equipment drain.

SPRAY/FOG METHOD - Preclean all surfaces after use. Prepare a 600 ppm available chlorine sanitizing solution of sufficient size by thoroughly mixing MIDLAND 655 in a ration of 6 oz. product with 10 gallons of water. Use spray and rinse spray/fog equipment with potable water after use. Thoroughly spray area for at least 2 hours. Prior to using equipment, rinse all surfaces with a 200 ppm sanitizing solution. Prepare a 200 ppm sanitizing solution by thoroughly mixing 2 oz. of MIDLAND 655 with 10 gallons of water.

KEEP OUT OF REACH OF CHILDREN - DANGER

See Principal Label For Complete Precautionary Information and Storage and Handling Instruction.

MIDLAND RESEARCH LABORATORIES, INC.
 10850 Mid America Avenue
 Lenexa, KS 66219
 (913) 888-0560

SUPPLEMENTAL LABELING

MIDLAND 655

Active Ingredients:	12.50
Sodium Hypochlorite	14.05%
Inert Ingredients	85.95%
	87.50

EPA Registration Number - 27581-20001

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

SANITIZATION OF NONPOROUS NON-FOOD CONTACT SURFACES

RINSE METHOD -- Prepare a sanitizing solution by thoroughly mixing 2 oz. of MIDLAND 655 with 10 gallons of water to provide approximately 200 ppm available chlorine by weight. Clean equipment surfaces in the normal manner. Prior to use, rinse all surfaces thoroughly with the sanitizing solution, maintaining contact with the sanitizer for at least 2 minutes. Do not rinse equipment with water after treatment and do not soak equipment overnight.

IMMERSION METHOD -- Prepare a sanitizing solution by thoroughly mixing, in an immersion tank, 2 oz. of MIDLAND 655 with 10 gallons of water to provide approximately 200 ppm available chlorine by weight. Clean equipment in the normal manner. Prior to use, immerse equipment in the sanitizing solution for at least 2 minutes and allow the sanitizer to drain. Do not rinse equipment with water after treatment.

SPRAY/FOG METHOD -- Preclean all surfaces after use. Prepare a 200 ppm available chlorine sanitizing solution of sufficient size by thoroughly mixing MIDLAND 655 in a ratio of 2 oz. product with 10 gallons of water. Use spray or fogging equipment which can resist hypochlorite solutions. Prior to using equipment, thoroughly spray or fog all surfaces until wet, allowing excess sanitizer to drain. Vacate area for at least 2 hours.

KEEP OUT OF REACH OF CHILDREN
DANGER

See Principal Label For Complete Precautionary Information and Storage and Handling Instructions

Midland Research Laboratories, Inc.
10850 Mid America Avenue :
Lenexa, KS 66219 :
(913) 888-0560 :

SUPPLEMENTAL LABELING

MIDLAND 655

Active Ingredients: 12.50
 Sodium Hypochlorite ~~14.05%~~
 Inert Ingredients ~~85.95%~~
87.50

EPA Registration Number - 27581-20001

DIRECTIONS FOR USE.

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

DISINFECTION OF NONPOROUS NON-FOOD CONTACT SURFACES

RINSE METHOD -- Prepare a disinfecting solution by thoroughly mixing 6 oz. of MIDLAND 655 with 10 gallons of water to provide approximately 600 ppm available chlorine by weight. Clean equipment surfaces in the normal manner. Prior to use, rinse all surfaces thoroughly with the disinfecting solution, maintaining contact with the solution for at least 10 minutes. Do not rinse equipment with water after treatment and do not soak equipment overnight.

IMMERSION METHOD -- Prepare a disinfecting solution by thoroughly mixing, in an immersion tank, 6 oz. of MIDLAND 655 with 10 gallons of water to provide approximately 600 ppm available chlorine by weight. Clean equipment in the normal manner. Prior to use, immerse equipment in the disinfecting solution for at least 10 minutes and allow the sanitizer to drain. Do not rinse equipment with water after treatment.

KEEP OUT OF REACH OF CHILDREN
 DANGER

See Principal Label For Complete Precautionary Information and Storage and Handling Instructions

Midland Research Laboratories, Inc.
 10850 Mid America Avenue
 Lenexa, KS 66219
 (913) 888-0560

SUPPLEMENTAL LABELING

MIDLAND 655

Active Ingredients: 12.60
Sodium Hypochlorite ~~14.05%~~
Inert Ingredients ~~85.95%~~
87.60

EPA Registration Number - 27581-20001

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

SANITIZATION OF POROUS NON-FOOD CONTACT SURFACES

RINSE METHOD -- Prepare a sanitizing solution by thoroughly mixing 6 oz. of MIDLAND 655 with 10 gallons of water to provide approximately 600 ppm available chlorine by weight. Clean surfaces in the normal manner. Prior to use, rinse all surfaces thoroughly with the sanitizing solution, maintaining contact with the sanitizer for at least 2 minutes. Do not rinse equipment with water after treatment and do not soak equipment overnight.

IMMERSION METHOD -- Prepare a sanitizing solution by thoroughly mixing, in an immersion tank, 6 oz. of MIDLAND 655 with 10 gallons of water to provide approximately 600 ppm available chlorine by weight. Clean equipment in the normal manner. Prior to use, immerse equipment in the sanitizing solution for at least 2 minutes and allow the sanitizer to drain. Do not rinse equipment with water after treatment.

SPRAY/FOG METHOD -- After cleaning, sanitize non-food contact surfaces with 600 ppm available chlorine by thoroughly mixing MIDLAND 655 in a ratio of 6 oz. of MIDLAND 655 with 10 gallons of water. Use spray or fogging equipment which can resist hypochlorite solutions. Always empty and rinse spray/fog equipment with potable water after use. Prior to using equipment, thoroughly spray or fog all surfaces until wet, allowing excess sanitizer to drain. Vacate area for at least 2 hours.

KEEP OUT OF REACH OF CHILDREN
DANGER

See Principal Label For Complete Precautionary Information and Storage and Handling Instructions

Midland Research Laboratories, Inc.
10850 Mid America Avenue
Lenexa, KS 66219
(913) 888-0560

•••
••••
•
••••
••••
•••

SUPPLEMENTAL LABELING

MIDLAND 655

11/22

Active Ingredients: 12.50
 Sodium Hypochlorite ~~14.05%~~
 Inert Ingredients ~~85.95%~~
87.50

EPA Registration Number - 27581-20001

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

SEWAGE AND WASTEWATER EFFLUENT TREATMENT

The disinfection of sewage effluent must be evaluated by determining the total number of coliform bacteria and/or fecal coliform bacteria, as determined by the Most Probable Number (MPN) procedure, of the chlorinated effluent has been reduced to or below the maximum permitted by the controlling regulatory jurisdiction.

On the average, satisfactory disinfection of secondary wastewater effluent can be obtained when the chlorine residual is 0.5 ppm after 15 minutes contact. Although the chlorine residual is the critical factor in disinfection, the importance of correlating chlorine residual with bacterial kill must be emphasized. The MPN of the effluent, which is directly related to the water quality standards requirements, should be the final and primary standard and the chlorine residual should be considered an operating standard valid only to the extent verified by the coliform quality of the effluent.

The following are critical factors affecting wastewater disinfection.

1. Mixing: It is imperative that MIDLAND 655 and the wastewater be instantaneously and completely flash mixed to assure reaction with every chemically active soluble and particulate component of the wastewater.
2. Contacting: Upon flash mixing, the flow through the system must be maintained.
3. Dosage/Residual Control: Successful disinfection is extremely dependent on response to fluctuating chlorine demand to maintain a predetermined, desirable chlorine level. Secondary, effluent should contain 0.2 to 1.0 ppm chlorine residual after a 15 to 30 minute contact time. A reasonable average of residual chlorine is 0.5 ppm after 15 minutes contact time.

SEWAGE AND WASTEWATER TREATMENT

EFFLUENT SLIME CONTROL -- Apply a 100 to 1000 ppm available chlorine solution at a location which will allow complete mixing. Prepare this solution by mixing 10 to 100 oz. of MIDLAND 655 with 100 gallons of water. Once control is evident, apply a 15 ppm available chlorine solution. Prepare this solution by mixing 3 oz. of MIDLAND 655 with 100 gallons of water.

 FILTER BEDS: SLIME CONTROL -- Remove filter from service, drain to a depth of 1 ft. above filter sand, and add 80 oz. of MIDLAND 655 per 20 sq. ft. evenly over the surface. Wait 30 minutes before draining water to a level that is even with the top of the filter. Wait for 4 to 6 hours before completely draining and backwashing filter.

KEEP OUT OF REACH OF CHILDREN
 DANGER

See Principal Label For Complete Precautionary Information and Storage and Handling Instructions

Midland Research Laboratories, Inc.
 10850 Mid America Avenue
 Lenexa, KS 66219
 (913) 888-0560

MIDLAND 655

12/22

Active Ingredients: ^{12.56}
 Sodium Hypochlorite ~~14.05%~~
 Inert Ingredients ~~85.95%~~
^{87.56}

EPA Registration Number - 27581-20001

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

PUBLIC WATER SYSTEMS

RESERVOIRS - ALGAE CONTROL: Hypochlorinate streams feeding the reservoir. Suitable feeding points should be selected on each stream at least 50 yards upstream from the points of entry into the reservoir.

MAINS -- Thoroughly flush section to be sanitized by discharging from hydrants. Permit a water flow of at least 2.5 feet per minute to continue under pressure while injecting MIDLAND 655 by means of hypochlorinator. Stop water flow when a chlorine residual test of 50 ppm is obtained at the low pressure end of the new main section after a 24 hour retention time. When chlorination is completed, the system must be flushed free of all heavily chlorinated water.

NEW TANKS, BASINS, ETC. -- Remove all physical soil from surfaces. Place 20 oz. of MIDLAND 655 for each 5 cubic feet of working capacity (500 ppm available chlorine). Fill to working capacity and allow to stand for at least 4 hours. Drain and flush with potable water and return to surface.

NEW FILTER SAND -- Apply 80 oz. of MIDLAND 655 for each 150 to 200 cubic feet of sand. The action of MIDLAND 655 dissolving as the water passes through the bed will aid in sanitizing the new sand.

NEW WELLS -- Flush the casing with a 50 ppm available chlorine solution of water containing 5 oz. of MIDLAND 655 for each 100 gallons of water. The solution should be pumped or fed by gravity into the well after thorough mixing with agitation. The well should stand for several hours or overnight under chlorination. It may then be pumped until a representative raw water sample is obtained. Bacterial examination of the water will indicate whether further treatment is necessary.

EXISTING EQUIPMENT -- Remove equipment from service, thoroughly clean surfaces of all physical soil. Sanitize by placing 21 oz. of MIDLAND 655 for each 5 cubic feet capacity (approximately 500 ppm available chlorine). Fill to working capacity and let stand at least 4 hours. Drain and place in service. If the previous treatment is not practical, surfaces may be sprayed with a solution containing 5 oz. of MIDLAND 655 for each 5 gallons of water (approximately 1,000 pm available chlorine). After drying, flush with water and return to service.

KEEP OUT OF REACH OF CHILDREN
 DANGER

See Principal Label For Complete Precautionary Information and Storage and Handling Instructions

Midland Research Laboratories
 10850 Mid America Avenue
 Lenexa, KS 66219
 (913) 888-0560

SUPPLEMENTAL LABELING

MIDLAND 655

Active Ingredients:

Sodium Hypochlorite 12.50% ^{12.50}

Inert Ingredients 85.95% ^{85.95}

EPA Registration Number - 27581-20001 ^{87.50}

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

DISINFECTION OF DRINKING WATER (EMERGENCY/PUBLIC/INDIVIDUAL SYSTEMS)

PUBLIC SYSTEMS: Mix a ratio of 1 oz. of MIDLAND 655 to 100 gallons of water. Begin feeding this solution with a hypochlorinator until a free available chlorine residual of at least 0.2 ppm and no more than 0.6 ppm is attained throughout the distribution system. Check water frequently with a chlorine test kit. Bacteriological sampling must be conducted at a frequency no less than that prescribed by the National Interim Primary Drinking Water Regulations. Contact your local Health Department for further details.

INDIVIDUAL SYSTEMS: DUG WELLS -- Upon completion of the casing (lining) wash the interior of the casing (lining) with a 100 ppm available chlorine solution using a stiff brush. This solution can be made by thoroughly mixing 1 oz. of MIDLAND 655 into 10 gallons of water. After covering the well, pour the sanitizing solution into the well through both the pipesleeve opening and the pipeline. Wash the exterior of the pump cylinder also with the sanitizing solution. Start pump and pump water until strong odor of chlorine in water is noted. Stop pump and wait at least 24 hours. After 24 hours flush well until all traces of chlorine have been removed from the water. Consult your local Health Department for further details.

INDIVIDUAL WATER SYSTEMS: DRILLED, DRIVEN AND BORED WELLS -- Run pump until water is as free from turbidity as possible. Pour a 100 ppm available chlorine sanitizing solution into the well. This solution can be made by thoroughly mixing 1 oz. of MIDLAND 655 into 10 gallons of water. Add 5 to 10 gallons of clean, chlorinated water to the well in order to force the sanitizer into the rock formation. Wash the exterior of pump cylinder with the sanitizer. Drop pipeline into well, start pump and pump water until strong odor of chlorine in water is noted. Stop pump and wait at least 24 hours. After 24 hours, flush well until all traces of chlorine have been removed from the water. Deep wells with high water levels may necessitate the use of special methods for introduction of the sanitizer into the well. Consult your local Health Department for further details.

INDIVIDUAL WATER SYSTEMS: FLOWING ARTESIAN WELLS -- Artesian wells generally do not require disinfection. If analyses indicate persistent contamination, the well should be disinfected. Consult your local Health Department for further details.

EMERGENCY DISINFECTION -- When boiling of water for 1 minute is not practical, water can be made potable by using MIDLAND 655. Prior to addition of the sanitizer, remove all suspended material by filtration or by allowing it to settle to the bottom. Decant the clarified, contaminated water to a clean container and add 1 drop of MIDLAND 655 to 20 gallons of water. Allow the treated water to stand for 30 minutes. Properly treated water should have a slight chlorine odor; if not, repeat dosage and allow the water to stand an additional 15 minutes. The treated water can then be made palatable by pouring it between clean containers for several times.

KEEP OUT OF REACH OF CHILDREN
DANGER

See Principal Label For Complete Precautionary Information and Storage and Handling Instructions

Midland Research Laboratories, Inc.
10850 Mid America Avenue
Lenexa, KS 66219
(913) 888-0560

Active Ingredients: ^{12.60}
Sodium Hypochlorite ~~14.05%~~
Inert Ingredients ~~85.95%~~
^{87.50}

14122

EPA Registration Number - 27581- 20001

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

EMERGENCY DISINFECTION AFTER FLOODS

WELLS — Thoroughly flush contaminated casing with a 500 ppm available chlorine solution. Prepare this solution by mixing 5 oz. of MIDLAND 655 with 10 gallons of water. Backwash the well to increase yield and reduce turbidity, adding sufficient chlorinating solution to the backwash to produce a 10 ppm available chlorine residual, as determined by a chlorine test kit. After the turbidity has been reduced and the casing has been treated, add sufficient chlorinating solution to produce a 50 ppm available chlorine residual. Agitate the well water for several hours and take a representative water sample. Retreat well if water samples are biologically unacceptable.

RESERVOIRS — In case of contamination by overflowing streams, establish hypochlorinating stations upstream of the reservoir. Chlorinate the inlet water until the entire reservoir obtains a 0.2 ppm available chlorine residual, as determined by a suitable chlorine test kit. In case of contamination from surface drainage, apply sufficient MIDLAND 655 directly to the reservoir to obtain a 0.2 ppm available chlorine residual in all parts of the reservoir.

BASINS, TANKS, FLUMES, ETC. — Thoroughly clean all equipment, then apply 20 oz. of MIDLAND 655 per 5 cubic feet of water to obtain 500 ppm available chlorine, as determined by a suitable test kit. After 24 hours, drain, flush, and return to service. If the previous method is not suitable, spray or flush the equipment with a solution containing 5 oz. of MIDLAND 655 for each 5 gallons of water (1,000 ppm available chlorine). Allow to stand for 2 to 4 hours, flush and return to service.

FILTERS — When the sand filter needs replacement, apply 80 oz. of MIDLAND 655 for each 150 to 200 cubic feet of sand. When the filter is severely contaminated, additional MIDLAND 655 should be distributed over the surface at the rate of 80 oz. per 20 sq. ft. Water should stand at a depth of one foot above the surface of the filter bed for 4 to 24 hours. When filter beds can be backwashed of mud and silt, apply 80 oz. of MIDLAND 655 per each 50 sq. ft., allowing the water to stand at a depth of one foot above the filter sand. After 30 minutes, drain water to the level of the filter. After 4 to 6 hours drain and proceed with normal backwashing.

DISTRIBUTION SYSTEM — Flush repaired or replaced section with water. Establish a hypochlorinating station and apply sufficient MIDLAND 655 until a consistent available chlorine residual of at least 10 ppm remains after a 24 hour retention time. Use a chlorine test kit.

KEEP OUT OF REACH OF CHILDREN
DANGER

See Principal Label For Complete Precautionary Information and Storage and Handling Instructions

Midland Research Laboratories, Inc.
10850 Mid America Avenue
Lenexa, KS 66219

15/22

SUPPLEMENTAL LABELING

MIDLAND 655

Active Ingredients: *12.50*
 Sodium Hypochlorite ~~14.05%~~
 Inert Ingredients ~~85.95%~~ *87.50*

EPA Registration Number - 27581-20001

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

EMERGENCY DISINFECTION AFTER FIRES

CROSS CONNECTIONS OR EMERGENCY CONNECTIONS -- Hypochlorination or gravity feed equipment should be set up near the intake of the untreated water supply. Apply sufficient MIDLAND 655 to give a chlorine residual of at least 0.1 to 0.2 ppm at the point where the untreated supply enters the regular distribution system. Use a chlorine test kit.

EMERGENCY DISINFECTION AFTER DROUGHTS

SUPPLEMENTARY WATER SUPPLIES -- Gravity or mechanical hypochlorite feeders should be set up on a supplementary line to dose the water to a minimum chlorine residual of 0.2 ppm after a 20-minute contact time. Use a chlorine test kit.

 WATER SHIPPED IN BY TANK, TANK CARS, TRUCKS, ETC. -- Thoroughly clean all containers and equipment. Spray a 500 ppm available chlorine solution and rinse with potable water after 5 minutes. This solution is made by mixing 5 oz. of MIDLAND 655 for each 10 gallons of water. During the filling of the containers, dose with sufficient amounts of MIDLAND 655 to provide at least a 0.2 ppm chlorine residual. Use a chlorine test kit.

EMERGENCY DISINFECTION AFTER MAIN BREAKS

MAINS -- Before assembly of the repaired section, flush out mud and soil. Permit a water flow of at least 2.5 feet per minute to continue under pressure while injecting MIDLAND 655 by means of hypochlorinator. Stop water flow when a chlorine residual test of 50 ppm is obtained at the low pressure end of the new main section after a 24-hour retention of time. When chlorination is completed, the system must be flushed free of all heavily chlorinated water.

KEEP OUT OF REACH OF CHILDREN
 DANGER

Midland Research Laboratories, Inc.
 10850 Mid America Avenue
 Lenexa, KS 66219
 (913) 888-0560

SUPPLEMENTAL LABELING

MIDLAND 655

Active Ingredients: 12.50
 Sodium Hypochlorite ~~14.05%~~
 Inert Ingredients ~~85.95%~~
87.50
 EPA Registration Number - 27581-20001

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

HOUSEHOLD LAUNDRY SANITIZERS

IN SOAKING SUDS -- Thoroughly mix 2 oz. of MIDLAND 655 to 10 gallons of wash water to provide 200 ppm available chlorine. Wait 5 minutes, then add soap or detergent. Immerse laundry for at least 11 minutes prior starting the wash/rinse cycle.

IN WASHING SUDS -- Thoroughly mix 2 oz. of MIDLAND 655 to 10 gallons of wash water containing clothes to provide 200 ppm available chlorine. Wait 5 minutes, then add soap or detergent and start the wash/rinse cycle.

COMMERCIAL LAUNDRY SANITIZERS

Wet fabrics or clothes should be spun dry prior to sanitization. Thoroughly mix 2 oz. of MIDLAND 655 with 10 gallons of water to yield 200 ppm available chlorine. Promptly after mixing the sanitizer, add the solution into the prewash prior to washing fabrics/clothes in the regular wash cycle with a good detergent. Test the level of available chlorine, if solution has been allowed to stand. Add more of MIDLAND 655 if the available chlorine level has dropped below 200 ppm.

KEEP OUT OF REACH OF CHILDREN
 DANGER

See Principal Label For Complete Precautionary Information and Storage and Handling Instructions

Midland Research Laboratories, Inc.
 10850 Mid America Avenue
 Lenexa, KS 66219
 (913) 888-0560

1712a

SUPPLEMENTAL LABELING

MIDLAND 655

Active Ingredients: 12.50
Sodium Hypochlorite ~~14.05%~~
Inert Ingredients 85.95%
87.50

EPA Registration Number - 27581-20001

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

FARM PREMISES

Remove all animals, poultry, and feed from premises, vehicles, and enclosures. Remove all litter and manure from floors, walls and surfaces of barns, pens, stalls, chutes and other facilities occupied or transverse by animals or poultry. Empty all troughs, racks and other feeding and watering appliances. Thoroughly clean all surfaces with soap or detergent and rinse with water. To disinfect, saturate all surfaces with a solution of at least 1000 ppm available chlorine for a period of 10 minutes. A 1000 ppm solution can be made by thoroughly mixing 11 oz. of MIDLAND 655 with 10 gallons of water. Immerse all halters, ropes and other types of equipment used in handling and restraining animals or poultry, as well as the cleaned forks, shovels and scrapers used for removing litter and manure. Ventilate buildings, cars, boats and other closed spaces. Do not house livestock or poultry or employ equipment until chlorine has been dissipated. All treated feed racks, mangers, troughs, automatic feeders, fountains and waterers must be rinsed with potable water before reuse.

KEEP OUT OF REACH OF CHILDREN
DANGER

See Principal Label For Complete Precautionary Information and Storage and Handling Instructions

Midland Research Laboratories, Inc.
10850 Mid America Avenue
Lenexa, KS 66219
(913) 888-0560

.....
.....
.....
.....
.....
.....

18/22

SUPPLEMENTAL LABELING

MIDLAND 655

Active Ingredients: 12.50
Sodium Hypochlorite ~~14.05%~~
Inert Ingredients ~~85.55%~~
87.50

EPA Registration Number - 27581-20001

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

PULP AND PAPER MILL PROCESS WATER SYSTEMS

SLUG FEED METHOD -- Initial Dose: When system is noticeably fouled, apply 52 to 104 oz. of MIDLAND 655 per 10,000 gallons of water in the system to obtain from 5 to 10 ppm available chlorine. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 11 oz. of MIDLAND 655 per 10,000 gallons of water in the system daily, or as needed to maintain control and keep the chlorine residual at 1 ppm. Badly fouled systems must be cleaned before treatment is begun.

INTERMITTENT FEED METHOD -- Initial Dose: When system is noticeably fouled, apply 52 to 104 oz. of MIDLAND 655 per 10,000 gallons of water in the system to obtain 5 to 10 ppm available chlorine. Apply half (or 1/3, 1/4, or 1/5) of this initial dose when half (or 1/3, 1/4, or 1/5) of the water in the system has been lost by blowdown.

Subsequent Dose: When microbial control is evident, add 11 oz. of MIDLAND 655 per 10,000 gallons of water in the system to obtain a 1 ppm residual. Apply half (or 1/3, 1/4, or 1/5) of this initial dose when half (or 1/3, 1/4, or 1/5) of the water in the system has been lost by blowdown. Badly fouled systems must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD -- Initial Dose: When system is noticeably fouled, apply 52 to 104 oz. of MIDLAND 655 per 10,000 gallons of water in the system to obtain 5 to 10 ppm available chlorine.

Subsequent Dose: Maintain this treatment level by starting a continuous feed of 1 oz. of MIDLAND 655 per 1,000 gallons of water lost by blowdown to maintain a 1 ppm residual. Badly fouled systems must be cleaned before treatment is begun.

BRIQUETTES OR TABLETS -- Initially slug dose the system with 52 oz. of MIDLAND 655 per 10,000 gallons of water in the system. Badly fouled systems must be cleaned before treatment is begun.

Subsequent Dose: When microbial control is evident, add 11 oz. of MIDLAND 655 per 10,000 gallons of water in the system daily, or as needed to maintain control and keep the chlorine residual at 1 ppm. Badly fouled systems must be cleaned before treatment is begun.

KEEP OUT OF REACH OF CHILDREN
DANGER

See Principal Label For Complete Precautionary Information and Storage and Handling Instructions

Midland Research Laboratories, Inc.
10850 Mid America Avenue
Lenexa, KS 66219
(913) 888-0560

19/22

SUPPLEMENTAL LABELING

MIDLAND 655

Active Ingredients: 12.60
Sodium Hypochlorite 14.05%
Inert Ingredients 85.35%
87.60

EPA Registration Number - 27581-20001

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

AGRICULTURAL USES

POST-HARVEST PROTECTION -- Potatoes can be sanitized after cleaning and prior to storage by spraying with a sanitizing solution at a level of 1 gallon of sanitizing solution per tons of potatoes. Thoroughly mix 1 oz. of MIDLAND 655 to 2 gallons of water to obtain 500 ppm available chlorine.

Disinfect leafcutting bee cells and bee boards by immersion in a solution containing 1 ppm available chlorine for 3 minutes. Allow cells to drain for 2 minutes and dry for 4 to 5 hours or until no chlorine odor can be detected. This solution is made by thoroughly mixing 1 tsp. of MIDLAND 655 to 100 gallons of water. The bee domicile is disinfected by spraying with 0.1 ppm solution until all surfaces are thoroughly wet. Allow the domicile to dry until all chlorine odor has dissipated.

FOOD EGG SANITIZATION -- Thoroughly clean all eggs. Thoroughly mix 2 oz. of MIDLAND 655 with 10 gallons of warm water to produce 200 ppm available chlorine solution. The sanitizer temperature should not exceed 130 F. Spray the warm sanitizer so that the eggs are thoroughly wetted. Allow the eggs to thoroughly dry before casing or breaking. Do not apply a potable water rinse. The solution should not be reused to sanitize eggs.

FRUIT AND VEGETABLE WASHING -- Thoroughly clean all fruits and vegetables in a wash tank. Thoroughly mix 5 oz. of MIDLAND 655 in 200 gallons of water to make a sanitizing solution of 25 ppm available chlorine. After draining the tank, submerge fruit or vegetables for 2 minutes in second wash tank containing the recirculating sanitizing solution. Spray rinse vegetables with the sanitizing solution prior to packaging. Rinse fruit with potable water only prior to packaging.

KEEP OUT OF REACH OF CHILDREN
DANGER

See Principal Label For Complete Precautionary Information and Storage and Handling Instructions

Midland Research Laboratories, Inc.
10850 Mid America Avenue
Lenexa, KS 66219
(913) 888-0560

SUPPLEMENTAL LABELING

MIDLAND 655

Active Ingredients:

Sodium Hypochlorite ~~14.05%~~ ^{12.50}Inert Ingredients ~~85.95%~~ ^{87.50}

EPA Registration Number - 27581- 20001

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

AQUACULTURAL USES

FISH PONDS -- Remove fish from ponds prior to treatment. Thoroughly mix 103 oz. of MIDLAND 655 to 10,000 gallons of water to obtain 10 ppm available chlorine. Add more product to the water if the available chlorine level is below 1 ppm after 5 minutes. Return fish to pond after the available chlorine level reaches zero.

FISH POND EQUIPMENT -- Thoroughly clean all equipment prior to treatment. Thoroughly mix 2 oz. of MIDLAND 655 to 10 gallons of water to obtain 200 ppm available chlorine. Porous equipment should soak for one hour.

MAINE LOBSTER PONDS -- Remove lobsters, seaweed, etc. from ponds prior to treatment. Drain the pond. Thoroughly mix 6,200 oz. of MIDLAND 655 to 10,000 gallons of water to obtain at least 600 ppm available chlorine. Apply so that all barrows, gates, rock and dam are treated with MIDLAND 655. Permit high tide to fill the pond and then close gates. Allow water to stand for 2 to 3 days until the available chlorine level reaches zero. Open gates and allow 2 tidal cycles to flush the pond before returning lobsters to pond.

CONDITIONING LIVE OYSTERS -- Thoroughly mix 5 oz. of MIDLAND 655 to 10,000 gallons of water at 50° to 70° F to obtain 0.5 ppm available chlorine. Expose oysters to this solution for at least 15 minutes, monitoring the available chlorine level so that it does not fall below 0.05 ppm. Repeat entire process if the available chlorine level drops below 0.05 ppm or the temperature falls below 50° F.

CONTROL OF SCAVENGERS IN FISH HATCHERY PONDS -- Prepare a solution containing 200 ppm of available chlorine by mixing 2 oz. of MIDLAND 655 with 10 gallons of water. Pour into drained pond potholes. Repeat if necessary. Do not put desirable fish back into refilled ponds until chlorine residual has dropped to 0 ppm, as determined by a test kit.

KEEP OUT OF REACH OF CHILDREN
DANGER

See Principal Label For Complete Precautionary Information and Storage, and
Handling Instructions

Midland Research Laboratories, Inc.
10850 Mid America Avenue
Lenexa, KS 66219
(913) 888-0560

21/22

SUPPLEMENTAL LABELING

MIDLAND 655

Active Ingredients: 12.50
Sodium Hypochlorite ~~14.05%~~
Inert Ingredients ~~85.95%~~
87.50

EPA Registration Number - 27581-20001

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

ASPHALT OR WOOD ROOFS AND SIDINGS

To control fungus and mildew, first remove all physical soil by brushing and hosing with clean water, and apply a 5000 ppm available chlorine solution. Mix 5 oz. of MIDLAND 655 per gallon of water and brush or spray roof or siding. After 30 minutes, rinse by hosing with clean water.

BOAT BOTTOMS

To control slime on boat bottoms, sling a plastic tarp under boat, retaining enough water to cover the fouled bottom area, but not allowing water to enter enclosed area. This envelope should contain approximately 500 gallons of water for a 14-foot boat. Add 18 oz. of MIDLAND 655 to this water to obtain a 35 ppm available chlorine concentration. Leave immersed for 8 to 12 hours. Repeat if necessary. Do not discharge the solution until the free chlorine level has dropped to 0 ppm, as determined by a swimming pool test kit.

ARTIFICIAL SAND BEACHES

To sanitize the sand, spray a 500 ppm available chlorine solution containing 5 oz. of MIDLAND 655 per 10 gallons of water at frequent intervals. Small areas can be sprinkled with a watering can.

TOILET BOWL SANITIZERS

[These products are marketed as individual packages for placement in the toilet. Therefore, use directions are not appropriate.]

[Claims are limited to sanitization. No claims for disinfection are permitted.]

KEEP OUT OF REACH OF CHILDREN DANGER

See Principal Label For Complete Precautionary Information and Storage and Handling Instructions

Midland Research Laboratories, Inc.
10850 Mid America Avenue
Lenexa, KS 66219
(913) 888-0560

22/22

SUPPLEMENTAL LABELING

MIDLAND 655

Active Ingredients: 12.50
Sodium Hypochlorite ~~14.05%~~
Inert Ingredients ~~85.95%~~
87.50

EPA Registration Number - 27581-20001

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

SANITIZATION OF DIALYSIS MACHINES

Flush equipment thoroughly with water prior to using MIDLAND 655. Thoroughly mix 6 oz. of MIDLAND 655 to 10 gallons of water to obtain at least 600 ppm available chlorine. Immediately use MIDLAND 655 in the hemodialysate system allowing for a minimum contact time of 15 minutes at 20 C. Drain system of the sanitizing solution and thoroughly rinse with water. Discard and DO NOT reuse the spent sanitizer. Rinsate must be monitored with a suitable test kit to insure that no available chlorine remains in the system.

MIDLAND 655 is recommended for decontaminating single and multipatient hemodialysate systems. MIDLAND 655 has been shown to be an effective disinfectant (virucide, fungicide, bactericide, pseudomonicide; when tested by AOAC and EPA test methods. MIDLAND 655 may not totally eliminate all vegetative microorganisms in hemodialysate delivery systems due to their construction and/or assembly but can be relied upon to reduce the number of microorganisms to acceptable levels when used as directed. MIDLAND 655 should be used in a disinfectant program which includes bacteriological monitoring of the hemodialysate or reverse osmosis (RO) membranes.

Consult the guidelines for hemodialysate systems which are available from the Hepatitis Laboratories, CDC, Phoenix, AZ 85021.

KEEP OUT OF REACH OF CHILDREN
DANGER

See Principal Label For Complete Precautionary Information and Storage and Handling Instructions

Midland Research Laboratories, Inc.
10850 Mid America Avenue
Lenexa, KS 66219
(913) 888-0560

