

U. S. ENVIRONMENTAL PROTECTION AGENCY WASHINGTON D.C. 20460-000

PREVENTION, PESTICIDES AND TOXIC SUBSTANCES

SEP 1 2 2000

Jody A. Fox Director of Regulatory Affairs Midland Fumigant Inc. 1805 South 2nd Street Leavenworth, KS 66048

Subject:

EPA Reg. No. 30574-8

TRI-TOX® 55% Pellets

Amendments to Label and Applicator's Manual

Your Letter dated July 21, 2000

Dear Ms. Fox:

The Agency has completed review of the submission referred to above. The label and Applicator's Manual are acceptable provided that you make the following changes:

Label

)

- 1. Change product's name to "TRI-TOX" 55% Pellets. Even though the Agency has accepted "PH THREE PELLETS" as an alternate name (Memo dated January 05, 1999), the primary label should carry the basic name.
- 2. Delete "See Applicator's Manual for additional environmental hazards" (last sentence under Environmental Hazards section) as there are no additional Environmental Hazard statements given in the Applicator's Manual under Burrowing Pest Control (page 12).
- 3. Add "Aluminum phosphide tablets are bulk packaged in resealable aluminum flasks" in the beginning of second paragraph under Directions for Use.
- 4. Delete "spray mixture or rinsate" from the sentence "Improper disposal ... violation of Federal Law" under Disposal section.

Applicator's Manual

- 1. Change product's name to "TRI-TOX"
- 2. Delete "or EPA" from "Call Midland Furnigant any part of the labeling" in the paragraph above Warranty section on page 1.

EPA Reg. No. 30574-8 contd...

A stamped copy of the label and Applicator's Manual are enclosed for your records. Submit two (2) copies of the final printed labeling and Applicator's Manual before you release the product for shipment. If this condition is not complied with, the registration will be subject to cancellation in accordance with FIFRA sec 6(e). Your release for shipment of the product bearing the amended labeling constitutes acceptance of this condition. Should you have any questions, do not hesitate to contact me at 703-605-0368.

Sincerely,

S. Oonnithan, Ph.D.

Entomologist; IRB/RD (7505C) Office of Pesticide Programs

Encl.

with CON ENTS
In EPA Letter Dated:

Under the Federal Insecticide.
Fungicide, and Rodenticide Actions amended, for the participations of the participation of the participations of the participation of the participation of the particip

30574-8

RESTRICTED USE PESTICIDE DUE TO ACUTE INHALATION TOXICITY OF HIGHLY TOXIC PHOSPHINE GAS

For retail sale to and use only by Certified Applicators for those uses covered by the Applicator's certification or persons trained in accordance with the attached Applicator's Manual working under the direct supervision of, and in the physical presence of the Certified Applicator on site or on the nembers.

READ AND FOLLOW THE LABEL AND THE PH THREE APPLICATOR'S MANUAL WHICH CONTAINS COMPLETE INSTRUCTIONS FOR THE SAFE USE OF THIS PESTICIDE.

ALUMINUM PHOSPHIDE

A fumigant for use against listed insects which infest listed raw Agricultural Commodities, Specified Processed Foods, Animals Feeds and Control of Burrowing Pests. (See Applicator's Manual)

ACTIVE INGREDIENT:										
Aluminum Phosphide	 ٠.	 	 		 			 ٠,	:	55%
INERT INGREDIENTS:										
Total	 	 			 			 	. 10	00%

DANGER PELIGRO

POISON

PRECAUCION AL USUARIO: Si usted no lee ingles, no use este producto hasta que la etiqueta se la haya sido explicado ampliamente

STATEMENT OF PRACTICAL TREATMENT

Symptoms of overexposure to phosphine are headache, dizziness, nausea, difficult breathing, vomiting and/or diarrhea, in all cases of overexposure, get medical attention immediately. Take victim to a doctor or emergency treatment faculty.

THE GAS FROM ALUMINUM PHOSPHIDE IS INHALED: Get exposed person to fresh air. Keep warm and make sure person can breather treely. If breathing has stopped, pive artificial respiration by mouth-omouth or other means of resuscitation. Do not give anything by mouth to an unconscious person, if ALUMINUM PHOSPHIDE PELLET IS SWALLOWED. Drink or administer one or two glasses of water and induce vomitting by touching back of throat with finger or, if available, syrup of ipecac. Do not give anything

by mouth if victim is unconscious or not alert. If POWDER, GRANULES, OR PELLETS OF ALUMINUM PHOSPHIDE GET ON SKIN: Brush material off colthes and shoes in a well ventilated area. Allow clothes to aerate in a ventilated area prior to laundering. Wash contaminated bare skin thoroughly with soap and water.

IF IN EYES; Flush with plenty of water. Get medical attention.

SEE SIDE PANEL AND APPLICATOR'S MANUAL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

Manufactured by: MIDLAND FUMIGANT CO. INC. 1805 South 2nd Street, Leavenworth, Kansas 66048

PRECAUTIONARY STATEMENTS Hazards to Humans and Domestic Animals KEEP OUT OF REACH OF CHILDREN DANGER - POISON

Aluminum phosphide powder, granules, or pellets may be fatal if swallowed. Do not get in eyes, or skin, or on clothing. Do not eat, drink or smoke while handling aluminum phosphide furnigants. If a sealed container is opened, or if the material comes in contact with moleture, water or acids, extremely toxic phosphine gas will be released, if a garlic odor is detected, you must monitor to determine whether phosphine gas is present above the acceptable exposure limits (see section or respiratory protection). Since an odor may not be detected under cartain circumstances, the absence of a garlic odor does not mean that phosphine gas is absent. Observe proper application, sention, re-entry, and disposal procedures specified elsewhere in the labelling to prevent oversposure. NOTE TO PHYSICIAN: Aluminum phosphide reacts with moisture in the air, acids and many other fiquids to release phosphine gas. Italie expessers by inhalation causes makies, ringing of ears, fatigue, nausea and/or pressure in the chest which is relieved by removal to trash air. Mederale pelsoning causes weakness, vomiting, epigastric pain, chest pain, diarrhea and/or-dyspnea. Severe pelsealing may occur in a few hours to several days, resulting in pulmonary edema, and may lead to dizziness, cyanosis, unconsciousness and/or death. In sufficient quantity, phosphine affects the liver, kidneys, lungs, nervous system and circulatory system. Inhalation can cause lung and brain symptoms, but damage to the viscera is more common. Phosphine polsoning may result in (1) pulmonary edema;(2) liver elevated serum GOT, LDH and alkaline phosphatase, reduced probrombin, hemorrhage and jaundica; and (3) kidney hematuria and anuria.

ENVIRONMENTAL HAZARDS

This product is very highly toxic to fish and wildlife. Non-target organisms exposed to phosphine gas will be kiffed. Do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water by cleaning of equipment or disposal of wastes. See Applicator's Manual for additional Environmental Hazards.

PHYSICAL/CHEMICAL HAZARDS

Aluminum phosphide in pellets or partially spent dust will release phosphine gas if exposed to moisture from the air or if it comes into contact with water, acids, and many other iquids. Piling of pellets or dust from their fragmentation may cause a temperature increase and confine the release of das so that familion could occur.

Always open container of aluminum phosphide products outdoors, as under certain conditions they may flash upon opening. When opening, point the container away from the face and body and slowly loosen the cap. Although the chances for flash are very remote, never open these containers in a flammable atmosphere. These precautions will also reduce the applicator's exposure to phosphine gas. Pure phosphine gas is practically insoluble in water and oils, and is stable at normal jumigation temperatures. However, it may react with certain metals and cause corrosion, especially at higher temperatures and relative humidities. Metals such as copper, brass, other copper alloys and precious metals such as gold and silver are susceptible to corrosion by phosphine. Thus, small electric motors, smoke detectors, brass sprinkler heads, batteries and battery chargers, fork lifts, temperature monitoring systems, switching gears, communication devices, computers, calculations and/or other electrical equipment should be protected or removed before fumigation. Phosphine gas will also react with certain metaltic salts and, therefore, sensitive items such as photographic film, some inorganic pigments, etc., should not be exposed.

STORAGE AND HANDLING

Store under lock and key, in a dry, well-vertilisted area away from heat. Post as a pesticide storage area. Do not comaminate water, food, or feed by storing pesticides in the same areas used to store these commodities. Do not store in buildings inhabited by humans or domestic ankmals. Aluminum phosphilde products shall not be placed in or attached to packages intended for retailers.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. This furnigant is a highly hazardous material and may only be used by individuals trained in its proper use. Before using, read and follow all precautions and complete directions for use on the PH THREE label and in the PH THREE APPLICATOR'S MANUAL. Additional APPLICATOR'S MANUALS and MSDS's are available through MIDLAND FUMISANT CO. INC., 1805 South 2nd, Leavenworth, KS 66048, (913) 651-3900.

SPILL AND LEAK PROCEDURES

A spill, other than incidental to application or normal handling, may produce high levels of gas. Therefore, attending personnel must wear SCBA or its equivalent when the concentration is unknown. Other NIOSH/MSNIA approved respiratory protection may be worn if the concentration is unknown. On not use water at any time to clean up a spill of aluminum phosphide. Water in contact with unreacted aluminum phosphide pellets will greatly accelerate the production of phosphine gas which could result in a toxic and/or fire hazard. Wear cotton gloves when handling this product. Return all intact containers to cardboard cases or other suitable packaging which has been properly marked according to DOT regulations. Notify consignee and shipper of damaged cases. If containers have been punctured or damaged so as to leak, the container may be temporarily repaired with aluminum tape or the aluminum phosphide may be transferred from the damaged containers to a sound metal container which should be sealed and properly labeled as aluminum phosphide. Transport the damaged container to an area suitable for pesticide storage for inspection. Further instructions and recommendations may be obtained, if required, from MIDLAND FUMIGANTS CO. INC.

STORAGE AND DISPOSAL

STORAGE:

Store in a locked, dry, well-ventilated area away from heat. Post as a pesticide storage area. Do not contaminate water, food or feed by storing pesticide in the same areas used to store these commodities. Do not store in buildings inhabited by humans or domestic animals.

DISPOSAL:

Unreacted or partially reacted aluminum phosphide is acutely hazardous, improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance. For specific instructions, see Spill and Leak Procedures in PH Three Applicator's Manual.

Some local and state waste disposal regulations may vary from the following recommendations. Disposal procedures should be reviewed with appropriate authorities to ensure compliance with local regulations. Contact your State Pesticide or Environmental Control Agency or Hazardous Waste Specialist at the nearest EPA Regional Office for guidance.

Empty Container Disposal: Make sure container is empty of pellets and dust. Triple rinse entire container and stoppers with water. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by other procedures approved by state and local authorities. It is also permissible to remove ilds and expose empty flasks to atmospheric conditions until residue in flasks is reacted. Then, puncture and dispose of flasks in a sanitary landfill or other approved site, or by other procedures approved by State and local authorities. If property exposed, the residual dust remaining after a fumigation with aluminum phosphide will be graytsh-white and contain only a small amount of unreacted material. However, residual dust from incompletely exposed aluminum phosphide will require special care. Refer to PH Three Applicator's Manual for specific instructions.

SEE APPLICATOR'S MANUAL FOR ADDITIONAL INFORMATION

WARRANTY

Seller does not make warranties expressed or implied on the usage of this product other than those directed on the label. Customer assumes all risks in handling and use of this material contrary to label recommengations.

10-14-9

ACCEPTED with COMMENTS EPA Letter Dated: SEP | 2 2000

Under the Federal income with Fungicide, and Rodenne

RESTRICTED USE PESTICIDE 30.5 74-8

DUE TO ACUTE INHALATION TOXICITY OF HIGHLY TOXIC HYDROGEN PHOSPHIDE (PHOSPHINE, PH.) GAS

For retail sale and use only by certified applicators for those uses covered by the applicator certification or persons trained in accordance with the Applicator's Manual working under the direct supervision and in the physical presence of the certified applicator. Physical presence means on site or on the premises. Read and follow the label and the Applicator's Manual which contains complete instructions for the safe use of this pesticide.

APPLICATOR'S MANUAL

FOR

PELLETS AND TABLETS OF ALUMINUM PHOSPHIDE

For use against insects which infest stored Commodities and Control of Burrowing Pests

PH THREE TABLET ACTIVE INGREDIENT: EPA REG NO

30574~7

Land to the Control of the Control o

Aluminum Phosphide . . . 55% **INERT INGREDIENTS: 45%**

Total 100%

PH THREE PELLET EPA REG NO

30574-8

DANGER **PELIGRO** POISON POISON **KEEP OUT OF** REACH OF CHILDREN

PELIGRO AL USUARIO: Si usted no lee ingles, no use este producto hasta que la etiqueta se la haya sido explicado

(TO THE USER: If you cannot read English, do not use this product until the label and manual has been fully explained to you.)

STATEMENT OF PRACTICAL TREATMENT

Symptoms of overexposure are headache, dizziness, nausea, difficult breathing, vomiting, and diarrhea. In all cases of overexposure, get medical attention immediately. Take victim to a doctor or emergency treatment facility.

If the gas or dust from aluminum phosphide is inhaled: Get exposed person to fresh air. Keep warm and make sure person can breathe freely. If breathing has stopped, give artificial respiration by mouth-to-mouth or other means of resuscitation. Do not give anything by mouth to an unconscious person.

if aluminum phosphide petlets or tablets are swallowed: Drink or administer one or two glasses of water and induce vomiting by touching the back of the throat with finger, or if available, syrup of ipecac. Do not give anything by mouth if victim is unconscious or not alert.

If powder or granules of aluminum phosphide get on skin or clothing: Brush or shake material off clothes and shoes in a well ventilated area. Allow clothes to aerate in a ventilated area prior to laundering. Do not leave contaminated clothing in occupied and/or confined areas such as automobiles, vans, motel rooms, etc. Wash contaminated clothing in occupied and/or confined areas such as automobiles, vans, motel rooms, etc. Wash contaminated clothing in occupied and/or confined areas such as automobiles, vans, motel rooms, etc. taminated skin thoroughly with soap and water.

If dust from pellets or tablets gets in eyes: Flush with plenty of water. Get medical attention immediately.

THIS PRODUCT IS ACCOMPANIED BY AN APPROVED LABEL AND APPLICATOR'S MANUAL. READ AND UNDERSTAND THE ENTIRE LABELING. ALL PARTS OF THE LABELING ARE EQUALLY IMPORTANT FOR SAFE AND EFFECTIVE USE OF THIS PRODUCT. CALL MIDLAND FUMIGANT OR EPA IF YOU HAVE ANY QUESTIONS OR DO NOT UNDERSTAND ANY PART OF THIS LABELING. REFER TO THE APPLICATOR'S MANUAL FOR DETAILED PRECAUTIONS, RECOMMENDATIONS AND DIRECTIONS FOR USE.

WARRANTY

Seller warrants that the product conforms to its chemical description and when used according to label directions under normal conditions of use, it is reasonably fit for the purposes stated on the label. Seller makes no other warranty, either expressed or implied, and buyer assumes all risk should the product be used contrary to label

CLASSIFIED BY UNDERWRITERS LABORATORIES, INC. AS TO FIRE HAZARD ONLY WHEN USED SPECIFICALLY AS DIRECTED IN THE MANUFACTURER'S INSTRUCTIONS. PH THREE TABLETS OF PELLETS ARE NONCOMBUSTIBLE, BUT EXPOSURE TO MOIST AIR OR WATER RELEASES FLAMMABLE AND TOXIC PHOSPHINE (HYDROGEN PHOSPHIDE) GAS. SPONTANEOUS IGNITION MAY RESULT IF CONTACTED BY WATER, ACIDS, OR CHEMICALS.

TABLE OF CONTENTS

INTRODUCTION

PRECAUTIONARY STATEMENTS

- A. Hazards to Humans and Domestic Animals
 B. Statement of Practical Treatment
 C. Note to Physical
 D. Physical and Chemical mazards

DIRECTIONS FOR USE

- A. General B. Efficacy C Exposur

- Exposure Conditions
 Commodities Which May Be Furnigated with PH THREE
 Recommended Dosages
- Application Procedures

PROTECTIVE CLOTHING

RESPIRATORY PROTECTION

- When respiratory Protection Must Be Worn
 Permissible Gas Concentration Ranges for Respiratory Protection Devices
- C. Requirements for Availability of Respiratory Protection

PLACARDING OF FUMIGATED AREAS

AERATION OF FUMIGATED COMMODITIES

- A. Foods and Feeds

APPLICATORS AND WORKER EXPOSURE

- A. Hydrogen Phosphide Exposure Limits
 B. Application of Furnigant
 C. Leakage from Furnigated Sites
 D. Aeration and Reentry
 E. Handling Unaerated Commodities
 F. Industrial Hygiene Monitoring

STORAGE INSTRUCTIONS

10. DISPOSAL INSTRUCTIONS

فالمستغلاف أنسا للفائف فليستنفؤه والمارات المناسي المازيان والمعجور أوالمعار

- B. Directions for Disposal of Residual Dust from PH THREE
 C. Directions for Deactivation of Residual Dust from PH THREE

SPILL AND LEAK PROCEDURES

- General Precautions and Directions
- B. Directions for Deactivation by the Wet Method

SECTION 1 INTRODUCTION

PH THREE furnigants are used to protect stored commodities from damage by insects and for the control of burrowing pests. Furnigation of stored products with PH THREE in the manner prescribed in the labeling does not contaminate the stored commodity.

PH THREE and other Aluminum Phosphide fumigants are acted upon by atmospheric moisture to produce Hydrogen Phosphide (phosphine, PH.) gas. PH THREE tablets or pellets contain aluminum phosphide (AIP) as their active ingredient and will liberate hydrogen phosphide via the following chemical reaction:

Hydrogen phosphide gas is highly toxic to insects, burrowing pests, humans, and other forms of animal life. In addition to its toxic properties, the gas will corrode certain metals and may ignite spontaneously in air at concentrations above its lower flammable limit of 1.8% (v/v). These hazards will be described in greater detail later on in this Applicator's Manual for PH THREE pellets or tablets.

PH THREE also contains ammonium carbamate which liberates ammonia and carbon dioxide as follows:

These gases are essentially nonflammable and act as inerting agents to reduce fire hazards. The ammonia gas also serves as a warning agent.

PH THREE is prepared in two forms: tablets and pellets. The rounded tablets weigh approximately 3 grams and release 1 gram of hydrogen phosphide gas. They are about 16mm in diameter and are bulk packaged in resealable aluminum flasks containing 100 or 500 tablets each. The pellets weigh approximately 0.6 grams and release 0.2 gram of hydrogen phosphide gas. They are about 16 mm in diameter and are packaged in resealable flasks containing about 1660 pellets.

Upon exposure to air, PH THREE pellets or tablets begin to react with atmospheric moisture to produce small quantities of hydrogen phosphide gas. This reaction starts slowly, gradually accelerates and then tapers off again as the aluminum phosphide is spent. PH THREE pellets react somewhat faster than do the tablets. The rates of decomposition of the tablets and pellets will vary depending upon moisture and temperature conditions. For example, when moisture and temperature of the furnigated commodity are high, decomposition of PH THREE may be complete in less than 3 days. However, at lower ambient temperatures and relative humidity levels, decomposition of PH THREE may require 5 days or more. After decomposition, PH THREE leaves a gray-white powder composed almost entirely of aluminum hydroxide and other approved inert ingredients. This will cause no problems if the furnigant has been added directly to commodities such as grain or bulk animal feed. However, the spent powder must usually be retrieved for disposal after space furnigations. If properly exposed, the spent PH THREE will normally contain only a small amount of unreacted aluminum phosphide and may be disposed of without hazard. While not considered a hazardous waste, partially spent residual powder from incompletely exposed PH THREE will require special care. Precautions and instructions for further deactivation and disposal will be given later in this Manual.

PH THREE pellets and tablets are supplied in gas-tight containers and their shelf life is unlimited as long as the packaging remains intact. Once opened for fumigation, the flasks of tablets and pellets may be tightly resealed and stored for future use. Storage and handling instructions will be given in detail later in this Applicator's Manual.

A Summary of Safety Recommendations is Outlined Below:

SAFETY RECOMMENDATION SUMMARY

- 1. Carefully read the labeling and follow instructions.
- 2. Never fumigate alone from inside the storage structure.
- Person supervising must be a certified furnigator and personnel assisting must be trained in the use of AIP. Never allow uninstructed personnel to handle PH THREE.
- 4. Approved respiratory protection must be available for the furnigation of structures from within.
- Wear dry gloves of cotton or other material if contact with PH THREE tablets or pellets is likely. Aerate used gloves and other contaminated clothing in a well-ventilated area prior to laundering. Wash hands thoroughly after using PH THREE.
- 6. Open fumigant containers in open air only. Never open in a flammable atmosphere.
- 7. Do not allow PH THREE to contact liquid.
- 8. Do not allow PH THREE to pile up.
- 9. Dispose of empty containers and spent residual dust in a manner consistent with the label instructions.
- 10. Post warning placards on furnigated areas.
- 11. Prior to fumigation, notify appropriate company employees. Provide to local officials (fire department, rescue squad, police, etc.) on an annual basis relevant safety information for use in the event of an emergency.
- 12. Hydrogen phosphide fumigants are not to be used for vacuum fumigations.
- Exposure to hydrogen phosphide must not exceed the eight hour TWA of 0.3 ppm during application, or a ceiling concentration of 0.3 ppm after application is completed.
- 14. Furnigated areas must be aerated to 0.3 ppm hydrogen phosphide or less prior to reentry by unprotected workers.
- 15. Finished foods and feeds that have been furnigated with PH THREE must be aerated for 48 hours prior to offering to the end use consumer.
- 16. Transfer of a treated commodity to another site without complete aeration is permissible, provided that the new storage site is placarded if its concentration is above 0.3 ppm.
- 17. Keep containers of PH THREE tightly closed except while removing product for application.
- 18. Protect materials containing metals such as copper, silver, gold and their alloys and salts from corrosive exposure to hydrogen phosphide.
- 19. Tablets, pellets and bags must not come in contact with any processed food except that they may be added directly to processed brewers rice, malt and com grits used in the manufacture of beer.
- 20. Do not use aluminum phosphide containers for any purpose other than recycling or reconditioning.
- OSHA recommends pre-exposure screening of employees to detect impaired pulmonary function.
 OSHA recommends that any employees developing this condition be referred for medical examination.

PRECAUTIONARY STATEMENTS

Hazards to Humans and Domestic Animals

CANGER: Aluminum phosphide from PH THREE tablets or pellets may be fatal if swallowed. Do not get in eyes, on skin or on clothing. Do not eat, drink or smoke while handling aluminum phosphide furnigants. If sealed container is opened, or if the material comes in contact with moisture, water or acids, these products will release hydrogen phosphide (phosphine, PH) which is an extremely toxic gas. If a garlic odor is detected, refer to the Industrial Hygiene Monaging Section on page 14 of the Applicator's Manual for appropriate monitoring procedures. Pure hydrogen phosphide gas is odorless; the garlic odor is due to a contaminant. Since the odor of hydrogen phosphide may not be detected under some circumstances, the absence of a garlic odor does not mean that dangerous levels of hydrogen phosphide gas are absent. Observe proper reentry procedures specified elsewhere in the labeling to prevent overexposure.

B. Statement of Practical Treatment

Symptoms of overexposure are headache, dizziness, nausea, difficult breathing, vomiting, and diarrhea. In all cases of overexposure, get medical attention immediately. Take victim to a doctor or emergency treatment facility.

If the gas or dust from aluminum phosphide is inhaled; Get exposed person to fresh air. Keep warm and make sure person can breathe freely. If breathing has stopped, give artificial respiration by mouth-to-mouth or other means of resuscita-tion. Do not give anything by mouth to an unconscious person.

If aluminum phosphide pellets or tablets are swallowed: Drink or administer one or two glasses of water and induce vomitting by touching back of throat with finger, or if available, syrup of ipecac. Do not give anything by mouth if victim is unconscious or not alert.

If powder or granules of aluminum phosphide get on skin or clothing: Brush or shake material off clothes and shoes in a well ventilated area. Allow clothes to aerate in a ventilated area prior to laundering. Do not leave contaminated clothing in occupied and/or confined areas such as automobiles, vans, motel rooms, etc. Wash contaminated skin thoroughly with soap and water.

If dust from pellets or tablets gets in eyes: Flush with plenty of water. Get medical attention.

C. Note to Physician (we recommend that this section be given to the attending physician) Aluminum phosphide tablets or pellets react with moisture from the air, acids and many other liquids to release hydrogen phosphide (phosphine PH.) gas. Mild exposure by inhalation causes malaise (indefinite feeling of sickness). ringing in the ears, fatigue, nausea and pressure in the chest which is relieved by removal to fresh air. Moderate poisoning may occur within a few hours to several days resulting in pulmonary edema (fluid in lungs) and may lead to dizziness, cyanosis (blue or purple skin color), unconsciousness, and death.

In sufficient quantity, phosphine affects the liver, kidneys, lungs, nervous system and circulatory system. Inhalation can cause lung edema (fluid in lungs) and hyperemia (excess of blood in body parts), small perivascular brain hemorrhages and brain edema (fluid in brain). Ingestion can cause lung and brain symptoms but damage to the viscera (body cavity organs) is more common. Phosphine poisoning may result in (1) pulmonary edema, (2) liver elevated serum GOT, LDH and alkaine phosphatase, reduced prothrombin, hemorrhage, and jaundice (yellow skin color) and (3) kidney hematuria (blood in urine) and anuria (abnormal or lack of unnation). Pathology is characteristic of hypoxia (oxygen deficiency in body tissue). Frequent exposure to concentration above permissible levels over a period of days or weeks may cause poisoning. Treatment is symptomatic.

The following measures are suggested for use by the physician in accordance with his own judgment: In its milder form, symptoms of poisoning may take some time (up to 24 hours) to make their appearance, and the following is suggested:

Give complete rest for 1-2 days, during which the patient must be kept quiet and warm.

Should patient suffer from vomiting or increased blood sugar, appropriate solutions should be administered. Treatment with oxygen-breathing equipment is recommended as is the administration of cardiac and circulatory stimulants.

In cases of severe poisoning (intensive Care Unit recommended):

Where pulmonary edema is observed, steroid therapy should be considered and close medical supervision is recommended. Blood transfusions may be necessary.

In case of manifest pulmonary edemá, venesection should be performed under vein pressure control. Heart glycosides (I.V.) (in case of hemoconcentration, venesection may result in shock). On progressive edema of the lungs: immediate intubation with a constant removal of edema fluid and oxygén over-pressure respiration, as well as any measures required for shock treatment. In case of kidney failure, extracorporeal hemodialysis is necessary. There is no specific antidote known for the poisoning.

3. Mention should be made here of suicidal attempts by taking solid phosphine by mouth. After swallowing: emptying of the stomach by vomiting, flushing of the stomach with diluted potassium permanganate solution of magnesium peroxide until flushing ceases to smell of carbide. Thereafter, apply carbomedicinalis.

D. Physical and Chemical Hazards

والمرابع المنتف المساعلات

Aluminum phosphide in tablets or pellets will release hydrogen phosphide if exposed to moisture from the air or if it comes in contact with water, acids and many other liquids. Piling of tablets or pellets from their fragmentation may cause a temperature increase and confine the release of gas so that ignition could occur.

It is preferable to open containers of aluminum phosphide products in open air, as under certain conditions, they may flash upon opening. You may also wish to open containers near a fan or other appropriate ventilation which will rapidly exhaust contaminated air. When opening, point the container away from the face and body and slowly loosen the cap. Although the chances for a flash are remote, never open the containers in a flammable atmosphere. These precautions will also reduce the furnigator's exposure to hydrogen phosphide.

Pure phosphine (hydrogen phosphide) gas is practically insoluble in water, fats and oils, and is stable at normal furnigation temperatures. However, it may react with certain metals and cause corrosion, especially at higher temperatures and relative humidities. Metals such as copper, brass and other copper alloys, and precious metals such as gold and silver are susceptible to corrosion by phosphine. Thus, small electric motors, smoke detectors, brass sprinkler heads, batteries and battery chargers, fork lifts, temperature monitoring systems, switching gears, communication devices, computers, calculators and other electrical equipment should be protected or removed before furnigation. Hydrogen phosphide will also react with certain metallic salfs and therefore, sensitive items such as photographic film, some inorganic pigments, etc. should not be exposed.

SECTION 3 DIRECTIONS FOR USE

A. General

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

1. PH THREE tablets or pellets are Restricted Use Pesticides due to the acute inhalation toxicity of hydrogen phosphide (phosphine PH.) gas. These products are for retail sale to and use only by certified applicators for uses covered by the applicator's certification or persons trained in accordance with the Applicator's Manual working under the direct supervision and in the physical presence of the certified applicator. Physical presence means on site or on the premises. Read and follow the label and the PH THREE Applicator's Manual which contains complete instructions for the safe use of this pesticide.

2. PH THREE is a highly hazardous material and should be used only by individuals trained in its proper use. Before using, read and follow the label precautions and directions. Additional copies of this Manual are available from: Midland Furnigant Co., Inc., 1805 S 2nd Street, Leavenworth, KS, 66048 (800) 332-3930. Persons working with PH THREE should be knowledgeable of the hazards of this chemical and trained in the

use of required respiratory equipment and detector device, emergency procedures and use of the fumigant.

3. A licensed furnigator must be present and at least two persons trained in the use of AIP should be present during furnigation of structure if entry into the structure is required for application of the furnigant. Two trained persons must also be present during reentry into furnigated or partially aerated structures. Only one trained person is required to be present when PH THREE is applied from outside the area to be treated.

Shipholds, barges, containers on ships, railroad cars and containers shipped piggyback by railway may be furnigated in transit. However, trucks, vans, trailers and similar transport vehicles cannot be moved over public roads

and highways until they are aerated and the warning placards removed.

5. Do not furnigate commodities with PH THREE when commodity temperature is below 40 degrees F. (5)

degrees C.). The site to be lumigated must first be inspected to determine if it can be sufficiently gas tight. Then a plan should be developed to provide for safe and efficient application of the furnigant to include emergency procedures, etc., where required, and decide how monitoring should be conducted to prevent excessive exposures.

7. Wear dry gloves of cotton or other material while handling PH THREE tablets or pellets. Wash hands

Hydrogen phosphide gas may flash at concentrations above its flammable limit. Therefore, always open PH THREE containers in open air and never in a flammable atmosphere. This precaution will not only prevent harm in the unlikely event of a flash, but will reduce the applicator's exposure to hydrogen phosphide gas.

Piling of tablets, pellets or bags or addition of liquid to PH THREE may speed up the reaction, cause a temperature increase and confine the gas so that ignition could occur.

10. As much as is possible, protect unused PH THREE from excessive exposure to atmospheric moisture

during application and tightly reseal the aluminum flask prior to returning tablets or pellets to storage.

11. Hydrogen phosphide gas may react with certain metals and their salts to produce corrosion. Copper,

copper alloys and precious metals such as silver and gold are susceptible to corrosion and items containing these elements should be removed or protected prior to furnigation with PH THREE

12. Do not allow PH THREE or its residual dust to come in contact with processed foods or commodity

packages intended for retailers except that PH THREE tablets or pellets may be added directly to processed brewers rice, malt and com grits used in the manufacture of beer.

13. Respiratory protection approved for the concentration to which the furnigator will be exposed must be available If PH THREE is to be applied from within the structure to be furnigated. Respiratory protection need not be available for uses such as outdoor application, addition of tablets or pellets to automatic dispensing devices, etc., if exposures above the TLV's will not be encountered.

A NIOSH/MSHA approved, full-face gas mask-hydrogen phosphide canister combination may be used at levels up to 15 ppm. Above this level or in situations where the hydrogen phosphide concentration is unknown, a NIOSH/MSHA approved, self-contained breathing apparatus (SCBA) or its equivalent must be used.

14. Notify appropriate company employees prior to furnigation. Provide to local officials (fire department, rescue squad, police, etc.) on an annual basis relevant safety information for use in the event of emergency.

B. Efficacy
PH THREE has been found effective against the following insects and their preadult stages — that is eggs, larvae, and pupae:

almond moth	European grain moth	Mediterranean flour moth
angoumois grain moth	flat grain beetle	pink bollworm
bean weevil	fruit flies	raisin moth
bees	granary weevil	red flour beetle
cadelle	greater wax moth	rice weevil
cereal leaf beetle	hairy fungus beetle	rusty grain weevil
cigarette beetle	Hessian fly	saw-toothed grain beetle
confused flour beetle	Indian meal moth	spider beetles
dermestid beetles	khapra beetle	tobacco moth
dried fruit beetle	lesser grain borer	yellow meal worm
dried fruit moth	maize weevil	•

Although it is possible to achieve total control of the listed insect pests, this is frequently not realized in actual practice. Factors contributing to less than 100% control are leaks, poor gas distribution, unfavorable exposure conditions, etc. In addition, some insects are less susceptible to hydrogen phosphide than others. If maximum control is to be attained, extreme care must be taken in sealing, the higher dosages must be used, exposure periods must be lengthened, proper application procedures followed, and temperature and humidity must be favorable.

C. Exposure Conditions

The following conditions may be used as a guide in determining the minimum length of the exposure period at the indicated temperatures:

Minimum Exposure Periods for PH THREE

Temperature	Pellets	Tablets
celow 40°F (5°C)	Do not furnigate	Do not fumigate
40°-53°F (5-12°C)	8 days (192 hours)	10 days (240 hours
54°-59°F (12-15°C)	4 days (96 hours)	5 days (120 hours)
50°-68°F(16-20°C)	3 days (72 hours)	4 days (96 hours)
above 68°F (20°C)	2 days (48 hours)	3 days (72 hours)

The length of the fumigation must be great enough so as to provide for adequate control of the insect pests which infest the commodity being treated. Additionally, the fumigation period should be long enough to allow for more or less complete reaction of PH THREE with moisture so that little or no unreacted aluminum phosphide remains. This will minimize exposures during further storage and/or processing of the treated bulk commodity as well as reduce hazards in the disposal of partially spent aluminum phosphide products remaining after space furnigations. The proper length of the furnigation period will vary with exposure conditions, since, in general, insects are more difficult to control at lower temperatures and the rate of hydrogen phosphide gas production by PH THREE is less at lower temperatures and

It should be noted that there is fittle to be gained by extending the exposure period if the structure to be furnigated has not been carefully sealed or if the distribution of gas is poor and insects are not subjected to lethal concentrations of hydrogen phosphide. Careful sealing is required to ensure that adequate gas levels are retained and proper application procedures must be followed to provide satisfactory distribution of hydrogen phosphide gas. Some structures can only be treated when completely tarped, while others cannot be properly sealed by any means and should not be furnigated. Exposure times must be lengthened to allow for penetration of gas throughout the commodity when furnigant is not uniformly added to the mass, for example, by surface application or shallow probing. This is particularly important in the furnigation of bulk commodity contained

in large storages.

Remember, exposure periods in the table are minimum periods and may not be adequate to control all stored products pests under all conditions nor will they always provide for total reaction of PH THREE, particularly if temperatures and commodity moisture levels or humidity are low during the fumigation.

D. Commodities Which May be Furnigated with PH THREE

PH THREE may be used for the furnigation of fisted raw agricultural commodities, animal feed and feed ingredients, processed foods, tobacco and certain other non-food items.

 Raw Agricultural Commodities, Animal Feed and Feed Ingredients
 PH THREE tablets or pellets may be added directly to animal feed, feed ingredients and raw agricultural
 commodities stored in bulk. For these commodities not stored in bulk, PH THREE may be placed in moisture permeable envelopes or on trays and furnigated as with processed foods.

Raw Agricultural Commodities and Animal Feed and Feed Ingredients Which May be Furnigated with PH THREE.

Filberts Almonds Flower Seeds Safflower Seeds Animal Feed **Grass Seeds** Seed & Pod Vegetables Barley Brazil Nuts Legumes Sesame Seeds Millet Cashews Sorghum Oats Soybeans Cocoa Beans Peanuts Coffee Beans Sunflower Seeds Pecans* Triticale X Com Cottonseed Pistachio Nuts * Vegetable Seeds Popcom Dates Walnuts Rice Wheat

2. Processed Foods

The listed processed foods may be furnigated with PH THREE. Under no condition shall any processed food or bagged commodity come in contact with PH THREE tablets or pellets or residual dust except that PH THREE may be added directly to processed brewer's rice, malt and com grits for use in the manufacture of beer.

Processed Foods Which May be Fumigated with PH THREE

- Processed candy and sugar
- Cereal flours and bakery mixes
- Cereal foods (including cookies, crackers, macaroni, noodles, pasta, pretzels, snack foods and spaghetti)
- Processed cereals (including milled fractions and packaged cereals)
- Cheese and cheese by-products
- Chocolate & chocolate products (assorted chocolate, chocolate liquor, cocoa, cocoa powder, dark chocolate coating and milk chocolate)
- Processed coffee
- Com grits Cured, dried and processed meat products and dried fish
- Dates and figs

- Dried eggs and egg yolk solids
 Dried eggs and egg yolk solids
 Dried milk, dried powdered milk, non-dairy creamers, and nonfat dried milk
 Dried or dehydrated fruits (apples, dates, figs, peaches, pears, prunes, raisins and sultanas)
 Processed herbs, spices, seasonings and condiments

- Processed nuts (almond, apricot kernels, Brazil nuts, cashews, filberts, peanuts, pecans, pistachio nuts, and walnuts
- Processed oats (including oatmeal)
- Rice (brewers rice, grits, enriched and polished wild rice)
- Processed tea
- Dried and dehydrated vegetables (beans, carrots, lentils, peas, potato products and spinach)
- Yeast (including primary yeast)

Nonfood commodities, including Tobacco

The listed nonfood items may be furnigated with PH THREE. Tobacco and certain other of the nonfood commodities should not be contacted by tablets, pellets, or residual dust.

- Nonfood commodities which may be fumigated with PH THREE
- Processed or unprocessed cotton, wool and other natural fibers of cloth, clothing
- Straw and hay
- Feathers

The same of the sa

- Human hair, rubberized hair, vulcanized hair, mohair
- Leather products, animal hides and furs
- Tobacco
- Wood, cut trees, wood chips and wood and bamboo products
- Paper and paper products
 Dried plants and flowers
- Seeds, (grass seed, ornamental herbaceous plant seed and vegetable seed)

E. Recommended Dosages

Hydrogen phosphide is a mobile gas that will penetrate to all parts of the storage structure. Therefore, dosage must be based upon the total volume of the space being treated and not on the amount of commodify it contains. The same amount of PH THREE is required to treat a 30,000 bushel silo whether it is empty or full of grain unless, of course, the surface of the commodity is sealed off by a tarpaulin. The following dosage ranges are recommended for bulk and space fumigations:

*Dosage rates for dates, nuts and dried fruits are 100-200 pellets or 20-40 tablets per 1000 cu. ft. and 125-250 pellets or 25-50 tablets per 1000 bu.

Product	per 1000 cu. ft.*	per 1000 bu.*
Pellets	100-725	120-900
Tablets	20-145	25-180

*Dosage range for dates, nuts & dried fruits is 100-200 pellets, 20-40 tablets, 125-250 pellets, 25-50 tablets.

These dosages are not to be exceeded. It is important to be aware that a shortened exposure period cannot be fully

compensated for with an increased dosage of hydrogen phosphide.

The wide range of dosages listed above is required to handle the variety of furnigation situations encountered in practice. Somewhat higher dosages are usually recommended under cooler, drier conditions or where exposure periods are relatively

However, the major factor in selection of dosage is the ability of the structure to hold hydrogen phosphide gas during the fumigation. A good illustration of this point is comparison of the low dosages required to treat modern, well-sealed warehouses with the higher range used for poorly constructed buildings that cannot be sealed adequately. In certain other fumigations, proper distribution of lethal concentrations of gas to reach all parts of the structure becomes a very important factor in dose selection. An example where they may occur is in the treatment of grain stored in tall silos. Poor gas distribution frequently results when the fumigant cannot be uniformly added to the grain and it must be treated by surface application.

Although it is permissible to choose from the full range of dosages listed above, the following dosages are recommended.

for the various types of fumigations:

Recommended PH THREE Dosages for Various Types of Fuminations

Type of Fumigation 1. Space	Pellets	Tablets				
Mills, Warehouses, etc.	100-300/1000 cu. ft.	20-60/1000 cu. ft.				
Bagged Commodities	150-300/1000 cu. ft.	30-60/1000 cu. ft.				
Processed Fruits & Nuts	100-200/1000 cu. ft.	20-40/1000 cu. ft.				
Stored Tobacco	100-200/1000 cu. ft.	20-40/1000 cu. ft.				
Bulk Stored Commodities						
Vertical Storages	150-300/1000 cu. ft.	30-70/1000 cu. ft.				
	200-375/1000 BU	40-75/1000 BU				
Tanks	150-350/1000 cu. ft.	30-60/1000 cu ft.				
	200-450/1000 BU	40-90/1000 BU				
Flat Storages	250-725/1000 cu ft.	50-145/1000 cu. ft.				
· At Oloragos	300-900/1000 BU	60-180/1000 BU				
Farm Bins	350-725/1000 cu ft.	70-145/1000 cu. ft.				
	450-900/1000 BU	90-180/1000 BU				
Bunkers & Tarped						
Ground Storages	150-400/1000 cu. ft.	30-80/1000 cu. ft.				
	200-500/1000 BU	40-100/1000 BU				
Railcars	150-325/1000 cu. ft.	30-65/1000 cu. ft.				
. 12:	200-400/1000 BU	40-80/1000 BU				
Barges	150-400/1000 cu. ft.	30-80/1000 cu. ft.				
	200-500/1000 BU	40-100/1000 BU				
Shipholds	150-330/1000 cu. ft.	30-66/1000 cu. ft.				
	200-375/1000 BU	40-75/1000 BU				

Higher dosages are recommended in structures that are of loose construction and in the fumigation of bulk stored commodities in which diffusion will be slowed and result in poor distribution of hydrogen phosphide gas.

Application Procedures

المناتبية والطائب المستهار تبزي المستهار المحتير البلازيات المنطق المستهار المستها

General Statement

Regardless of the type of storage to be treated, there are several important factors common to all application procedures. A number of these points have been covered in other sections of the Applicator's Manual but are listed again in the following for

a. A plan should be devised for application, aeration and disposal of the furnigant so as to keep to a minimum any exposures to hydrogen phosphide. See the requirements for industrial Hygiette Monitoring under the Applicator and Worker Exposure section of this Applicator's Manual.

PH THREE tablets or pellets should be applied so as to provide effective gas concentrations throughout the storage. When tablets or pellets are not applied uniformly to a bulk commodity (surface application in a tall são or ship's hold for example), exposure times should be lengthened to allow for penetration of gas throughout the storage.

The storage structure should be sealed so as to maintain a suitable gas concentration over the time period required for control of insect pests.

d. Ideally, exposure periods should be long enough to provide for adequate control of insect pests and also more or

less completely react the furnigant.

Piling of large numbers of tablets or pellets, whether applied to a bulk commodity or for space furnigation may prevent complete breakdown of the product by limiting its access to moist air. This can result in decreased efficacy as a result of poor gas release and may leave an active residual for disposal which contains considerable amounts of unreacted aluminum phosphide. Pilling of product may also result in increased hazard of fire if water should come into contact with the mass of aluminum phosphide.

Contact with liquid water should be carefully avoided when applying PH THREE for treatment of bulk commodities or space.

Aluminum phosphide furnigants should not be applied to confined spaces where the concentration of hydrogen phosphide may build up to exceed its lower flammable limit.

h. Observe the precautionary and safety statements mentioned in this manual.

The following instructions are intended to provide general guidance for typical furnigations. These instructions are not intended to cover every type of situation nor are they meant to be restrictive. Other procedures may be used if they are safe, effective and consistent with the properties of aluminum phosphide products.

2. Fumigations of Farm Bins

Leakage is the single most important cause of failures in the treatment of farm storages. Since these storages are often small, they usually have a higher leakage area in proportion to their capacity. Most wooden storage structures are so porous that they cannot be successfully furnigated unless they are completely tarped. Do not furnigate storages which will be entered by humans or animals prior to aeration. Do not furnigate areas which house sensitive equipment

containing copper or other metals likely to be corroded by hydrogen phosphide gas.

Seal the bin as tightly as possible. It is recommended that the surface of the grain be covered with poly after PH THREE has been applied. Tarping the grain surface will greatly reduce the leak rate of the gas as well as reduce the amount of PH THREE required. Only the volume below the tarp must be dosed. If not tarped, the entire volume

of the storage must be treated, whether full or empty.

PH THREE tablets or pellets may be scattered over the surface or probed into the grain using a rigid PVC pipe about 5 to 7 feet in length and having a diameter of 1-1/4 inches. Use about 20-50 tablets or 100-250 pellets. Immediately cover the surface of the grain with a plastic tarpaulin. Place no more than 25 percent of the total dose at the bottom if the bin is equipped with aeration lans. Caution: Make sure that the aeration duct is dry before adding PH THREE. Addition of PH THREE to water in an aeration duct may result in a fire. Seal the aeration fan with 4 mil plastic sheeting.

Post furnigation warning signs on entrances to the bin and near the ladder.

Following aeration of the bin, the surface of the grain may be sprayed with an approved protectant to discourage reinfestation

Furnigation of Flat Storages

المناك بفتاعين والمنافق والمنا

Establish a plan for application of fumigant to the structure. Treatment of these types of storages may require considerable effort. Therefore, sufficient manpower should be available to complete the work rapidly enough to prevent excessive exposure to hydrogen phosphide gas. Vent flasks outside the storage, conduct furnigations during the cooler periods and employ other work practices to minimize exposures. It is often advisable to wear respiratory protection during application of furnigant to flat storages. Refer to the sections on Applicator and Worker Exposure and Respiratory Protection.

Seal any vents, cracks and other sources of leaks.

Apply tablets or pellets by surface application, shallow probing, deep probing or uniform addition as the bin is filled

Storage requiring more than 24 hours to fill should not be treated by addition of furnigant to the commodity stream as large quantities of hydrogen phosphide may escape before the bin is completely sealed.

Probes should be inserted vertically at intervals along the length and width of the flat storage. Pellets or tablets

may be dropped into the probe at intervals as it is withdrawn.

Surface application may be used if the bin can be sufficiently gas tight to contain the furnigant gas long enough for it to penetrate the commodity. In this instance, it is advisable to place about 25 percent of the dosages in the floor level aeration ducts. Check the ducts prior to addition of PH THREE to make sure that they contain no liquid water.

ď Tarping the surface of the commodity is often advisable, particularly if the overhead of the storage cannot be well sealed.

e. Lock all entrances to the storage and post fumigation warning placards.

Fumigation of Vertical Storages (concrete upright bins and other silos in which grain can be rapidly transferred).

Close all openings and seal all cracks to make the structure as airtight as possible. Prior to the furnigation, seal

the vents near the bin top which connects to adjacent bins.

b. Pellets or tablets may be applied continuously by hand or by an automatic dispenser on the headhouse/gallery belt or into the fill opening as the commodity is loaded into the bin. An automatic dispenser may also be used to add PH THREE into the commodity steam in the leg of the elevator.

Seal the bin deck openings after the fumigation has been completed

Bins requiring more than 24 hours to fill should not be furnigated by continued addition into the commodity stream. These bins must be furnigated by probing surface application, or other appropriate means. Exposure periods should be length-ened to allow for diffusion of gas to all parts of the bins in which PH THREE has not been applied uniformly throughout the commodity mass

Place warning placards on the discharge gate and on all entrances.

Fumigation of Mills, Food Processing Plants and Warehouses

a. Using the information presented above in this manual, calculate the length of the furnigation and dosage of tablets or pellets to be applied based upon volume of the building, air and/or commodity temperature and the general tightness of the structure.

Carefully seal and placard the space to be furnigated.

- Place trays or sheets of Kraft paper or foil, up to 12 sq. ft (1.1 sq. M) in area, on the floor throughout the structure to
- hold PH THREE pellets or tablets. Use total floor space.

 d. Spread PH THREE on the sheets at a density no greater than 30 tablets per sq. ft. This corresponds to slightly more than one-half flask of tablets or one-half flask of pellets per 3' x 4' sheet. Check to see that PH THREE has not piled up and that it is spread evenly to minimize contact between the individual pellets or tablets.

Doors leading to the furnigated space should be closed, seated, locked, and placarded with warning signs. The furnigation period usually lasts from 2 to 5 days, depending upon the temperature. Upon completion of the exposure period, windows, doors, vents, etc. should be opened and the furnigated structure allowed to aerate for at least two hours before entering. When required, gas concentration readings may be taken using low level detector tubes or similar devices to ensure safety of personnel who reenter the treated area. Refer to the section on Applicator and Worker Exposure.

Collect the residual dust and dispose of it, with or without further deactivation. following the recommendations

given under Disposal Instructions.

Remove fumigation warning placards from the aerated structure.

Fumigation of Railcars, Containers, Trucks, Vans and other Transport Vehicles

Railcars, containers, trucks, vans and other transport vehicles loaded with bulk commodities to which PH THREE tablets or pellets may be added directly are treated in essentially the same way as any other flat storage facility. PH THREE may be added as the vehicle is being filled, the dose may be scattered over the surface after loading has been completed or the tablets or pellets may be probed below the surface. Carefully seal any vents, cracks, or other leaks, particularly if the furnigation is to be carried out in transit. Remember, railcars and containers shipped piggyback by rail may be furnigated in transit, but it is not legal to move trucks, trailers, vans, etc. over public roads or highways until they are aerated. See Section 6 of this Applicator's Manual for the recommendations on placarding. Notify the consignee if the commodity is to be shipped under furnigation with PH THREE. If the consignee is unfamiliar with proper handling of treated railcars, it is recommended that they be provided with the necessary information.

Tarpaulin and Bunker Fumigations

وللاسك المعت كالكوالكوا للتاسف الحتني الطائلا المنافية المقامدة

Use of plastic sheeting or tarpaulins to cover commodities is one of the easiest means for providing relatively gas-tight enclosures which are very well suited for furnigation. Poly tarps are penetrated only very slowly by hydrogen phosphide gas, and tight coverings are readily formed from the sheets. The volume of these enclosures may vary widely from a few cubic feet, for example, a furnigation tarpaulin placed over a small stack of bagged commodity, to a plastic bunker storage capable of holding 600,000 bushets of grain or more.

An enclosure suitable for fumigation may be formed by covering bulk or packaged commodity with poly sheeting. The sheets may be tarped together to provide a sufficient width of material to ensure that adequate sealing is obtained. If the flooring upon which the commodity rests is of wood or other porous material, it should be repositioned onto poly prior to covering for furnigation. The plastic covering of the pile may be sealed to the floor using sand or water snakes, by shoveling soil or sand onto the ends of the plastic covering or by other suitable procedures. The poly covering should be reinforced by tape or other means around any sharp corners or edges in the stack so as to reduce the risk of tearing. Thinner poly, about 2 mil., is suitable for most indoor tarp furnigations and for sealing of windows, doors and other openings in structures. However, 4 mil poly or thicker is more suitable for outdoor applications where wind or other mechanical stresses are likely to be encountered

Tablets or pellets may be applied to the tarped stack or bunker storage of bulk commodity through slits in the poly covering. Probing or other means of dosing may be used. Avoid application of large amounts of PH THREE at any one point. The PH THREE should be added below the surface of the commodity if condensation or other source of moisture is likely to form beneath the poly. The stits in the covering should be carefully taped to prevent loss of gas once the dose has been applied. PH THREE tablets and pellets on trays or sheets of kraft paper may be used for the treatment of bagged commodities and processed foods. Care should be taken to see that the poly is not allowed to cover the PH THREE and prevent contact with moist air or confined gas.

Distribution of hydrogen phosphide gas is generally not a problem in the treatment of bagged commodities and processed foods. However, furnigation of larger bunker storages containing bulk commodity will require proper application procedures to obtain adequate results.

Place warning placards at conspicuous locations on the enclosure.

8. Fumigation of Ships

General Information

IMPORTANT --- shipboard, in-transit ship or shiphold furnigation is also governed by U. S. Coast Guard

1. IMPOHTANT — snipocard, in-transit snip or sniphod rumigation is also governed by 0. S. Coast Guard Regulation 46 CFR 147A. Refer to this regulation prior to furnigation.

2. PH THREE tablets or pellets are classified by EPA as Restricted Use Pesticides due to the acute inhalation toxicity of hydrogen phosphide (phosphine PH,) gas. These products are for retail sale to and use only by certified applicators for those uses covered by the applicators certification or persons trained in accordance with the Applicator's Manual working under the direct supervision and in the physical presence of the certified applicator. (Physical presence means on site or on the premises).

Read and follow the label and the Midland Furnigant Co., Inc. Applicator's Manual which contains complete instructions for the safe use of this pesticide.

b. Pre-Voyage Fumigation Procedures

1. Prior to furnigation a vessel for in-transit cargo furnigation, the master of the vessel, or his representative, and the furnigator must determine whether the vessel is suitably designed and configured so as to allow for safe occupancy of the ships crew throughout the duration of the furnigation. If it is determined that the design and configuration of the vessel does not allow safe occupancy by the ships crew throughout the duration of the furnigation, then the vessel will not be furnigated unless all crew members are removed from the vessel. The crew members will not be allowed to reoccupy the vessel until the vessel has been properly aerated and a determination has been made by the master of the vessel and the furnigator, that the vessel is safe for required.

vessel and the funigator that the vessel is safe for occupancy.

2. The person responsible for the funigation must notify the master of the vessel, or his representative, of the requirements relating to personal protection equipment, detection equipment, and that a person qualified in the use of this equipment must accompany the vessel with cargo under furnigation. Emergency procedures, cargo ventilation, periodic monitoring and inspections, and first air measures must be discussed with and understood by the master of the

vessel or his representative.

*Personal Protection equipment means a NIOSH/MSHA approved respirator or gas mask fitted with an approved canister for phosphine. The canister must be approved for use up to 15 ppm, SCBA or its equivalent must be used above 15 ppm or at unknown concentrations.

3. Seal all openings to the cargo hold or tank and lock or otherwise secure all openings, manways, etc., which might be used to enter the hold. The overspace pressure relief system of each tank aboard tankers must be sealed by closing the appropriate valves and sealing the openings into the overspace with gas-tight materials.

4. Placard all entrances to the treated spaces with furnigation warning signs.

5. If the furnigation is not completed and the vessel aerated before the manned vessel leaves port, the person in charge of the vessel shall ensure that at least two units of personal protection equipment and one gas or vapor detection

device, and a person qualified in their operation be on board the vessel during the voyage

During the furnigation or until a manned vessel leaves port or the cargo aerated, the person in charge of the turnigation shall ensure that a qualified person using gas or vapor detection equipment tests spaces adjacent to spaces containing furnigated cargo and all regularly occupied spaces for furnigant leakage of the furnigant is detected, the person in charge of the furnigation shall take action to correct the leakage, or shall inform the master of the vessel, or his representative of the leakage so that corrective action can be taken.

Review with the master of the vessel or his representative, the precautions and procedures for during the

vovage.

Application Procedures for Bulk Dry Cargo Vessels and Tankers

Apply tablets or pellets by scattering uniformly over the commodity surface. Alternatively, tablets or pellets may be deep or shallow-probed into the commodity mass.

2. Immediately after application of the fumigant, close and secure all hatch covers, tank tops, butterworth valves,

d. In Transit Fumigation of Containers Aboard Ships

In transit furnigations of containers on ships is also governed by U. S. Coast Guard Regulation 46 CFR 147A as modified by U. S. Coast Guard Special Permit 52-75. This permit, which must be obtained prior to the furnigation is available from: U. S. Coast Guard, Hazardous Materials Branch, MTH-1, Washington, D. C. 20593-0001.

Application procedures for fumigation of raw commodities or processed foods in containers and other transport vehicles are described in Section 3a.

Precautions and Procedures During Voyage

Using appropriate gas detection equipment, monitor spaces adjacent to areas containing furnigated cargo and all regularly occupied areas for furnigant leakage. If leakage is detected, the area should be evacuated of all personnel ventilated, and action taken to correct the leakage before allowing the area to be occupied.

Do not enter furnigated areas except under emergency conditions. If necessary to enter a furnigated area, appropriate personal protection equipment must be used. Never enter fumigated areas alone. At least one other person, wearing personal protection equipment should be available to assist in case of an emergency.

Precautions and Procedures During Discharge

 If necessary to enter holds prior to discharge, test spaces directly above grain surface for tumigant concentra-tion, using appropriate gas detection and personal safety equipment. Do not allow entry to furnigant areas without personal safety equipment, unless furnigant concentrations are at safe levels, as indicated by a suitable detector.

9. Fumigation of Barges

Barge furnigations are also regulated by U. S. Coast Guard regulation 46 CFR 147A as modified by U. S. Coast Guard Special Permit 2-75. This permit, which must be obtained prior to the furnigation, is available from: U. S. Coast Guard, Hazardous Materials Branch, MTH-1, Washington, D. C. 20593-001

Leaks are a common cause of failures in the treatment of commodities aboard barges. Carefully inspect all hatch covers prior to application of PH THREE and seal, if necessary. Notify consignee if the barge is to be furnigated in transit,

10. Fumigations in Small Sealable Enclosures

Excellent results may be attained in the treatment of small enclosures since it is often possible to control the furnigation and also to make the enclosure virtually gas tight. Take care not to overdose during these furnigations. A single pellet will treat a space from 1.4 to 10 cubic feet. From 6.9 to 50 cubic feet may be furnigated with a single PH THREE tablet.

11. Treatment of Beehives, Supers and other Beekeeping Equipment

PH THREE tablets or pellets may be used for the control of the greater wax moth in stored beehives, supers and other beekeeping equipment and for the destruction of bees, Africanized bees, and diseased bees including those intested with tracheal mites and foulbrood. The recommended dosage for this use is 30-45 tablets, 150-225 pellets.

Fumigations may be performed in chambers at atmospheric pressure, under tarpaulins, etc. by placing the tablets or pellets on trays or in moisture permeable envelopes. Do not add more than 2 tablets or 10 pellets to each envelope. Honey from treated hives or supers may only be used for bee food.

12. Burrowing Pest Control

a. Environmental Hazards. This product is very highly toxic to wildlife. Non-target organisms exposed to phosphine gas in burrows will be killed. Do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water by cleaning equipment or disposal of waste.

b. Directions for Use

Use Restrictions: This product may be applied to underground burrow systems located in non-crop areas, crop areas, or orchards, and occupied by woodchucks, yellowbelly marmots (rockchucks), prairie dogs (except Utah prairie dogs, <u>Cynomys parvidens</u>), Norway rats, roof rats, house mice, ground squirrels, moles, voles, pocket gophers, or chipmunks. All treatments for control of these species in burrows must be made outdoors. Pellets or tablets must be applied directly to underground burrow systems. Do not use within 15 feet (5 meters) of inhabited structures. Do not apply any aluminum phosphide product to any burrow system which might open into or under occupied buildings. Consult Local, State, and Federal Game Authorities to ensure that endangered species do not inhabit the area proposed for treatment. Refer to the "Endangered Species" text helper. Species" text below.

Application Directions: Use application procedures appropriate to the type of burrow system being treated.

For species with open burrow systems, locate all entrances to each burrow system. Seal all but one entrance to the burrow system tightly by shoveling and packing soil and/or sod to completely seal the opening. Insert 2 to 4 tablets or 10 to 20 pellets into each entrance to be treated. Use the lower rates for smaller burrows and/or when soil moisture is high. Use the higher rates for larger burrow systems and when soil moisture is relatively low. Pack the treated entrance with crumpled paper and shovel soil to completely cover the paper. Using crumpled paper will prevent soil from covering the tablets or pellets and slowing down their action. Inspect treated areas 1 or 2 days following treatment for signs of residual activity of target species. Treat all re-opened or previously undiscovered burrows in the manner prescribed above.

For species with closed burrow systems (pocket gophers, and moles in some situations), locate the main underground runway by probing with a smooth-sided rod 12 to 18 inches from a fresh mound. For pocket gophers, begin probing on the flat side of the mound. A sudden reduction in soil resistance to the probe indicates that the main runway has been located. Once the main runway is located, remove the probe and apply 2 to 4 tablets or 10 to 20 pellets through the probe hole. Adjust treatment rate according to the level of soil moisture, using more pellets or tablets if the soil is relatively dry. Do not treat if soil is extremely dry or if there are no signs of recent gopher or mole activity. Make a tight seal to close probe hole by using a clod of soil or a soil plug to cover the hole or by using the heel of your shoe to push soil and/or soil over the surface opening. If the probe hole is more than one inch in diameter, place crumpled paper in the hole before closing it with soil and/or sod. Two days after treatment, check area for residual pest activity by poking holes in main runways of burrow systems. Flag holes and inspect them two days later. Retreat all re-closed systems on both sides of the plug.

d. Endangered Species Considerations

المناتبينية الغفاط كسريره أتفو بالكريث التحلي الشبيا التراسيعي

The use of PH THREE in a manner that may kill or otherwise harm an endangered or threatened species or adversely modify their habitat is a violation of Federal laws. The use of this product is controlled to prevent death or harm to endangered or threatened species that occur in the following counties or elsewhere in their range. Use of this product in the areas listed below are prohibited without first contacting and obtaining permission from the Endangered Species Specialist at the nearest regional offices of the U. S. Fish and Wildlife Service (FWS).

- Areas Inhabited by Endangered or Threatened Species
 Black-footed Ferret States of Arizona, Colorado, Kansas, Montana, Nebraska, New Mexico, North
 Dakota, Oklahoma, South Dakota, Texas, Utah and Wyoming.
 Bjunt-nosed Leopard Lizard Counties of Kern, Kings, Fresno, Madera, Merced and Tulare in the State
- of California.

Desert Tortise — Washington County in the State of Utah.
Eastern Indigo Snake — States of Florida and Georgia.
San Joaquin Kit Fox — Counties of Kern, Kings, Fresno, Merced, Monterey, San Benito, San Luis Obispo. Santa Barbara, Tulare and Ventura in the State of California.

e. Special Local Restrictions

North Carolina: PH THREE tablets or pellets may only be used for control of rats and mice in the State of North Carolina. Use against other burrowing pests is not permitted.

Oklahoma: A special permit for black-tailed prairie dog control by poisoning is required in Oklahoma.

Contact the Oklahoma State Department of Wildlife Conservation to obtain this permit.

Wisconsin: A state permit is required for use of pesticides in Wisconsin to control small mammals, except rats or mice. Please contact your local Department of Natural Resources office for information.

Indiana: Use of PH THREE tablets or pellets for mole control is not legal in the State of Indiana.

Missouri: A state permit is required for use of pesticide in Missouri to control small mammals, except rats and mice. Please contact the Missouri Department of conservation office for information.

Kansas: A special permit for black-tailed prairie dog control by poisoning is required in Kansas. Contact the Kansas Fish and Game Commission to obtain this permit.

California: Use of PH THREE tablets or pellets for chipmunk control is not legal in the State of California.

SECTION 4 PROTECTIVE CLOTHING

Wear dry gloves of cotton or other material if contact with PH THREE tablets or pellets is likely. Wash hands thoroughly after handling aluminum phosphide products. Aerate used gloves and other contaminated clothing in a well ventilated area prior to laundering.

SECTION 5 RESPIRATORY PROTECTION

When Respiratory Protection Must Be Worn

NIOSH/MSHA approved respiratory protection must be worn if worker exposure limits cannot be met through controls (such as forced air ventilation) and/or worker practices. Respiratory protection is required if exposure is likely to exceed the TWA of 0.3 ppm during application, or a 0.3 ppm ceiling at any time afterwards. For example, respiratory protection is required to be worn upon reentry into a partially aerated structure if the hydrogen phosphide concentration is above 0.3 porn. When required, gas concentration measurements for safety purposes may be made using low level detector tubes. See the section on Applicator and Worker Exposure for Monitoring requirements. Information on hydrogen phosphide (phosphine, PH,) detector tubes may be obtained from: Midland Furnigant Co., Inc., 1805 S. 2nd St., Leavenworth, KS 66048.

B. Permissible Gas Concentration Ranges for Respiratory Protection Devices

A NIOSH/MSHA approved, full-faced mask with hydrogen phosphide canister combination may be used at levels up to 15 ppm or to escape from levels up to 1500 ppm. Gas levels above 15 ppm, or in situations where the hydrogen phosphide concentration is unknown, a NIOSH/MSHA approved, self-contained breathing apparatus (SCBA) or its equivalent must be used. The NIOSH/OSHA Pocket Guide, 8085 DHEW/NIOSH 78-210, lists these and other types of approved respirators and the concentration limits at which they may be used.

Requirements for Availability of Respiratory Protection

If PH THREE is to be applied from within the structure to be furnigated, an approved full-face gas mask — phosphine canister combination or self-contained breathing apparatus (SCBA) or its equivalent must be available at the site of application in case it is needed. In addition, SCBA or its equivalent must be available locally, for example, at fire station or rescue if it is not available at the fumigation site.

Respiratory protection need not be available for applications from outside the area to be furnigated such as addition of tablets or pellets to automatic dispensing devices, outdoor applications, etc. if exposures above the

permitted exposure limits will not be encountered.

If monitoring equipment is not available on a farm and application of furnigant cannot be made from outside the structure, an approved canister respirator must be worn during application from within the structure being treated.

SECTION 6 PLACARDING OF FUMIGATED AREAS

The applicator must placard or post all entrances to the structure under furnigation with signs bearing, in English and Spanish:

The signal word DANGER PELIGRO and the SKULL AND CROSSBONES symbols in red.

The statement: "Area and or commodity under furnigation DO NOT ENTER. NO ENTRE."

The statement, "This placard may only be removed after the furnigated area is aerated down to 0.3 ppm. hydrogen prosphide or below. Transfer of incompletely aerated commodity to a new site is permissible provided that the naw storage is placarded if it contains more than 0.3 pcm. Warkers must not be exposed to more than 0.3 ppm. hydrogen phosphide.
4. The date and time that fumigation begins and is completed.

Name of fumigant used.

the state of the s

Name, address and telephone number of the applicator.

All entrances to a furnigated area must be placarded. Where possible, placards should be placed in advance of the furnigation to keep unauthorized persons away. For railroad hopper cars, placards must be place on both sides of the car near the ladders and next to the top hatches into which the fumigant is introduced.

Do not remove placards until the treated commodity is aerated down to 0.3 ppm hydrogen phosphide or less. To determine whether aeration is complete, each fumigated site or vehicle must be monitored and shown to contain 0.3 ppm or less hydrogen phosphide gas in the air space around and, if feasible, in the mass of the commodity. Transfer or incompletely aerated commodity to a new site is permissible. However, the new storage must be placarded if it contains more than 0.3 ppm hydrogen phosphide. Workers who handle incompletely aerated commodity must be informed and appropriate measures taken (i. e., ventilation or respiratory protection) to prevent exposures from exceeding 0.3 ppm hydrogen phosphide.

It is recommended that the persons responsible for removing placards be familiar with physical, chemical and toxicological properties of hydrogen phosphide. They should also be knowledgable in making gas concentration measurements, exposure limits and symptoms and first air treatment for hydrogen phosphide poisoning.

SECTION 7 AERATION OF FUMIGATED COMMODITIES

A. Foods and Feeds

Tolerances for hydrogen phosphide residues have been established at 0.1 ppm for animal feeds and 0.01 ppm for finished foods. To guarantee compliance with these tolerances, it is necessary to aerate these commodities for 48 hours prior to offering to the end use consumer.

B. Tobacco

Tobacco must be aerated for at least three days (72 hours) when furnigated in hogshead and for at least two days (48 hours) when furnigated in other containers. Tobacco furnigated in containers with plastic liners will probably require longer aeration periods to reach 0.3 ppm.

SECTION 8 EXPOSURE

A. Hydrogen Phosphide Exposure Limits

Exposure to hydrogen phosphide may not exceed 0.3 ppm measured as an eight-hour time-weighted average (TWA), for applicators and workers during application. Application is defined as the time period covering the opening of the first containers, applying the appropriate dosage of furnigant and closing up the site to be furnigated. All persons in the treated site and in adjacent indoor areas are covered by its exposure standard.

persons in the treated site and in adjacent indoor areas are covered by its exposure standard.

After application, exposure for any person may not exceed a 0.3 ppm ceiling for hydrogen phosphide. Such exposures may occur if the commodity or space under fumigation leaks, when treated commodity is transferred or handled, if an unaerated or partially aerated space is entered, etc.

B. Application of Fumigant

Depending upon temperature and humidity, PH THREE tablets and pellets release hydrogen phosphide gas slowly upon exposure to moisture from the air. In most cases, this release is slow enough to permit applicators to deposit furnigant in the desired areas and then vacate the premises without significant exposure to the gas. Furnigators must wear approved respiratory protection if exposure is likely to exceed the eight-hour TWA of 0.3 ppm. When required, gas concentration measurements for safety purposes may be made using low level detector tubes. See the write-up below on Industrial Hygiene Monitoring, Information on hydrogen phosphide (phosphine PH₂) detector tubes may be obtained from: Midland Furnigant Co., Inc., 1805 S. 2nd St., Leavenworth, KS 66048.

It is often advisable to use respiratory protection during application of furnigant under hot and humid conditions, particularly when considerable time must be spent inside the structure being treated.

C. Leakage from Fumigated Sites

Hydrogen phosphide is highly mobile and given enough time may penetrate seemingly gas tight materials such as concrete and cinder blocks. Therefore, adjacent, enclosed areas likely to be occupied should be examined to ensure that significant leakage has not occurred. Sealing of the fumigated site and/or air flow into the occupied areas must be sufficient to meet exposure standards.

D. Aeration and Reentry

If the area is to be enfered after furnigation, it must be aerated until the level of hydrogen phosphide gas is 0.3 ppm or below. The area or site must be monitored to ensure that liberation of gas from the treated commodity does not result in the development of unacceptable levels of hydrogen phosphide. Do not allow reentry into treated areas by any persons before this time unless protected by an approved respirator.

E. Handling Unaerated Commodities

Workers must not be exposed to hydrogen phosphide in excess of 0.3 ppm during moving, storage or processing of incompletely aerated commodities.

F. Industrial Hygiene Monitoring

It is recommended that hydrogen phosphide exposures be documented in an operations log or manual for each site and operation where exposure may occur. The purpose of monitoring is to prevent excessive exposures and to determine when and where respiratory protection is required. Once exposures have been adequately characterized, subsequent monitoring is not routinely required. However, spot checks should be made occasionally, especially if conditions change significantly or an unexpected garlic odor is detected. Gas measurements should be made in the workers' breathing zone. Monitoring is not required for outdoor operations.

If monitoring shows that workers are exposed to concentrations in excess of the permitted limits, then engineering controls (such as forced air ventilation) and/or appropriate work practices should be used where possible to reduce exposure to within permitted limits.

There are a number of devices on the market for measurement of hydrogen phosphide gas levels for industrial hygiene purposes. One of these is the hydrogen sampling pump. These devices are reliable, portable, simple to use, do not require extensive training, and provide relatively rapid, inexpensive, and accurate low-level industrial hygiene moni-

SECTION 9 STORAGE INSTRUCTIONS

Store PH THREE under lock and key, in a dry, well-ventilated area away from heat. Post as pesticide storage area. Do not contaminate water, food or feed by storing pesticides in the same areas used to store these commodities.

Do not store in buildings where humans or domestic animals reside. Keep out of reach of children. PH THREE tablets or pellets are supplied in gas tight, resealable aluminum flasks. Do not expose the product to atmospheric moisture any longer than is necessary and seal tightly before returning opened flasks to storage. The shelf life of PH THREE is virtually unlimited as long as the containers are tightly sealed.

SECTION 10 DISPOSAL INSTRUCTIONS

A. General

A. General

1. Do not contaminate water, food or feed by storage or disposal.

2. Unreacted or partialty reacted PH THREE is acutely hazardous. Improper disposal of excess pesticides is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance. For specific instructions, see Section 11 of this manual, Spill and Leak Procedure.

3. Some local and state waste disposal regulations may vary from the following recommendations. Disposal procedures should be reviewed with appropriate authorities to ensure compliance with local regulations. Contact your state Pesticide or Environmental Control Agency or Hazardous Waste Specialist at the nearest EPA regional Office for guidance.

4. Triple rinse flasks and stoppers with water. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by other procedures approved by state and local authorities. Rinsate may be disposed of in a sanitary landfill by pouring it out onto the ground or by other approved procedures. Or, it is permissible to remove lids and expose empty flasks to atmospheric conditions until residue in flasks is reacted, then puncture and dispose of flasks in

expose entity lasks to amospheric conditions that residue it liasks is reacted, went purchase and aspose of liasks in a sanitary landfill or other approved site, or by other procedures approved by State and local authorities.

If property exposed, the residual dust remaining after a furnigation with PH THREE will be a grayish-white powder containing only a small amount of unreacted aluminum phosphide. However, residual dust — so called green dust" — from incompletely exposed PH THREE will require special care.

B. Directions for Disposal of Residual Dust from PH THREE

B. Directions for Disposal of Residual Dust from PH THREE

1. Confinement of partially spent residual dust, as in a closed container, or collection and storage of large quantities of dust may result in a fire hazard. Small amounts of hydrogen phosphide may be given off from unreacted aluminum phosphide, and confinement of the gas may result in a flash.

2. In open areas, small amounts of residual dust, up to about 5 to 8 kg., may be disposed of on site by burial or by spreading over the land surface away from inhabited buildings.

3. Spent residual dust from PH THREE may also be collected and disposed of at a sanitary landfill, incinerator or other approved sites or by other procedures approved by Federal, State or Local authorities. "Green Dust" must be further deactivated before disposal at a landfill.

4. From 2 to 3 kg. (4 to 7 lbs) of spent dust from 2 to 3 flasks of PH THREE may be collected for disposal in a 1 gallon bucket. Larger amounts, up to about one-half case, may be collected in burlap, cotton or other types of porous cloth bags for transportation in an open vehicle to the disposal site. Do not collect dust from more than 7 flasks of tablets or 10 flasks of pellets (about 11 kg. or 25 lbs) in a single bag. Do not pile cloth bags together. Do not use this method for partially spent or "green dust." Caution: Do not collect dust in large drums, dumpsters, plastic bags or other containers where conlinement may occur.

C. Directions for Deactivation of Partially Spent Residual Dust from PH THREE.

1. Partially spent dust may be deactivated prior to ultimate disposal. This is especially true in cases of incomplete exposure which has resulted in so-called "green dust" or following a furnigation which has produced large quantities of partially spent material. "Green dust" must be further deactivated prior to disposal in landfills.

2. Residual dust from PH THREE may be deactivated as follows using the "Wet Method."

a. Deactivating solution is prepared by adding the appropriate amount of low-sudsing detergent or surface active agent to water in a drum or other suitable container. A 2% solution of detergent is suggested. The container should be filled with deactivating solution to within a few inches of the top.

b. Residual dust is poured slowly into deactivating solution and stirred so as to thoroughly wet all of the particles. This should be done in the open air and not in the furnigated structure. Dust from PH THREE tablets or pellets should be mixed into no less than 10 gallons of water-detergent solution for each case of material used. Wear appropriate respiratory protection during wet deactivation of partially spent dust.

c. Dispose of the deactivated dust-water suspension, with or without preliminary decanting, at a sanitary landfill or other suitable site approved by local authorities. Where permissible, the slurry may be poured out onto the ground. If the slurry has been held for 36 hours or more, it may be poured into a storm sewer.

d. Caution: Respiratory protection is required during wet deactivation of partially spent material. Do not cover the

d. Caution: Respiratory protection is required during wet deactivation of partially spent material. Do not cover the container at any time. Do not dispose of dust in a toilet. Do not allow quantities of dry residual dust from PH THREE to be collected or stored without deactivation.

3. Residual dust from PH THREE may also be deactivated as follows using the "Dry Method."

a. Extension of the furnigation period is the simplest method for further deactivation of "green dust" or partially spent dust

prior to ultimate disposal.

b. Small amounts of partially spent dust, from 2 to 3 kg. (4 to 7 lbs) may be further deactivated by storage in a 1 gallon bucket. Larger amounts of dust (about 11 kg. or 25 lbs) may be held for deactivation in porous cloth bags (burlap, cotton, etc.) Caution: Transport these bags in open vehicles, do not pile up bags and do not use this method for "green dust."

SECTION 11 SPILL AND LEAK PROCEDURE

A. General Precautions and Directions

A spill other than incidental to application or normal handling, may produce high levels of gas and, therefore, attending personnel must wear SCBA or its equivalent when the concentration of hydrogen phosphide gas is unknown. Other NIOSH/MSHA approved respiratory protection may be worn if the concentration is known. Do not use water at any time to clean up a spill of PH-THREE. Water in contact with unreacted tablets or pellets will greatly accelerate the production of hydrogen phosphide gas which could result in a toxic and/or fire hazard. Wear cotton gloves or other material when handling aluminum phosphide.

Return all intact aluminum flasks to fiberboard cases or other packaging which has been suitably constructed and marked according to DOT regulations. Notify consignee and shipper of damaged cases.

If aluminum flasks have been punctured or damaged so as to leak, the container may be temporarily repaired with aluminum tape or the PH THREE may be transferred from the damaged flask to a sound metal container which should be sealed and properly labeled as aluminum phosphide. Transport the damaged containers to an area suitable for pesticide storage for inspection.

Further instructions and recommendations may be obtained from Midland Furnigant Co., Inc.

If a spill has occurred which is only a few minutes old, collect the tablets or pellets and place them back into the original flasks, if they are intact, and stopper tightly. Place the collected tablets or pellets in a sound metal container if the

original flasks are damaged. Caution: these flasks may flash upon opening at some later time.

If the age of the spill is unknown or if the tablets or pellets have been contaminated with soil, debris, water, etc. gather up the spillage and place it into small open bucket having a capacity no larger than about 1 gallon. Do not add more than one flask of spilled material, 1 to 5 kg. (2 to 3 lbs) to the bucket. If on-site, wet deactivation is not feasible, these containers should be transported in open vehicles to a suitable area. Wet deactivation may then be carried out as described in Section 10. Alternatively, small amounts of spillage from 4 to 5 flasks (4 to 8 kg.) (9 to 18 lbs) may be spread out in an open area away from inhabited buildings, and deactivated by atmospheric moisture.

B. Directions for Deactivation by the Wet Method

If the contaminated material is not to be held until completely reacted by exposure to atmospheric moisture, deactivate the product by the Wet Method as follows:

Deactivating solution is prepared by adding the appropriate amount of low sudsing detergent or surface active agent to water in a drum or other suitable container. A 2% solution of 4 cups in 30 gallons is suggested. The container should be filled.

with deactivation solution to within a few inches of the top.

- The tablets or pelfets are poured slowly into the deactivating solution and stirred so as to thoroughly wet all of the PH THREE. This should be done in the open air. PH THREE tablets or pellets should be mixed with no less than about 15 gallons of water-detergent solution for each case of spent material. Wear appropriate respiratory protection during wet deactivation.
- 3. Allow the mixture to stand, with occasional stirring, for about 36 hours. The resultant sturry will then be safe to dispose
- Dispose of the slurry of deactivated material, with or without preliminary decanting, at a sanitary landfill or other suitable site approved by local authorities. Where permissible, this slurry may be poured into a storm sewer or out onto the ground.
 Caution: Respiratory protection is required during wet deactivation of unexposed PH THREE. Never place
- pellets, tablets, or bags in a closed container such as a dumpster, sealed drum, plastic bag, etc. as flammable concentrations and a flash of hydrogen phosphide gas is likely to develop.

 6. The EPA has determined that proper disposal of aluminum phosphide will cause no unreasonable effects to the environ-
- ment

FOR ASSISTANCE, CONTACT:

Midland Fumigant Co., Inc. 1805 S. 2nd St. Leavenworth, KS 66048 (800) 332-3930 (913) 651-3900

PH THREE Pellets EPA Reg. No. 30574 -8 PH THREE Tablets EPA Reg. No. 30574-7