



# PEN-KOTE Copper Naphthenate

**PRESERVATIVE  
FOR WOOD CANVAS ROPE**

**ANALYSIS**  
**ACTIVE INGREDIENT**  
Copper Naphthenate 10%  
**INERT INGREDIENT 90%**  
Copper as Metallic 1%

An air-drying, copper base preservative for wood, fabric, and rope. Will arrest the action of decay, rot fungi, termites and other wood infesting insects. Estimated coverage from 200 to 450 square feet. The natural light green color is not permanent.

### DIRECTIONS

Use as it comes from the package. Do not thin. Remove all previous paint coating and cut away rotten wood.

FOR BRUSH OR SPRAY: Apply liberally using as many coats as necessary to secure penetration desired. The degree of protection afforded is dependent upon the amount of preservative that penetrates into the material. At least 2 coats should be given by brush or spray to all wood that comes into contact with the ground.

DIP: Length of time for soaking dependent upon thickness of wood to be treated as well as type of wood. A minimum of 30 minutes suggested for one inch thickness or less. Overnight soaking is suggested in treating heavier timbers.

FOR CANVAS OR ROPE: Saturate thoroughly. Let dry before using.

SURFACE TO BE PAINTED LATER: Allow 48 hours before painting. On white or light tints, there may be slight discoloration on first coat but will disappear on second coat if wood is thoroughly dry.

**CAUTION** KEEP AWAY FROM FIRE. USE IN WELL VENTILATED PLACE.  
KEEP OUT OF REACH OF CHILDREN. HARMFUL IF SWALLOWED.  
FLASH POINT 110°F. DO NOT USE, POUR, SPILL, OR STORE NEAR HEAVY OILS OR FLAMMABLES.  
DO NOT REUSE CONTAINER, DESTROY WHEN EMPTY.

This product is toxic to fish. Keep out of lakes, streams, or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

**PEN-KOTE PAINT CO. ■ PANAMA, FLORIDA 32505**  
**EPA REG. NO. 31259-1**