

AQUATREAT DNM-30



PRECAUTIONARY STATEMENTS

Hazardous to Humans and
Domestic Animals.

WARNING

Causes eye and skin irritation. Do not get in eyes, on skin or on clothing. Wear goggles or face shield, rubber gloves and protective clothing (hat, long sleeve shirt, long pants and boots) when handling. Harmful if swallowed. Avoid contamination of food and feedstuffs.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not apply in marine and/or estuarine oil fields. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not discharge treated effluent into lakes, streams, ponds or public waters unless in accordance with a NPDES permit. For guidance contact your Regional Office of the Environmental Protection Agency.

ACTIVE INGREDIENTS	30%
Sodium Dimethyldithiocarbamate	15%
Nabam (Disodium Ethylene Bis-dithiocarbamate)	15%
INERT INGREDIENTS	70%
TOTAL	100%

DIRECTIONS FOR USE GENERAL CLASSIFICATION

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

INDUSTRIAL RECIRCULATING WATER COOLING TOWER AND EVAPORATIVE CONDENSERS

Dosage for industrial recirculating water cooling tower or evaporative condensers will depend on the condition of the system prior to treatment initiation. Systems which are heavily contaminated should be cleaned first. Apply AQUATREAT DNM-30 to the cleaned system or when growth is first noticed, according to the following schedule:

Initial Dose: Apply 13.06-43.60 ounces of product per each 1000 gallons of water in the system (120-400 ppm). This dose may be repeated once, twice or three times weekly or as required to control the growth of slime-forming organisms.

Subsequent Dose: When microbial control is evident add 2.18-4.36 fluid ounces of AQUATREAT DNM-30 per 1000 gallons of water (20-40 ppm) in the system every three days or as needed.

AIR WASHERS

In treating air washer systems preclean by introducing a suitable detergent solution into the system and allow air washer to run with fan off for two hours. Check all nozzles and manually clean those that are plugged.

Feeding: AQUATREAT DNM-30 may be fed directly from the drum or diluted with water and fed by any suitable feed system. AQUATREAT DNM-30 should be dosed directly into the sump or basin or any other location where good distribution can be assured.

Initial Dose: Apply 13.06-21.80 ounces of product per each 1000 gallons of water in the system (120-200 ppm). This dose may be repeated once, twice or three times weekly or as required to control the growth of slime-forming organisms.

Subsequent Dose: When microbial control is evident add 2.18-4.36 fluid ounces of AQUATREAT DNM-30 per 1000 gallons of water (20-40 ppm) in the system every three days or as needed.

HYDROCARBON FLUIDS STORAGE

AQUATREAT DNM-30 is a highly effective fungicide and bactericide for use in fuel oil (No. 2 oil, intermediate fuel oil and No. 6 oil), lubricating oil and hydraulic fluids.

AQUATREAT DNM-30 is applied initially at a level of 0.1 liters per ton of contaminated liquid (100 ppm by weight). Subsequent dosages may be decreased once the contaminants have been brought under control.

BEST AVAILABLE COPY

KEEP OUT OF REACH OF CHILDREN

WARNING

STATEMENT OF PRACTICAL TREATMENT

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse.

If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Call a physician immediately.

See Side Panel For
Additional Precautionary Statements.



Manufactured by:

ALCO Chemical Corporation

909 Mueller Drive

Chattanooga, Tennessee 37406

Phone: 615-629-1405

EPA Establishment No. 31910-1N-1

EPA Registration No. 31910-2

Net Contents: Liquid

See Markings on Top of Drum for Net Weight

STORAGE AND DISPOSAL

1. PROHIBITIONS

Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

2. PESTICIDE DISPOSAL

Pesticide, spray mixture, or rinse water that cannot be used according to label instructions must be disposed of according to Federal or approved state procedures under Subtitle C of the Resource Conservation and Recovery Act.

3. CONTAINER DISPOSAL

(a) Reseal container and offer for reconditioning, or

(b) Metal Containers: Triple rinse (or equivalent). Then offer for recycling or reconditioning or puncture and dispose of in a sanitary landfill or by other approved state and local procedures.

Plastic Containers: Triple rinse (or equivalent). Then offer for recycling or reconditioning or puncture and dispose of in a sanitary landfill, or incineration or if allowed by state and local authorities, by burning. If burned, stay out of smoke.

4. GENERAL

Consult federal, state or local disposal authorities for approved alternative procedures.

AQUATREAT DNM-30 is a highly effective bactericide and fungicide for use in controlling the growth of bacteria and fungi found in paper mills, drilling fluids, secondary and tertiary petroleum recovery, sugar beet flume water transporting and washing systems, beet and cane sugar mills, and hydrocarbon fluids storage. AQUATREAT DNM-30, in addition to being a bactericide and fungicide is a highly effective algicide for use in controlling the growth of algae as well as bacteria and fungi found in industrial recirculating water cooling towers, evaporative condensers, and air washers.



DRILLING FLUIDS

AQUATREAT DNM-30 is a highly effective microbiocide for use in controlling growth of fungi and bacteria found in water based drilling muds. It is especially useful in muds containing starches, Xanthanate gums, and wood sugars. The uncontrolled growth of these fungi and bacteria can cause increased corrosion, undesirable odors, and degradation of the drilling mud, especially fluid loss properties.

AQUATREAT DNM-30 is used at the rate of 1 to 5 gallons per 100 bbl. of mud. (0.02% to 0.1%). It can be used directly from the shipping container or pre-diluted with water. It can be put in through the mud hopper or added to the pump suction.

SECONDARY AND TERTIARY PETROLEUM RECOVERY

AQUATREAT DNM-30 is a highly effective microbiocide for use in controlling the growth of fungi and bacteria found in secondary and tertiary petroleum recovery waterflood systems.

AQUATREAT DNM-30 can be injected directly from the shipping container. It should be thoroughly mixed into the produced water, fresh or salt water or commingled water or the secondary or tertiary oil recovery waterflood systems for effective microorganism control. It may also be diluted with water for injection.

AQUATREAT DNM-30 is used at the rate of 1 pint per 100 bbl. of water for growth inhibition of *Bacillus Cereus* and *Desulfovibrio desulfuricans* and 1.1 to 1.8 gallons per 100 bbl. of water for heterotrophic bacteria including *Pseudomonas*. It is also effective against many fungi such as *Aspergillus*, *Penicillium* and *Trichoderma* at the 1 pint per 100 bbl. of water.

PAPER MILLS

Dosage will vary from 0.1 to 2.0 pounds (0.04 to 0.81 quarts) of AQUATREAT DNM-30 per ton of finished paper depending on the type of stock, complexity of the system, quality of raw water, and type and degree of contamination.

Feeding: AQUATREAT DNM-30 may be drip fed continuously from the drum or fed by suitable chemical pumps such as adjustable proportioning types; variable speed, positive displacement types or by the reciprocating type. This product should be fed as early as possible in the system at such points including the hydropulper, machine chest or broke system.

AQUATREAT DNM-30 can be used to control slime on machines which can make paper and paperboard for use in food packaging. AQUATREAT DNM-30 complies with Title 21 Code of Federal Regulations section 176.100 of the Food Additive Regulations and may be used under conditions specified in the regulations.

BEET SUGAR MILLS

AQUATREAT DNM-30 should be fed directly into the raw juice during sugar extraction of beets to keep equipment free of bacterial slime deposits. It is to be used at the rate of 10-20 ppm of raw beets sliced, and fed continuously into the pulp press water tank with a metering pump. The maximum rate to be fed is 20 ppm. Refer to composite table 1 for the proper dosage in milliliters and ounces of AQUATREAT DNM-30 to be used per minute.

COMPOSITE TABLE 1
Rate of Feed of AQUATREAT DNM-30

SHORT TONS OF CANE GROUND OR RAW BEETS SLICED PER DAY	10 ppm		20 ppm	
	ml/min	oz/min	ml/min	oz/min
1,000	5.5	0.186	11	0.372
2,000	11.0	0.372	22	0.744
3,000	16.5	0.558	33	1.115
4,000	22.0	0.744	44	1.487
5,000	27.5	0.930	55	1.859
6,000	33.0	1.115	66	2.231
7,000	38.5	1.301	77	2.603
8,000	44.0	1.487	88	2.974
9,000	49.5	1.673	99	3.347
10,000	55.0	1.859	110	3.718

This product complies with Title 21 Code of Federal Regulations Section 173.320 (Chemicals used for the Control of Microorganisms in Cane and Beet Sugar Mills) of the Food Additive Regulations and may be used under conditions specified in the regulations.

CANE SUGAR MILLS

AQUATREAT DNM-30 is a liquid which should be fed directly into the cane juice so that the treated juice circulates to all parts of the mill tandem. The point or points of addition will depend on mill design. Frequently the dosage will be split between the crusher juice and juice from the last mill. The best addition point is to the juice which is circulated back to the crusher from the first mill. Do not add this product to the maceration water.

AQUATREAT DNM-30 should be fed continuously at the rate of 10-20 parts of product per million parts of cane ground per day. 10 ppm of product is the standard dosage. This may be raised up to a maximum of 20 ppm, if necessary. Conditions warranting, some increase would be warranted when grinding cane damaged through freezing, poor weather or delays between cutting and grinding. See feeding directions which follow.

Proper food of AQUATREAT DNM-30 is best obtained through the use of a chemical feed pump such as the adjustable proportioning type; the variable speed, positive displacement type, or the reciprocating type. The required dosage will depend on the average daily rate of cane ground. Refer to composite table 1 for the proper dosage in milliliters and ounces of AQUATREAT DNM-30 to be used per minute.

Do not exceed feed rate of 4 gallons (19.2 pounds) of product per 1000 short tons of cane ground per twenty-four hours.

The use of AQUATREAT DNM-30 does not replace good housekeeping. This should include regular cleaning at least once per shift. Regular hosing of mill bagacillo conveyors, and screens with hot water and steam is essential for maintaining efficient control of microbiological slime and surross losses.

SUGAR BEETS AND

AQUATREAT DNM-30 is a highly effective microbiocide for use in the degradation of sugar beets by porting and washing process.

AQUATREAT DNM-30 is applied in the total volume of water in the per shift basis. Thereafter, shift. The concentration may decrease in pH or increase in

To calculate the amount of AQUATREAT DNM-30 to use for volume of gallons. To calculate the amount of AQUATREAT DNM-30 to use for volume of gallons. To calculate the amount of AQUATREAT DNM-30 to use for volume of gallons.

Millions of
Gallons
In System

0.1	1-1/2
0.5	7
1.0	1 gal.
5.0	8 gal.

For Che
Spill, Leak, Fire
Call CHEM
1-8

Other makes no warranty for this product other than that it is safe for the handling of it. Use contrary to label instructions.

BEST AVAILABLE