

PM 31

31910-11

194

Please read instructions on reverse before completing form.

Form Approved, OMB No. 2070-0080, EPA Form 7000-11-30-83



United States Environmental Protection Agency
Office of Pesticide Programs (H7505C)
Washington, DC 20460

Application for Pesticide:

Registration
 Amendment
 Other

Registration Number
15085

Section I

1. Company/Product Number 31910-11	2. EPA Product Manager Walter Francis	3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Other
4. Company/Product (Name) AQUATREAT DNM-9	PM# 31	
5. Name and Address of Applicant (Include ZIP Code) Alco Chemical Division National Starch & Chemical Company 909 Mueller Drive P.O. Box 5401 Chattanooga, TN 37406 <input type="checkbox"/> Check if this is a new address	6. Expedited Review. In accordance with FIFRA Section 2(b)(1), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____	

Section II

<input type="checkbox"/> Amendment - Explain below	<input type="checkbox"/> Final printed labels in response to Agency letter dated _____
<input type="checkbox"/> Resubmission in response to Agency letter dated _____	<input type="checkbox"/> "Me Too" Application.
<input checked="" type="checkbox"/> Notification - Explain below.	<input type="checkbox"/> Other - explain below.

Explanation: Use additional page(s) if necessary. (For section I and Section II)

The purpose of this Notification is to amend the Environmental Hazards statement to comply with EPA PR Notice 93-10 regarding Effluent Discharge Labeling Statements.

BEST AVAILABLE COPY

Section III

1. Material This Product Will Be Packaged In:				2. Type of Container	
Child-Resistant Packaging <input type="checkbox"/> Yes* <input type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No		<input type="checkbox"/> Metal	<input type="checkbox"/> Plastic
	If "Yes," Unit Package wgt.	No. per container	If "Yes," Package wgt.	No. per container	<input type="checkbox"/> Glass
					<input type="checkbox"/> Paper
					<input type="checkbox"/> Other (Specify) _____
3. Location of Net Contents Information <input type="checkbox"/> Label <input type="checkbox"/> Container		4. Size(s) of Retail Container		5. Location of Label Directions <input type="checkbox"/> On Label <input type="checkbox"/> On Labeling accompanying product	
6. Manner In Which Label Is Affixed To Product <input type="checkbox"/> Lithograph <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled				<input type="checkbox"/> Other (_____)	

Section IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)

Name Chester J. Kawa, Jr.	Title Commercial Development Manager	Telephone No. (include Area Code) 615/629-1405
------------------------------	-----------------------------------------	---------------------------------------------------

Certification

I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.

6. Date Application Received (Stamped)

2. Signature 	3. Title Commercial Development Manager
4. Typed Name Chester J. Kawa, Jr.	5. Date XX/XX/XX 9/25/95

294

AFTER

AQUATREAT® DNM-9

PRECAUTIONARY STATEMENTS

Hazards to Humans and Domestic Animals

WARNING

Causes eye and skin irritation. Do not get in eyes, on skin or on clothing. All industrial workers applying this product must wear coveralls over a long-sleeved shirt and long pants, shoes, socks, and chemical-resistant gloves. During dilution, a chemical-resistant apron and goggles or face shield must also be worn. Harmful if swallowed. Avoid contamination of food and feedstuffs.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not apply (or use) in estuarine oil fields where drilling fluids (muds) are discharged in the surface water. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

AQUATREAT DNM-9 is a highly effective bactericide and fungicide for use in controlling the growth of bacteria and fungi in industrial recirculating water cooling towers, air washers, evaporative condensers, pulp and paper mills, drilling fluids, secondary and tertiary petroleum recovery, and cane and beet sugar mills.

AQUATREAT DNM-9 in addition to being a bactericide and fungicide, is a highly effective algaecide for use in controlling the growth of algae as well as bacteria and fungi found in industrial recirculating water cooling towers, evaporative condensers, and air washers.

STORAGE AND DISPOSAL

1. PROHIBITIONS

Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

2. PESTICIDE DISPOSAL

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

3. CONTAINER DISPOSAL

(a) Reseal container and offer for reconditioning, or

(b) **Metal Containers:** Triple rinse (or equivalent).

Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by other approved state and local procedures.

Plastic Containers: Triple rinse (or equivalent).

Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

4. GENERAL

Consult federal, state or local disposal authorities for approved alternative procedures.

ACTIVE INGREDIENTS

Sodium Dimethyldithiocarbamate 4.5%
Nabam (Disodium Ethylene
Bis-dithiocarbamate) 4.5%

INERT INGREDIENTS 91.0%

TOTAL 100.0%

*It is a violat
manner inc*

*This produc
or to formul
crop.*

KEEP OUT OF REACH OF CHILDREN

WARNING

STATEMENT OF PRACTICAL TREATMENT

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse.

If swallowed, drink promptly a large quantity of egg whites, gelatin solution or if these are not available, drink large quantities of water. Call a physician immediately.

See Side Panel For
Additional Precautionary Statements.

INDUSTRI EVA

Dosages for
or evaporate
the system
are heavily
AQUATRE
growth is f
schedule:


Initial Dose
1000 gallons
may be req
or as requ
organisms.

Subsequen
acid 7.27 to
per 1000 ga
every three

In treating a
suitable det
washer to r
nozzles and
product as s

Feeding
AQUATRE
or diluted w
AQUATRE
sump or be
tribution car

AQUATRE
for use in
found in wa
in muds co
wood sugar
bacteria ca
odors, and
loss proper



Manufactured by:


ALCO CHEMICAL DIVISION

National Starch and Chemical Company

909 Mueller Dr. • P.O. Box 5401 • Chattanooga, TN 37406
423-629-1405
FAX 423-698-8723 • TLX 755002

E.P.A. Establishment No. 31910-TN-1 E.P.A. Registration No. 31910-11
Net Contents: Liquid
See Markings on Top of Drum for Net Weight

Cooling Towers and Air Washers



Drilling Fluids



374
Secondary

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

This product must not be used on any food or field crop or to formulate any product for use on any food or field crop.

AQUATREAT DNM-9 is used at the rate 3.7 to 18.6 gallons per 100 bbl. of mud. (0.067% to 0.33%). It can be used directly from the shipping container or pre-diluted with water. It can be put in through the mud hopper or added to the pump suction.

SECONDARY AND TERTIARY PETROLEUM RECOVERY

AQUATREAT DNM-9 is a highly effective microbiocide for use in controlling the growth of fungi and bacteria found in secondary and tertiary petroleum recovery waterflood systems.

AQUATREAT DNM-9 can be injected directly from the shipping container. It should be thoroughly mixed into the produced water, fresh or salt water or commingled water or the secondary or tertiary oil recovery waterflood systems for effective microorganism control. It may also be diluted with water for injection.

AQUATREAT DNM-9 is used at the rate of 3.3 pints per 100 bbl. of water for growth inhibition of *Bacillus Cereus* and *Desulfovibrio desulfuricans* and 3.7 to 6.2 gallons per 100 bbl. of water for heterotropic bacteria including *Pseudomonas*. It is also effective against many fungi such as *Aspergillus*, *Penicillium* and *Trichoderma* at the 3.3 pints per 100 bbl. of water.

INDUSTRIAL RECIRCULATING WATER COOLING TOWER AND EVAPORATIVE CONDENSERS

Dosages for industrial recirculating water cooling towers or evaporative condensers will depend on the condition of the system prior to treatment initiation. Systems which are heavily contaminated should be cleaned first. Apply AQUATREAT DNM-9 to the cleaned system or when growth is first noticed, according to the following schedule:

Initial Dose: Apply 43.53 ounces of product per each 1000 gallons of water in the system (400 ppm). This dose may be repeated once, twice or three times weekly or as required to control the growth of slime-forming organisms.

Subsequent Dose: When microbial control is evident add 7.27 to 14.33 fluid ounces of AQUATREAT DNM-9 per 1000 gallons of water (66.7-133.3 ppm) in the system every three days or as needed.

AIR WASHERS

In treating air washer systems preclean by introducing a suitable detergent solution into the system and allow air washer to run with fan off for two hours. Flush. Check all nozzles and manually clean those that are plugged. Add product as specified under dosages for Cooling Towers.

Feeding

AQUATREAT DNM-9 may be fed directly from the drum or diluted with water and fed by any suitable feed system. AQUATREAT DNM-9 should be dosed directly into the sump or basin or any other location where good distribution can be assured.

DRILLING FLUIDS

AQUATREAT DNM-9 is a highly effective microbiocide for use in controlling the growth of fungi and bacteria found in water based drilling muds. It is especially useful in controlling growing starches, Xanthanate gums, and wood sugars. The uncontrolled growth of these fungi and bacteria can cause increased corrosion, undesirable odors, and degradation of the drilling mud, especially fluid loss properties.

PAPER MILLS

Dosage will vary from 0.33 to 6.67 pounds (0.13 to 2.70 quarts) of AQUATREAT DNM-9 per ton of finished paper depending on the type of stock, complexity of the system, quality of raw water, and type and degree of contamination

Feeding

AQUATREAT DNM-9 may be drip fed continuously from the drum or fed by suitable chemical pumps such as adjustable proportioning types; variable speed, positive displacement types; or by the reciprocating type. This product should be fed as early as possible in the system at such points including the hydropulper, machine chest or broke system.


AQUATREAT DNM-9 can be used to control slime on machines which can make paper and paperboard for use in food packaging.

BEET SUGAR MILLS

AQUATREAT DNM-9 should be fed directly into the raw juice during sugar extraction of beets to keep equipment free of bacterial slime deposits. It is to be used at the rate of 33.3-66.7 ppm of raw beets sliced, and fed continuously into the pulp press water tank with a metering pump. The maximum rate to be fed is 66.7 ppm. Refer to composite table 1 for the proper dosage in milliliters and ounces of AQUATREAT DNM-9 to be used per minute.

BEST AVAILABLE COPY

Secondary and Tertiary Oil Recovery



Pulp & Paper



Sugar



CANE SUGAR MILLS

AQUATREAT DNM-9 is a liquid which should be fed directly into the cane juice so that the treated juice circulates to all parts of the mill tandem. The point or points of addition will depend on mill design. Frequently the dosage will be split between the crusher juice and juice from the last mill. The best addition point is to the juice which is circulated back to the crusher from the first mill. Do not add this product to the maceration water.

AQUATREAT DNM-9 should be fed continuously at the rate of 33.3-66.7 parts of product per million parts of cane ground per day. 33.3 ppm. of product is the standard dosage. This may be raised up to a maximum of 66.7 ppm, if necessary. Conditions warranting, some increase would be warranted when grinding cane damaged through freezing, poor weather or delays between cutting and grinding. See feeding directions which follow.

Proper feed of **AQUATREAT DNM-9** is best obtained through the use of a chemical feed pump such as the adjustable proportioning type; the variable speed, positive displacement type; or the reciprocating type. The required dosage will depend on the average daily rate of cane ground. Refer to composite table 1 for the proper dosage in milliliters and ounces of **AQUATREAT DNM-9** to be used per minute.

Do not exceed feed rate of 15 gallons (130.7 pounds) of product per 1000 short tons of cane ground per twenty-four hours.

The use of **AQUATREAT DNM-9** does not replace good housekeeping. This should include regular cleaning at least once per shift. Regular hosing of mills bagacillo conveyors, and screens with hot water and steam is essential for maintaining efficient control of microbiological slime and sucrose losses.

COMPOSITE TABLE 1

SHORT TONS OF CANE GROUND OR RAW BEETS SLICED PER DAY	RATE OF FEED OF AQUATREAT DNM-9			
	33.3 ppm		66.7 ppm	
	ml/min	oz/min	ml/min	oz/min
1,000	18.3	0.620	36.7	1.240
2,000	36.7	1.240	73.3	2.480
3,000	55.0	1.860	109.9	3.716
4,000	73.3	2.480	146.7	4.956
5,000	91.7	3.100	183.3	6.196
6,000	110.0	3.716	220.0	7.436
7,000	128.3	4.336	256.6	8.676
8,000	146.7	4.956	293.3	9.912
9,000	165.0	5.576	330.0	11.152
10,000	183.3	6.196	366.6	12.392

**For Chemical Emergency
Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC — Day or Night
1-800-424-9300**

Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on label. Buyer assumes all risk of use and or handling of material, when such use and/or handling is contrary to label instructions.

BEST AVAILABLE COPY