

AQUATREAT® DNM-360**ACTIVE INGREDIENTS**

Dibam (Sodium	
Dimethyldithiocarbamate)....	18%
Nabam (Disodium Ethylene	
Bis-dithiocarbamate).....	18%
INERT INGREDIENTS.....	64%
TOTAL.....	100%

E.P.A. Establishment No. 31910-TN-1

E.P.A. Registration No. 31910-12

Manufactured by:

909 Mueller Avenue – Chattanooga, TN 37406

Phone 423-629-1405

Fax 423-698-8723

Net Contents: Liquid Measure

TO See Markings on Top of Drum for Net Weight**KEEP OUT OF REACH OF CHILDREN****WARNING****FIRST AID**

IF SWALLOWED	-Call poison control center or doctor immediately for treatment advice. -Have person sip a glass of water if able to swallow. -Do not induce vomiting unless told to do so by the poison control center or doctor. -Do not give anything by mouth to an unconscious person.
IF IN EYES	-Hold eye open and rinse slowly and gently with water for 15-20 minutes. -Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. -Call a poison control center or doctor for treatment advice.
IF ON SKIN OR ON CLOTHES	-Take off contaminated clothing. -Rinse skin immediately with plenty of water for 15-20 minutes. -call a poison control center or doctor for treatment advice.

HOT LINE NUMBER

1. In case of emergency call toll free number 1-888-456-6218.
2. Have the product container or label with you when calling a poison control center or doctor or going for treatment.

PRECAUTIONARY STATEMENTS**HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

Harmful if swallowed. Harmful if absorbed through skin. Causes moderate eye irritation. Avoid contact with skin, eyes, or clothing.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

All industrial workers applying this product must wear coveralls over a long-sleeved shirt and long pants, shoes, socks, and chemical-resistant gloves. During dilution, a chemical-resistant apron and goggles or face shield must also be worn.

USER SAFETY REQUIREMENTS

Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

ENGINEERING CONTROLS

This product must be loaded and transferred only using a metering-pump system or a closed loading/application system for the following uses: industrial recirculating water cooling tower and evaporative condensers, air washers, drilling fluids, secondary and tertiary petroleum recovery, paper mills, beet sugar mills, and cane sugar mills. Open pouring is prohibited.

USER SAFETY RECOMMENDATIONS

Users should wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet.

Users should remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing.

Users should remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing.

ACCEPTED

APR 12 2005

Under the Federal Insecticide, Fungicide, and
Rodenticide Act as amended, for the
pesticide, registered under
EPA Reg. No. 31910-12

Under the Federal Insecticide, Fungicide, and
Rodenticide Act as amended, for the
pesticide, registered under
EPA Reg. No. 31910-12

Users should wear protective clothing and equipment to avoid contact with the product. Contact with the product can cause increased corrosion, undesirable odors, and degradation of the drilling mud, especially fluid loss properties.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not apply (or use) in estuarine oil fields where drilling fluids (muds) are discharged in the surface water. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

This product must not be used on any food or field crop or to formulate any product for use on any food or field crop.

STORAGE AND DISPOSAL

1. PROHIBITIONS

Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

2. STORAGE

Keep from freezing. Do not store below 32°F.

3. PESTICIDE DISPOSAL

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.


4. CONTAINER DISPOSAL

(a) Reseal container and offer for reconditioning, or
(b) **Metal Containers:** Triple rinse (or equivalent). Puncture and dispose of in a sanitary landfill or by other approved state and local procedures.

Plastic Containers: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

5. GENERAL

Consult federal, state or local disposal authorities for approved alternative procedures.



General Information (non-site-specific)

AQUATREAT DNM-360 is a highly effective bactericide and fungicide for use in controlling the growth of bacteria and fungi in industrial recirculating water cooling towers, air washers, evaporative condensers, pulp and paper mills, drilling fluids, secondary and tertiary petroleum recovery, and cane and beet sugar mills.

AQUATREAT DNM-360 in addition to being a bactericide and fungicide, is a highly effective algaecide for use in controlling the growth of algae as well as bacteria and fungi found in industrial recirculating water cooling towers, evaporative condensers, and air washers.

General Precautions and Restrictions

Do not apply this product in a way that will contact worker or other persons. Avoid contamination of food and feedstuffs.

APPLICATION INSTRUCTIONS (site-specific)

INDUSTRIAL RECIRCULATING WATER COOLING TOWER AND EVAPORATIVE CONDENSERS

Dosages for industrial recirculating water cooling towers or evaporative condensers will depend on the condition of the system prior to treatment initiation. Systems which are heavily contaminated should be cleaned first. Apply **AQUATREAT DNM-360** to the cleaned system or when growth is first noticed, according to the following schedule:

Initial Dose: Apply 10.88 ounces of product per each 1000 gallons of water in the system (100 ppm). This dose may be repeated once, twice or three times weekly or as required to control the growth of slime-forming organisms.

Subsequent Dose: When microbial control is evident add 1.82 to 3.63 fluid ounces of **AQUATREAT DNM-360** per 1000 gallons of water (16.7-33.3 ppm) in the system every three days or as needed.

AIR WASHERS

In treating air washer systems preclean by introducing a suitable detergent solution into the system and allow air washer to run with fan off for two hours. Flush. Check all nozzles and manually clean those that are plugged. Add product as specified under dosages for Cooling Towers.

Feeding

AQUATREAT DNM-360 may be fed directly from the drum or diluted with water and fed by any suitable feed system. **AQUATREAT DNM-360** should be dosed directly into the sump or basin or any other location where good distribution can be assured.

DRILLING FLUIDS

AQUATREAT DNM-360 is a highly effective microbiocide for use in controlling the growth of fungi and bacteria found in water based drilling muds. It is especially useful in muds containing starches, Xanthanate gums, and wood sugars. The uncontrolled growth of these fungi and bacteria can cause increased corrosion, undesirable odors, and degradation of the drilling mud, especially fluid loss properties.

AQUATREAT DNM-360 is used at the rate 0.83 to 4.17 gallons per 100 bbl. of mud. (0.017% to 0.083%). It can be used directly from the shipping container or pre-diluted with water. It can be put in through the mud hopper or added to the pump suction.

SECONDARY AND TERTIARY PETROLEUM RECOVERY

AQUATREAT DNM-360 is a highly effective microbiocide for use in controlling the growth of fungi and bacteria found in secondary and tertiary petroleum recovery waterflood systems.

AQUATREAT DNM-360 can be injected directly from the shipping container. It should be thoroughly mixed into the produced water, fresh or salt water or commingled water or the secondary or tertiary oil recovery waterflood systems for effective microorganism control. It may also be diluted with water for injection.

AQUATREAT DNM-360 is used at the rate of 1 pint per 100 bbl. of water for growth inhibition of *Bacillus Cereus* and *Desulfovibrio desulfuricans* and 0.9 to 1.5 gallons per 100 bbl. of water for heterotropic bacteria including *Pseudomonas*. It is also effective against many fungi such as *Aspergillus*, *Penicillium* and *Trichoderma* at the 1 pint per 100 bbl. of water.

PAPER MILLS

Dosage will vary from 0.08 to 1.67 pounds (0.03 to 0.67 quarts) of **AQUATREAT DNM-360** per ton of finished paper depending on the type of stock, complexity of the system, quality of raw water, and type and degree of contamination.

Feeding

AQUATREAT DNM-360 may be drip fed continuously from the drum or fed by suitable chemical pumps such as adjustable proportioning types; variable speed, positive displacement types; or by the reciprocating type. This product should be fed as early as possible in the system at such points including the hydropulper, machine chest or broke system.

AQUATREAT DNM-360 can be used to control slime on machines which can make paper and paperboard for use in food packaging.

BEET SUGAR MILLS

AQUATREAT DNM-360 should be fed directly into the raw juice during sugar extraction of beets to keep equipment free of bacterial slime deposits. It is to be used at the rate of 8.3-16.6 ppm of raw beets sliced, and fed continuously into the pulp press water tank with a metering pump. The maximum rate to be fed is 16.6 ppm. Refer to composite table 1 for the proper dosage in milliliters and ounces of **AQUATREAT DNM-360** to be used per minute.

CANE SUGAR MILLS

AQUATREAT DNM-360 is a liquid which should be fed directly into the cane juice so that the treated juice circulates to all parts of the mill tandem. The point or points of addition will depend on mill design. Frequently the dosage will be split between the crusher juice and juice from the last mill. The best addition point is to the juice which is circulated back to the crusher from the first mill. Do not add this product to the maceration water.

AQUATREAT DNM-360 should be fed continuously at the rate of 8.3-16.6 parts of product per million parts of cane ground per day. 8.3 ppm. of product is the standard dosage. This may be raised up to a maximum of 16.6 ppm, if necessary. Conditions warranting, some increase would be warranted when grinding cane damaged through freezing, poor weather or delays between cutting and grinding. See feeding directions which follow.

Proper feed of **AQUATREAT DNM-360** is best obtained through the use of a chemical feed pump such as the adjustable proportioning type; the variable speed, positive displacement type; or the reciprocating type. The required dosage will depend on the average daily rate of cane ground. Refer to composite table 1 for the proper dosage in milliliters and ounces of **AQUATREAT DNM-360** to be used per minute.

Do not exceed feed rate of 33.3 gallons (32.7 pounds) of product per 1000 short tons of cane ground per twenty-four hours.

The use of **AQUATREAT DNM-360** does not replace good housekeeping. This should include regular cleaning at least once per shift. Regular hosing of mills bagacillo conveyors, and screens with hot water and steam is essential for maintaining efficient control of microbiological slime and sucrose losses.

COMPOSITE TABLE 1

SHORT TONS OF CANE GROUND OR RAW BEETS SLICED PER DAY	RATE OF FEED OF AQUATREAT DNM-360			
	8.3 ppm		16.6 ppm	
	ml/min	oz/min	ml/min	oz/min
1,000	4.6	0.155	9.2	0.310
2,000	9.2	0.310	18.3	0.620
3,000	13.7	0.465	27.5	0.929
4,000	18.3	0.620	36.7	1.240
5,000	22.9	0.775	45.8	1.549
6,000	27.5	0.929	55.0	1.859
7,000	32.1	1.084	64.2	2.169
8,000	36.7	1.239	73.3	2.478
9,000	41.2	1.394	82.5	2.787
10,000	45.8	1.549	91.7	3.098

For Chemical Emergency

Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC — Day or Night

1-800-424-9300

WARRANTY STATEMENT

Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material, when such use and/or handling is contrary to label instructions.

