PRECAUTIONARY ST. **ENTS** Hazard to Humans and Domestic Animals.

WARNING Causes eye and skin irritation. Do not get in eyes, or skin.

or on clothing. Wear donnies or face shield, rubber gloves and protective clothing (hats, long sleeve shirt, long pants and boots) when handling. Harmful or fatal if swallowed. Avoid contamination of food and feedstuffs.

This product is a primary skin irritant and skin sensitizer in albino guinea bigs by the modified Bueh. ; method.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not apply (or use) in estuarine oil fields where culling fluids (muds) are discharged in the surface water. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not discharge treated effluent into lakes, streams, ponds or public waters unless in accordance with an NPDES permit. For guidance contact your Regional Office of the Environmental Protection Agency.

AQUATREAT DNM-80 is a highly effective bactercide and fungicide for use in controlling the growth of bacteria and fungi in industrial recirculating water cooling towers, evaporative condensers, air washers, paper mills, crilling fluids, and secondary and tertiary petroleum recovery systems.

In addition, AQUATREAT DNM-80 is a highly effective algaecide for use in controlling the growth of algae found in air washers (except in California), industrial recirculating water cooling towers, and evaporative condensers.

STORAGE AND DISPOSAL

1. PROHIBITIONS

Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

2. PESTICIDE DISPOSAL

Pesticide wastes are toxic, Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law, If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

3. CONTAINER DISPOSAL

When product is supplied in a water soluble bag within a plastic outer bag, completely empty plastic bag into application equipment. Do not tear or open water solubie bag. Then dispose of empty plastic bag in a sanitary landfill or by incideration, or, if allowed by State and local authorities, by burning. If burned, stay out of smoke.

When product is supplied in a single water soluble bag, add hag and contents directly to application equipment. Do not tear or open water soluble bag. In this case there is no container

te dispose of.
PLASTIC COST ANNI S: Triple timbe equivalent,. Then offer for recycling or reconditioning, of puncture are alspose of in esamisary conditions of allowed to other and to a state of the same Out of series.

4. GENERA!

Consult federal, state or local disposal authorities for approved alternative procedures

AQUATREAT DNM-80

ACTIVE INGREDIENTS Sodium Dimethyldithiocarbamate 40% Nabam (Disodium Ethylene Bis-dithiocarbamate) 40% INERT INGREDIENTS 20% TOTAL 100%

BEST AVAILABLE COPY

KEEP OUT OF REACH OF CHILDREN

WARNING

STATEMENT OF

PRACTICAL TREATMENT

In case of contact, immediately flush eves or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse.

If swallowed, drink promptly a large quantity of egg whites, gelatin solution or if these are not available, drink large quantities of water. Call a physician immediately.

See Side Panel For C 400 pional Plecautionary Statements.

APR 03 1992

Under the Federal Insecticide. Fungicide, and Rodenticide Act, as amended, for the pesticide d under 3/9/0-30 EPA Reg. No.



Manufactured by:

ALCO CHEMICAL DIVISION National Starch and Chemical Company

P.O. Box 5401

909 Mucher Drive


Chattanoosa, Tennessae 37406


Phone, 615-629-1405

E.P.A. Establishment No. 3151G-TN-1

E.P.A. Redistration No. 31915-20

Cooling Towers and Air Washers





Pulp & Paper


DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

This product must not be used on any food of field CEPT crop or to formulate any product for crop or to formulate any product for use on any food or field crop.

Drilling Fluids







WORKOVER AND COMPLETION FLUIDS

AQUATREAT DNM-80 is a highly effective microbiocide in controlling the growth of fungi and bacteria found in water based workover and completion fluids. AQUATREAT DNM-80 is used at the rate of 0.63-2.5 APR 03 1992 pounds per 1000 gallons (0.0075%-0.03%) of workover

Under the Federal Insecticide. Fungicitic, and Rodenticide Act. os amended, for the pesticide registered under 31910-20 PA Reg. No.

DRILLING FLUIDS

AQUATREAT DNM-80 is a highly effective microbiocide for use in controlling growth of fungi and bacteria found in water based drilling muds. It is especially useful in muds containing starches. Xanthanate gums, and wood sugars. The uncontrolled growth of these fungi and bacteria can cause increased corrosion, undesirable odors, and degradation of the drilling mud, especially fluid loss properties.

AQUATREAT DNM-80 is used at the rate of 3 to 15 pounds per 100 bbl. of mud (60-300 ppm). It can be used directly from the shipping container or precissolved in water. It can be put in through the mud hopper or added to the pump suction.

SECONDARY AND TERTIARY PETROLEUM RECOVERY

AQUATREAT DNM-80 is a highly effective microbiocide for use in controlling the growth of fungi and bacteria found in secondary and tertiary petroleum recovery waterflood systems.

AQUATREAT DNM-80 should be thoroughly dissolved into the produced water, fresh or salt water or commingled water or the secondary or tertiary oil recovery waterflood systems for effective micro-o.ganism control. It may also be predissolved in water for injection.

AQUATREAT DNM-80 is used at the rate of 0.3 lbs. per 100 bbl. of water for growth inhibition of Bacillus Cereus and Desulfovibrio desulfuricans and 3.15 to 5.23 (pounds per 100 bbl. of water for heterotropic bacteria including Pseudomonas. It is also effective against many fungi such as Aspergillus Penicillium and Trichoderma at the 0.3 pound per 100 bbl, of water

> For Chemical Emergency Spill, Leaks, Fire, Explosive, or Accident Call CHEMTREC - Day or Night 1-800-424-9300

Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material, when such use and/or handling is contrary to label instructions.

INDUSTRIAL RECIRCULATING WATER **COOLING TOWERS AND EVAPORATIVE CONDENSERS**

Dosage for industrial recirculating water cooling towers or evaporative condensers will depend on the condition of the system prior to treatment initiation. Systems which are heavily contaminated should be cleaned first. Apply AQUATREAT DNM-80 to the cleaned system or when growth is first noticed, according to the following schedule:

INITIAL DOSE: Apply 4.8 ounces — 1 pound of product per each 1000 gallons of water in the system (36-120 ppm). This dose may be repeated once, twice or three times weekly or as required to control the growth of slime-forming organisms.

SUBSEQUENT DOSE: When microbial control is evident add 0.8-1.6 ounces of AQUATREAT DNM-80 per 1000 gallons of water (6-12 ppm) in the system every three days or as needed.

AIR WASHERS

In treating air washer systems preclean by introducing a suitable detergent solution into the system and allow air washers to run with fan off for two hours. Check all nozzies and manually clean those that are plugged.

DOSAGE: Follow dosage and directions under Industrial Recirculating Water Cooling Tower and Evaporative Condensers.

PAPER MILLS

(NOT APPLICABLE IN CALIFORNIA)

Dosage will vary from 0.04 to 0.75 pounds of AQUA-TREAT DNM-80 per ton of finished paper depending on the type of stock, complexity of the system, quality of raw water, and type and degree of contamination.

FEEDING: AQUATREAT DNM-80 should be applied as early as possible in the system at such points including the hydropulper, machine chest or broke system.

AQUATREAT DNM-80 can be used to control slime on machines which make paper and paperboard for use in food packaging.

FRACTURING FLUIDS

For the control of bacteria in fracturing fluids, add 0.3 to 1.6 lbs. AQUATREAT DNM-80 per 1000 gallons of fracturing fluids (33-160 ppm).

