

31910-20 10-2-2000 1/3
PRECAUTIONARY STATEMENTS
Hazards to Humans and Domestic Animals

WARNING

Causes eye and skin irritation. Do not get in eyes, on skin or on clothing. All industrial workers applying this product must wear coveralls over a long-sleeved shirt and long pants, shoes, socks, and chemical-resistant gloves. During dilution, a chemical-resistant apron and goggles or face shield must also be worn. Harmful or fatal if swallowed. Avoid contamination of food and feedstuffs.

This product is a primary skin irritant and skin sensitizer in albino guinea pigs by the modified Buehler method.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not apply (or use) in estuarine oil fields where drilling fluids (muds) are discharged in the surface water. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

AQUATREAT DNM-80 is a highly effective bactericide and fungicide for use in controlling the growth of bacteria and fungi in industrial recirculating water cooling towers, evaporative condensers, air washers, paper mills, drilling fluids, and secondary and tertiary petroleum recovery systems.

In addition, **AQUATREAT DNM-80** is a highly effective algacide for use in controlling the growth of algae found in air washers (except in California), industrial recirculating water cooling towers, and evaporative condensers.

STORAGE AND DISPOSAL

1. PROHIBITIONS

Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

2. PESTICIDE DISPOSAL

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

3. CONTAINER DISPOSAL

When product is supplied in a water soluble bag within a plastic outer bag, completely empty plastic bag into application equipment. Do not tear or open water soluble bag. Then dispose of empty plastic bag in a sanitary landfill or by incineration, or, if allowed by State and local authorities, by burning. If burned, stay out of smoke.

When product is supplied in a single water soluble bag, add bag and contents directly to application equipment. Do not tear or open water soluble bag. In this case there is no container to dispose of.

PLASTIC CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

4. GENERAL

Consult federal, state or local disposal authorities for approved alternative procedures.

AQUATREAT DNM-80

ACTIVE INGREDIENTS

Sodium

Dimethyldithiocarbamate 40%

Nabam (Disodium Ethylene

Bis-dithiocarbamate) 40%

INERT INGREDIENTS 20%

TOTAL 100%

KEEP OUT OF REACH OF CHILDREN
WARNING

FIRST AID


IF IN EYES	<ul style="list-style-type: none">Hold eye open and rinse slowly and gently with water for 15-20 minutes.Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.Call a poison control center or doctor for treatment advice.
IF ON SKIN OR CLOTHING	<ul style="list-style-type: none">Take off contaminated clothing.Rinse skin immediately with plenty of water for 15-20 minutes.Call a poison control center or doctor for treatment advice.
IF SWALLOWED	<ul style="list-style-type: none">Call a poison control center or doctor immediately for treatment advice.Have person sip a glass of water if able to swallow.Do not induce vomiting unless told to do so by the poison control center or doctor.Do not give anything by mouth to an unconscious person.
IF INHALED	<ul style="list-style-type: none">Move person to fresh air.If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible.Call a poison control center or doctor for further treatment advice.

HOT LINE NUMBER

Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also call 1-888-456-6218 day or night for emergency medical treatment information.

See Side Panel For

Additional Precautionary Statements.



Manufactured by:

ALCO CHEMICAL DIVISION

National Starch and Chemical Company

909 Mueller Dr. • P.O. Box 5401 • Chattanooga, TN 37406

423-629-1405

FAX 423-698-8723


E.P.A. Establishment No. 31910-TN-1

E.P.A. Registration No. 31910-20

Net Contents: Powder

See Markings on Top of Container for Net Weight

Cooling Towers and Air Washers



2/3

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

This product must not be used on any food or field crop or to formulate any product for use on any food or field crop.

INDUSTRIAL RECIRCULATING WATER COOLING TOWER AND EVAPORATIVE CONDENSERS

Dosages for industrial recirculating water cooling towers or evaporative condensers will depend on the condition of the system prior to treatment initiation. Systems which are heavily contaminated should be cleaned first. Apply **AQUATREAT DNM-80** to the cleaned system or when growth is first noticed according to the following schedule:

INITIAL DOSE: Apply 4.8 ounces-1 pound of product per each 1000 gallons of water in the system (36-120 ppm). This dose may be repeated once, twice or three times weekly or as required to control the growth of slime-forming organisms.

SUBSEQUENT DOSE: When microbial control is evident add 0.8-1.6 ounces of **AQUATREAT DNM-80** per 1000 gallons of water (6-12 ppm) in the system every three days or as needed.

AIR WASHERS

In treating air washer systems preclean by introducing a suitable detergent solution into the system and allow air washers to run with fan off for two hours. Check all nozzles and manually clean those that are plugged.

DOSAGE: Follow dosage and directions under Industrial Recirculating Water Cooling Tower and Evaporative Condensers.

PAPER MILLS


(NOT APPLICABLE IN CALIFORNIA)

Dosage will vary from 0.04 to 0.75 pounds of **AQUATREAT DNM-80** per ton of finished paper depending on the type of stock, complexity of the system, quality of raw water, and type and degree of contamination.

FEEDING: **AQUATREAT DNM-80** should be applied as early as possible in the system at such points including the hydropulper, machine chest or broke system.

AQUATREAT DNM-80 can be used to control slime on machines which make paper and paperboard for use in food packaging.


Drilling Fluid



Secondary and Tertiary Oil Recovery



Pulp & Paper



3/3

FRACTURING FLUIDS

For the control of bacteria in fracturing fluids, add 0.3 to 1.6 lbs. **AQUATREAT DNM-80** per 1000 gallons of fracturing fluids (33-160 ppm).

WORKOVER & COMPLETION FLUIDS

AQUATREAT DNM-80 is a effective microbiocide for use in controlling the growth of fungi and bacteria found in water based workover and completion fluids. **AQUATREAT DNM-80** is used at the rate of 0.9-3.6 pounds per 1000 gallons of workover or completion fluids.

DRILLING FLUIDS

AQUATREAT DNM-80 is a effective microbiocide for use in controlling the growth of fungi and bacteria found in water based drilling muds. It is especially useful in muds containing starches, zanthanate gums, and wood sugars. The uncontrolled growth of those fungi and bacteria can cause increased corrosion, undesirable odors, and degradation of the drilling mud, especially fluid loss properties.

AQUATREAT DNM-80 is used at the rate of 3 to 15 pounds per 100 bbl. of mud (60-300 ppm). It can be used directly from the shipping container or predissolved in water. It can be put in through the mud hopper or added to the pump suction.

SECONDARY AND TERTIARY PETROLEUM RECOVERY

AQUATREAT DNM-80 is a effective microbiocide for use in controlling the growth of fungi and bacteria found in secondary and tertiary petroleum recovery waterflood systems.

AQUATREAT DNM-80 should be thoroughly dissolved into the produced water, fresh or salt water or commingled water or the secondary or tertiary oil recovery waterflood systems for effective microorganism control. It may also be predissolved in water for injection.

AQUATREAT DNM-80 is used at the rate of 0.3 lbs. per 100 bbl. of water for growth inhibition of *Bacillus Cereus* and *Desulfovibrio desulfuricans* and 4.1-6.7 pounds per 100 bbl. of water for heterotrophic bacteria including *Pseudomonas*. It is also effective against many fungi such as *Aspergillus Penicillium* and *Trichoderma* at the 0.3 pound per 100 bbl. of water.

PASTEURIZER COOLING WATER SYSTEMS

(NOT APPLICABLE IN CALIFORNIA)

Dosage will depend on the condition of the system prior to treatment initiation. Systems which are heavily contaminated should be cleaned first. Apply **AQUATREAT DNM-80** to the cleaned system or when growth is first noticed, according to the following schedule:

INITIAL DOSE: Apply 4.8 ounces-1 pound of product per each 1000 gallons of water in the system (36-120 ppm). This dose may be repeated once, twice or three times weekly or as required to control the growth of slime-forming organisms.

SUBSEQUENT DOSE: When microbial control is evident, add 0.8-1.6 ounces of **AQUATREAT DNM-80** per 1000 gallons of water (6-12 ppm) in the system every three days or as necessary.

ACCEPTED

OCT 02 2000

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 31910-20

For Chemical Emergency

Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC — Day or Night

1-800-424-9300

Seller makes no warranty expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material, when such use and/or handling is contrary to label instructions.