

COMPOSITION

	Percent by	_
Active ingredient	30.0	percent
Poly (oxyethylene (dimethyliminio) ethylene (dimethyliminio) ethyler	ne	
dichloride)		percent
Inert ingredient		
Weight per gallon		
Weight of active ingredient		
per gallon	2.67	pounds

CAUTION

Keep out of the reach of children

Harmful if swallowed. Avoid contact with skin and eyes. In case of contact flush with plenty of water for at least 15 minutes. If eye irritation persists get medical attention. Avoid contamination of food.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Do not contaminate water by cleaning of equipment or disposal of waste. Use only as directed on label. Do not reuse container. Destroy when empty.

EPA Reg. No. 31964-3

GESSCOCIDE 30

APPLICATION—GESSCOCIDE 30 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 1.90 to 4.75 fluid ounces of GESSCOCIDE 30 per 1000 gallons of water to provide a concentration of 16 to 40 parts per million of GESSCOCIDE 30 based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 0.47 to 4.75 fluid ounces of GESSCOCIDE 30 per 1000 gallons of water (4 to 40 parts per million of GESSCOCIDE 30) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

GESSCO Sales Division

Gulf Engineering Co., Inc.

NEW ORLEA

- HOUSTON - NEW IBERIA - SI EV