



READY TO USE
CLEAR . PAINTABLE . WATER REPELLENT
WOOD
PRESERVATIVE

Protects wood and insulation, controls termites, minimizes shrinkage and swelling. Meets N.W.M.A. standards for millwork preservative and Federal Specification TT-W-1452E.

WARNING: KEEP OUT OF REACH OF CHILDREN

See side panel for other warnings.

ONE YEAR WARRANTY AND EXCLUSIONS

NO LONGER THAN ONE YEAR
ACTIVE INGREDIENTS

ACTIVE INGREDIENTS	
Proprietary	4.47%
Terpenes, Phenols & Related Compounds*	52%
Misc. Spices	8.05%
TOTAL	100.00%

EPA Reg. No. 62

CANTON CHEMICAL COMPANY, INC.
 100 E. Main Street
 CANTON, N.C. 28716

CONTENTS 1 U.S. GALLON

WARNING

MADE FATALE IF SWALLOWED. INHALED OR ABSORBED THROUGH SKIN CAN CAUSE SEVERE IRRITATION.
 MAY DAMAGE OR DESTROY HUMAN EYES AND SKIN.
 Do not breathe spray. Must use only with adequate ventilation. Do not get spray in eyes or on skin or in clothing. Wash thoroughly after handling.

Wear protective clothing and rubber gloves when handling this freshly treated lumber.

Do not use near heat or store near heat or open flame.

FIRST AID: If swallowed induce vomiting by sticking finger down throat or by taking small or strong salty water to drink. Repeat until solution is clear. Call a physician. Never give anything by mouth to an unconscious person.

FIRST AID: In case of contact, wash skin with soap and water. For eyes, flush with water for at least 15 minutes and get medical attention.

NOTE TO PHYSICIAN: This product is a metabolic stimulant. Causes hypothermia. Treat symptomatically.

This product is toxic to fish and wildlife. Keep out of lakes, streams and rivers. Do not contaminate soil when not in use. Do not pollute water by clearing of equipment or discarding wastes. Apply this product only as specified on this label.

Maximum exposure of adequate ventilation is not in order. Do not use near furnaces or any other source of heat which may ignite the product and cause a fire or explosion.

LIMIT OF WARRANTY AND LIABILITY

This product is warrantied to be free from defects in materials and workmanship for one year from the date of manufacture. The manufacturer's liability for damages resulting from the use of this product is limited to the cost of repair or replacement of the damaged material. The manufacturer shall not be liable for any incidental or consequential damages resulting from the use of this product. The manufacturer shall not be liable for any damage caused by the user or buyer of the product if such damage is caused by the user or buyer's negligence or carelessness. The manufacturer and/or users are deemed to have accepted the terms of this notice which may not be varied by any verbal or written agreement.



DIRECTIONS FOR USE

This product is a clear oil-based sealant useful for the protection of wood against tanus growths which cause rot and stain termites. It is a power post beetle and carpenter ants and contains water repellents found in the control of shrinking, swelling and checking grain raising and warping.

WOOD PRESERVATION AND DIMENSIONAL CONTROL

For best results this product should be applied so as to effect maximum penetration into the wood and heavy absorption especially at joints and where wood grain exists. A 3-minute immersion period is recommended for end grain. For dimensional treatments, complete saturation of the wood in the solution is preferred, except that 1/2 to five minutes per face of fastness. For the control of insects, a change of shrinkage and swelling, the treatment of the end grain is most important since the insect picks up there a factor 10 to a thousand times greater than on the flat or edge grain surface for many species of wood.

Where open tank treating is impractical as in the case of an existing structure, two heavy brush applications of this product should be applied, cutting end and removing all old and loose wood two feet beyond any visible evidence of decay. All wood should be normally dry and the framing or cutting completed before application. Coverage is approximately 1/2 to 10 square feet per gallon for brush application.

This product is also good for application to wood for the control of termites, powder post beetles and carpenter ants. In all of these cases dimensional control in the areas of the wood contacted by the solution. Therefore, thorough treatments is essential to good control.

TERMITICIDE CONTROL: For protection of new wood products, construction, etc., in structures. Care must be exercised that the solution does not come in contact with paper, insulation, drywall, gypsum board, other substances of that nature, and any materials which contain starch, plastic or other surfaces. Treatment of these items is subject to loss of strength.

POWDER POST BEETLE CONTROL: Treated wood products should be treated with 1/2 to 10 square feet per gallon for brush application. Allow 1/2 hour to 1/2 day for absorption, minimum of 5 minutes per face of fastness. Since it is a power post beetle dimensional control after treatment of floors, furniture, etc., the floor, furniture, etc., items after treatment with a heavy-duty paste wax after the solvent has evaporated is necessary to insure against insect attack.

CARPENTER ANTS: This product is not effective unless the termite is controlled by insecticides. The carpenter ant is a social insect and cannot live without its nest. Destroying the nest is the best way to control carpenter ants. If the nest is located in the ground, treatments of areas around the nest are effective.

NOTICE

Avoid contamination of feed or foodstuffs.

Do not reuse container. Return to drum recycler or destroy and bury at a safe place. Do not contaminate water by cleaning equipment or discs, hoses, waste and containers. Treated sawdust and other wood wastes should not come in contact with birds, pets, animals or be buried as much where it will come in contact with animals or plant life.

ACCEPTED

AUG 19 1975

Under Signature	At Address
BB Corp.	BB Corp.
Registered Agent	BB Corp.
BB Reg. No.	BB Reg. No.