

PM21

32259-10

173

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

263851 / 300
6 / 17

JUL 30 1990

Mr. Harry Greenberg
Hoboken Paints, Inc.
40 Industrial Road
P.O. Box 866
Lodi, NJ 07644-0420

Dear Mr. Greenberg:

Subject: Amended Labeling
Wood Last/Weather-Life Clear Wood Preservative
EPA Registration No. 32259-10
Your Submission Dated March 9, 1990

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act, as amended, is acceptable with the following comments:

1. Under Environmental Hazards, change the last sentence to "Do not contaminate water when disposing of equipment washwaters" for both labels.

2. On the Weather-Life label, change the statement "can be used indoors" to "Treated wood can be used indoors or outdoors" or delete the statement.

Stamped copies of the labels are enclosed.

Sincerely yours,

SL

Susan T. Lewis
Product Manager (21)
Fungicide-Herbicide Branch
Registration Division (H7505C)

Enclosure

H7505C:J. Fairfax:jl:7/24/90

CONCURRENCES

| SYMBOL | SURNAME | DATE | | | | | |
|--------|---------|------|--|--|--|--|--|
| | | | | | | | |

BEST AVAILABLE COPY

PERGAMENT PERGAMENT PERGAMENT P

WEATHER-LIFE®
PAINTABLE

MEETS THESE SPECS

CLEAR

(METALLIC ZINC CONTENT 2%)

ACTIVE INGREDIENTS
Zinc Naphthenate
Total
WEIGHT PER GALLON
METRIC 3.785 LITERS

WOOD

CONTAINS PETROLEUM

KEEP OUT OF REACH OF CHILDREN

CAUTION!
HARMFUL IF SWALLOWED
OR ABSORBED THROUGH SKIN
See additional statements on label

PRESERVATIVE

EXTERIOR

INHIBITS TERMITE INFESTATION • WATER
MILDEW & ROT RESISTANT • USE ABOVE & BELOW

1 GALLON 3.785 LITERS

EPA REG. NO. 3225



19151 82881

See COMMENTS
in EPA Letter Dated

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended for the pesticide registered under EPA Reg. No.

9/15/79 (REV) NAK (8/79)



WEATHER-LIFE CLEAR WOOD PRESERVATIVE

Especially formulated to:

Extend the useful life of wood surfaces • Maintain their natural beauty for years longer
Repels water, protecting against rotting and warping • Inhibits mildew and fungal growth
Penetrating base for paint, varnish, enamel • Protects against termite infestation • Prepares wood for below grade use

FOR BEST RESULTS

Use on clean, dry, unfinished lumber. Use the total immersion method, where possible, allowing all surfaces complete saturation. Wood to be used below grade or in contact with soil should be immersed 48 hours. All other lumber products one to thirty minutes depending on thickness.

For wood unable to be immersed, apply liberally with brush or roller. Give two coats to below grade or soil contact wood. WOOD PRESERVATIVE may be painted over in 72 hours. Allow four weeks before applying stain finishes.

Product coverage varies greatly with type and porosity of wood, and the method of application.

Clean all tools with mineral spirits or turpentine

Remove WOOD PRESERVATIVE from glass promptly with paint thinner to avoid staining.

Wood rot protection of interior wood is only needed where frequent or prolonged wetting of wood is a problem.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Preparation before treatment should include machining, cutting, sanding and fastening as required. Wood must be clean, dry, and free from previous finishes. Do not use steel wool before applying WOOD PRESERVATIVE.

Can be used indoors or outdoors.

Fence posts, poles, foundation timbers, and other heavy wooden members should be free of bark, dry, and well seasoned, and immersed in the product for a period of 12-48 hours to be effectively preserved.

This product is not recommended for feed or potable water structures or livestock and dairy animals facilities or wood which will be in frequent or prolonged contact with skin.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS:

CAUTION! Causes skin irritation. Do not get in eyes, on

skin or on clothing. Harmful if swallowed or absorbed through skin. Do not breathe vapor or spray mist. Wear protective clothing and rubber gloves when handling the freshly treated lumber. Use only with adequate ventilation.

FIRST AID: IF IN EYES: Flush with plenty of water. Get medical attention.

IF ON SKIN: Wash with plenty of soap and water. Get medical attention. Remove and wash contaminated clothing before reuse.

IF SWALLOWED: Do not induce vomiting. Call physician immediately. Never give anything by mouth to an unconscious person.

ENVIRONMENTAL HAZARDS: This product is toxic to fish. Do not apply directly to water. Do not contaminate water by cleaning of equipment, or disposal of wastes.

PHYSICAL OR CHEMICAL HAZARDS: COMBUSTIBLE. This product may ignite. Keep contents and treated articles away from flame, food and living plants. Do not use, pour, spill, or store near heat or open flame. Vapors will cause injury if adequate ventilation is not insured. Do not use or mix this product indoors or in any other confined areas where vapors may concentrate and cause injury to plant or animal life.

STORAGE AND DISPOSAL: Store at temperatures between 40° F. and 100° F. If the product has been spilled or is leaking remove the source of the spill or leak. Recover free liquid. Spread absorbent. Then pick up and place in containers. Then, where applicable, wash area with detergent and water. Store product in the original container only. Keep container closed when not in use. Do not use empty container. Wrap container and put into trash collection.

PERGAMENT PAINTS, INC.

LODI, N.J. 07644